BMES MÜHENDİSLİK DIŞ TİCARET LTD. ŞTİ.



THE SAFETY BOOK: THE ESSENCE

FROM HEAD TO TOE


BMES INNOVATES,
DESIGNS, STANDARDISES
TO SUPPLY A GLOBAL
OFFER THAT MEETS YOUR
NEEDS

BMES cares about well-being at the workplace and researches more innovative solutions in terms of comfort, design and technicality, to protect you in all circumstances.

Each of our product families is worked to provide products that meet European standards (and for some U.S. standards).

Our range managers are inspired by sport and recreation to develop easy to wear PPE at work everyday.

All BMES PPE solutions are offered at the best value: need/ quality/ price







A SEGMENTATION FOR DESIGNING PRODUCTS AND RANGES:



KNOW THE RISKS





ANALYZE THEM IN THE WORKERS **ENVIRONMENT AND CONSTRAINTS**





TOOL: **SEGMENTATION**





CONSTRUCTION **OF A SUITABLE PRODUCT OFFER**











areas, risks, levels of range) is the foundation on which is built the strategy of the range and future products are determined and designed, which meet the constraints and risks in the workplace.



SEGMENTATION TO MEET THE NEEDS OF USERS



LISTEN TO THE USER



EVALUATE THEIR RISKS AND THEIR NEEDS



TOOL: **SEGMENTATION**



THE EPI ADAPTED SOLUTION

Our multi key input segmentation (business areas, risks, levels of range) facilitates the advice from the distributor toward their user customer:

- Respond more quickly and effectively to the needs of the user customer.
- Guide the customer in the same way in the 5 product families

THE KEY INPUTS OF THE SEGMENTATION

THE BUSINESS AREAS

	AGRICULTURE/ GREEN AREAS	Farmers - Woodcutters - Gardeners		SERVICES / LOGISTICS	Logistics - Transportation - Airport - Distribution
	CONSTRUCTION/ CIVIL ENGINEERING	Structural work - Construction		HYGIENE ENVIRONMENT	Food industry - Pharmacy - Hospitals - Restaurants - Communities
A	SECOND WORK/CRAFTSMAN	Electricians - Plumbers - Heating specialists - Painters		OIL/GAS	Petrochemical industry - Refinery - Off shore - Exploration - Pipelines
ΑÎ	HEAVY INDUSTRY	Metal construction - Petrochemical	<u>×</u>	MINING	Mines (exploration, extraction) -Stone-pit
444	LIGHT INDUSTRY	Automotive - Aerospace - Industrial Subcontracting	林	WIND ENERGY	

• RISK





NOISE









SHOCK

FALL



CUTTING /

PERFORATION













BIOLOGICAL CHEMICAL PARTICLES









READABLE AND EFFECTI

• LEVELS OF THE RANGE

High Tech products for specialized uses

Powerful multi-purpose products

Standard multi-purpose products

PREMIUM

EVOLUTION

ESSENTIAL

BMES______INOVATION



Product providing the look and/ or the particular design of Delta Plus: the pleasure of wearing PPE.

BASEBALL DIAMOND

 Comfortable to wear with its unique and functional look



D-MACH

 Look, comfort, durability: Mach quality from Delta Plus



RANDERS

 Pleasant in its look and its comfort in mid-season



SPORTSWEAR

 Easy to wear with its look and comfort



DELTA EASYFIT

Practical Solutions for a rapid introduction and/ or removal of the PPE.

GRANITE PEAK

- Easy to position.
- Quick adjustment with ROTOR® system.
- Light and easy to carry



DIAMOND V UP

- Easy to position.
- Quick adjustment with ROTOR® system



X-RUN

- Easy to put on and take off.
- Saving time in the lacing and unlacing





Adhesion techniques for safe movements and/ or steps.

AS0

 Flexible arms in bi-material = anti slip effect



 Safety provided on ladders, soft ground, slippery floors, hot floors etc...





Technological advances for a protection higher than required by the standard.

SUPER QUARTZ

 High multiple hazard and multiple environment protection level



Anatomical and/ or ergonomic solutions for maximum comfort and ergonomics.

KISKA

 The lightest safety glasses in the world

APOLLON

- High level of comfort by its flexibility
- Waterproof while limiting perspiration.
- Great dexterity



- Comfortable and easy to adjust as a result of its design
- Economy through innovation

HAR32 ANATOM

VIRAGE S1P

· High level of comfort with

and breathability

flexibility, stability, lightness

 Innovative ergonomics for a greater comfort and enhanced security



HAR35 EOLIEN

 Innovative ergonomics for a greater comfort and enhanced security





Heat shields

for regulating the temperature of the body or a part of the body.

GRANITE WIND

 Good head ventilation due to a large ventilation area



NORDLAND

 High insulation for low temperatures with appropriate materials and design




ICEBERG

 High insulation for low temperatures with appropriate materials and design



HEAD PROTECTION




HEARING PROTECTION Suitable protection PIT-STOP 38 YAS MARINA 39 Ear defenders SILVERSTONE 2 39 INTERLAGOS 40 MAGNY-COURS 42 MAGNY HELMET 42 CONICFIR050 44 Earplugs CONICMOVE01 44 CONICMOVE01BR 44 SEPANG 2 43 45 CONICCO200 CONIC DISPLAY 45 SUZUKA 2 43 SPA 3 43 45 CONIC200 CONIC500 45

		70		E C
100				
7		TO THE		7
4				
	P		17	VA
				×
				the

Suitable protection SPIDERMASK P3 X5 46 SPIDERMASK P2 X5 46 SPIDERMASK P2W X5 46 SPIDER REFILL FFP2 46 SPIDER REFILL FFP3 46 SPIDER REFILL FFP2W 46 48 M1200VPLUS 48 M9200 - ROTOR GALAXY 50 M9300 - STRAP GALAXY 50 M9000 A2 51 M9000 A2B2E2K2 51 M9000A2B2E2K2P3 51 M9000 A2P3 51 M9000 P3 51 M1300V2 49 M1200V 49 M1200VW 49 M1100V 49 M1300VB 49 49 M1200VB M6100 JUPITER 52 M6200 JUPITER 52 M6300 JUPITER 52 M6400 JUPITER 52 M6000 A1 53 53 M6000 A2 M6000 A1B1E1K1 53 M6000 PREP3 53 M6000 P2 53 M6000 P2 CLIP 53 M6000 P3 53 M1200 48 M1100 49 M1195B 49

RESPIRATORY PROTECTION

HEAD PROTECTION




Kit mines




Metallic front support for mining lamp and plastic hook on the back for lamp cable. Available on demand. Lamp not included.



Visor



Welding



Badge Holder



Helmet All our helmets have standard all for accessories. EVOLUTION ESSENTIAL BASEBALL GRANITE WIND **GRANITE PEAK** DIAMOND V UP SUPER QUARTZ QUARTZ UP IV QUARTZ UP III FORESTIER2 QUARTZ I ZIRCON I 0 COLOURS \bigcirc ADJUSTMENT VENTILATION ELECTRICAL INSULATION VAC VAC VAC VAC VAC 440 VAC 440 VAC 440 VAC MM MM MM MM MM MM MM MM MM -LD--LD--LD-LD +150°C +50°C +50°C +50°C +50°C +50°C TEMPERATURE **1**.10°C ELECTRICAL **A A A**

Bump cap





CUSTOMIZE YOUR SAFETY HELMETS!

- > The logo sent must be in vectorized format (.eps, .ai, or .pdf) and do not have different colour background of the chosen helmet.
- > For logos in colours, thanks to give us the pantone reference for each colour.
- > Warning: the colours of the logos can be slighty changed according to the colour of helmets. To have the same colour as your logo, we recommend to choose white helmets.
- > It is impossible to do gradient colours in pad printing.
- > Minimum of order: 240 pieces per colour for all orders out of Europe
- > Maximum number of colours: 4
- > The space to put the logo may not exceed dimensions shown on the schema below:




ZIRCON	QUARTZ - SUPER QUARTZ	GRANITE	BASEBALL DIAMOND
₹70 → YOUR LOGO \$ 40	₹70 ∀ YOUR LOGO ₹40	√70 ∀OURLOGO 40	VOURLOGO ♥40
Front Geo YOURLOGO \$\rightarrow{20}{20}\$	Front 60 707LOG0 +35	NOTICE: only front printing available	Front GO YOURLOGG #20
Back	Back		Back

HEAD PROTECTION

HEARING PROTECTION

Ear defenders and earplugs





HEAD PROTECTION

DIPOSABLE RESPIRATORY PROTECTION






Optional test of EN149: 2001 standard for clogging of dolomite dust
*The Assigned Protection Factor, might be different according local regulations.

** This list is indicative but not contractual and can not engage the responsibility of DELTA PLUS

REUSABLE RESPIRATORY PROTECTION







Advice: Change the filter after each use, or quicker if the atmosphere is polluted, humid and the air flow (or breathing) is high.







Article	Colours	Description	Standard	<u> </u>	
ASO CLEAR	Clear	Polycarbonate glasses. Sport design. Polycarbonate/ TPR bi-material arms:	<i>C &</i> EN166	EN170 UV 2C-1.2	v 100
ASO SMOKE	Smoke	Polycarbonate glasses. Sport design. Polycarbonate/ TPR bi-material arms: Flexible and non slip. D-Pad: Nose piece suitable for all body shapes.	1 FT KN/FT	30 g EN172 UV 5-3.1	x 100



EYEWEAR PROTECTION Safety glasses

FUJI2 CLEAR











UV400 Anti-mist Anti-scratch



FUJI2 GRADIENT











UV400 Anti-scratch



Article	Colours	Description	Standard	•	
FUJI2 CLEAR	Clear	Polycarbonate twin lens glasses. Twin material arms. Soft tips. Soft TPE nose	ANSI Z87.1 EN170 UV 2C-1.2 Z87+	00 -	100
FUJI2 GRADIENT	Gradient	piece.	EN166 1 FT / FT EN172 UV 5-1.4:5-1.7	· 29 g	x 100

THUNDER CLEAR













THUNDER SMOKE













Article	Colours	Description	Standard	<u> </u>	Ŷ
THUNDER CLEAR	Clear	Description Standard Ergonomic glasses. Polycarbonate lens. Sports look. Twin material arms. Soft tips. Soft, extra comfort TPE nose piece. EN170 UV 2C-1.2 EN172 UV 5-3.1	UV 2C-1.2	v 100	
THUNDER SMOKE	Smoke	Soft tips. Soft, extra comfort TPE nose piece.	1FT/FT	EN172 UV 5-3.1	X 100

EYEWEAR PROTECTION Safety glasses

















UV400









UV400 Anti-mist Anti-scratch





Colours Article Description Standard PACAYA LYVIZ EN170 UV 2C-1.2 Clear **C** € EN166 Polycarbonate single lens glasses. Integrated polycarbonate nose piece. PACAYA CLEAR Adjustable nylon arms. Side protection. 36 g x 100 ANSI Z87.1 PACAYA SMOKE EN172 Smoke UV 5-3.1

KISKA CLEAR


















The lightest safety glasses in the world. 20 g

Extra fine metal free frame

Ultra light frame





Treatments: Anti-mist, Anti-scratch, Antistatic & Non reflecting



Article	Colours	Description	Standard		<u>•</u>	
KISKA CLEAR	Clear	Ultra light one-piece polycarbonate glasses. Extra fine rimless frame and	C C EN166	EN170 UV 2C-1.2	00.5	100
KISKA SMOKE	Smoke	extra soft polycarbonate nose bridge. Suitable for long duration wear.	C E EN166	EN172 UV 5-3.1	20 g	X 100



EYEWEAR PROTECTION Safety glasses





LIPARI2 T5

















UV400 Anti-mist Anti-scratch



Article	Colours	Description	Standard		<u>^</u>	
LIPARI2 CLEAR	Clear	Polycarbonate single lens glasses. Adjustable and tilting nylon arms.	ANSI Z87.1	EN170 UV 2C-1.2	04 -	100
LIPARI2 T5	Shade 5	Spatula tips. Integrated TPE nose piece. Side protection.	EN166 1 FT / FT	EN169 UV 5	34 g	X 100

HEKLA









UV400 Anti-scratch



Article	Colours	Description	Standard		
HEKLA	Clear	Single lens polycarbonate over glasses. Side shields. Integrated polycarbonate nose piece. Flexible polycarbonate arms. Suitable for all types of prescription glasses.	C € EN166 EN170 UV 2C-1.2	36 g	x 100

VULCANO2 PLUS CLEAR VULCANO2 CLEAR 4 4 4 UV400 UV400 Anti-mist Anti-mist Anti-scratch Anti-scratch **VULCANO2 SMOKE** UV400 Anti-mist Anti-scratch Article Colours Description Standard **ANSI Z87.1** Z87+ VULCANO2 PLUS Clear **EN166** 1 FT K N / FT CLEAR EN170 UV 2C-1.2 Polycarbonate single lens glasses. Adjustable and tilting nylon arms. Spatula tips. Integrated TPE nose piece. Side protection. VULCANO2 CLEAR Clear 26 g x 100 ANSI Z87.1 Z87+ **EN166** 1 FT / FT EN172 UV 5-3.1 VULCANO2 SMOKE



KUNLUN





Article	Colours	Description		
KUNLUN	Clear	Single lens polycarbonate glasses. Confortable polycarbonate nose piece. Adjustable polycarbonate arms. Non-slip PVC tips. EN166 1FT/FT UV 2C-1.2 ANSI Z87.1	24 g	x 100

444

EYEWEAR PROTECTION Safety glasses

Article	Colours	Description	Standard	2	
MEIA CLEAR	Clear	Single lens polycarbonate glasses.Integrated polycarbonate nose piece. Polycarbonate arms. Non-slip PVC tips.	C€	24 g	x 100
A N		UV400 Anti-scratch	EN166 1 FT / FT EN170 UV 2C-1.2		
MEIA SMOKE	Smoke	Single lens polycarbonate glasses. Integrated polycarbonate nose piece. Polycarbonate arms. Non-slip PVC tips. UV400	EN166	24 g	x 100
		Anti-scratch The scratch	EN172 UV 5-3.1		
BRAVA2 CLEAR	Clear	Polycarbonate single lens glasses. Soft flat spatula type arms. Integrated polycarbonate nose piece. Easy to use with safety helmet and ear defenders. Side protection. UV400 Anti-scratch	ANSI Z87.1 287+ EN166 1FT/FT EN170 UV 2C-1.2	25 g	x 100
BRAVA2 YELLOW	Yellow	Polycarbonate single lens glasses. Soft flat spatula type arms. Integrated polycarbonate nose piece. Easy to use with safety helmet and ear defenders. Side protection. UV400 Anti-scratch	ANSI Z87.1 287+ EN166 1 FT / FT EN170 UV 2C-1.2	25 g	x 100
BRAVA2 SMOKE	Smoke	Polycarbonate single lens glasses. Soft flat spatula type arms. Integrated polycarbonate nose piece. Easy to use with safety helmet and ear defenders. Side protection. UV400 Anti-scratch	ANSI Z87.1 Z87+ EN166 1FT/FT EN172 UV 5-3.1	25 g	x 100

	Colours	Description	Standard		
KILIMANDJARO CLEAR	Clear	Polycarbonate single lens glasses. Adjustable nylon arms. Side protection. UV400 Anti-scratch	ANSI Z87.1 Z87+ EN166 1FT / FT EN170 UV 2C-1.2	32 g	x 100
KILIMANDJARO CLEAR AB	Clear	Polycarbonate single lens glasses. Adjustable nylon arms. Side protection. UV400 Anti-mist Anti-scratch	ANSI Z87.1 287+ EN166 1 FT / FT EN170 UV 2C-1.2	32 g	x 100
KILIMANDJARO SMOKE	Smoke	Polycarbonate single lens glasses. Adjustable nylon arms. Side protection. UV400 Anti-scratch	ANSI Z87.1 287+ EN166 1 FT / FT EN172 UV 5-3.1	32 g	x 100
PITON 2 CLEAR	Clear	Polycarbonate single lens glasses. Modern and sport design. Side protection.	C€	30 g	x 100
		Open arms for lateral ventilation. Hole in arms for neck cord. UV400 Anti-scratch	EN166 1 FT / FT EN170 UV 2C-1.2		
PITON CLEAR	Clear	Clear polycarbonate single lens glasses. Direct side ventilation. Side protection. Hole in arms for neck cord. UV400	ANSI Z87.1 287+ EN166 1FT/FT EN170 UV 2C-1.2	45 g	x 300

EYEWEAR PROTECTION Safety goggles

GALERAS




















Anti-mist Anti-scratch





Tilting elastic to fit better

- Marking (EN166) 1 = the best optical class B = medium energy impact
- resistance
 T = impact resistance at extreme temperature
- 3 = liquid projections resistance 4 = large dust particles resistance 9 = molten metal projections
- resistance

Article	Colours	Description	Sizes	Standard		
GALERAS	Clear	Clear polycarbonate goggles. Indirect ventilation. Flexible PVC and nylon frame. Wide screen with non-reflecting effect. Adapted to the wearing of corrective glasses and disposable respiratory half-masks. Wide elastic strap.	Adjustable	ANSI Z87.1 Z87+: High impact EN166 1 BT 9 349 BT	104 g	x 60

FILM GOGGLE









Δ	rticle	Colours	Description	2	
F	ILM GOGGLE	Clear	Box of 10 sets of protective film to protect screens of goggles. Each set is made of 3 layers of films.		x 10

EYEWEAR PROTECTION Safety goggles

Article	Colours	Description	Sizes	Standard		
RUIZ 1	Clear	Clear polycarbonate goggles. Flexible PVC frame. Indirect ventilation with 4 ventilators. Textile elastic strap.		ANSI Z87.1 297 EN166 1 B/3 B	86 g	x 60
MURIA 1	Clear	Clear polycarbonate goggles. Flexible PVC frame. Direct ventilation. Textile elastic strap.		ANSI Z87.1 287 EN166 1B/B	60 g	x 60
				1070		



Sensitivity ≤ 0,0003 s







Article	Colours	Description	Sizes	Standard	•	
BARRIER	Blue	Helmet for electric arc welding, MIG, TIG that requires DIN9 to DIN13 protection. Polypropylene. Sweat band. Headband with easy ratchet adjustment. Vision shield: 100 x 60 mm. LCD filter included. Shades: Clear: DIN4 - Dark: DIN9 to DIN13, Sensitivity ≤ 0,0003 s. (Clear shade to dark shade). Powered by solar cells and 2 replaceable lithium batteries included.		ANSI Z87.1 287 EN166 1 S EN379 1/3/3/3/4/9-13 EN175 S	520 g	x 6
BARRIER PLATE	Clear	Pack of 5 exterior spare screens for BARRIER helmet in polycarbonate.		EN166		x 50
CASOUD 2	Black	Helmet for all types of welding that requires shade 11 protection. Polypropylene with glass fibre. Headband. Sold ready to use: fixed screen equipped with one clear polycarbonate filter (FILTER-IN), Flip-up screen equipped with one DIN11 filter (FILTER-11), protected by one clear polycarbonate filter (FILTER-IN). Dimensions of the filters: 108 x 51 mm.		EN166 IFF EN169 I1 EN175 F	522 g	x 10
CASOUD2HE	Black	Polypropylene welding face shield, to be used on safety helmets. For all types of welding that requires shade 11 protection. Sold ready to use: fixed screen equipped with one clear polycarbonate filter, Flip-up screen equipped with one DIN11 filter, protected by one clear polycarbonate filter. Dimensions of the filters: 108 x 51 mm.	Adjustable	EN166 1FS EN169 11 EN175	260 g	x 10
FILTER-IN	Clear	Pack of 5 clear polycarbonate filter, 108 x 51 mm. to be fitted on CASOUD2 welding helmet and MASOUD2 welding shield. Thickness: 1,8 mm.		EN166 1F	140 g	x 20
FILTER 11	Green	Pack of 5 Shade 11 mineral filter, 108 x 51 mm. to be fitted on CASOUD2 welding helmet and MASOUD2 welding shield. Thickness: 3 mm.		EN166 1F EN169 11	240 g	x 20
FILTER-KIT		Pack of 5 shade 11 mineral filters 108 x 51 mm. Thickness: 3 mm + 5 clear polycarbonate filters 108 x 51 mm. Thickness: 1,8 mm to be fitted to CASOUD2 & CASOUD2HE welding helmet & welding visors.		EN166 1F EN169 11	340 g	x 10
T0BA 2 T5	Red	Welding goggles. Flip-up screen. Flexible PVC frame. Indirect ventilation. Elastic strap. Clear polycarbonate inside lens. Shade 5 mineral glass upper lens with clear polycarbonate reinforcement lens.	Adjustable	EN166 1FF EN169 W 5 EN175 F	140 g	x 60
LIPARI2 T5	Shade 5	Polycarbonate single lens glasses. Adjustable and tilting nylon arms. Spatula tips. Integrated TPE nose piece. Side protection.		ANSI Z87.1 Z87+ EN166 1 FT / FT EN169 UV 5	34 g	x 100

EYEWEAR PROTECTION Safety visors

VISOR TORIC

















Marking (EN166)

- 1 = the best optical class
- A = highest shock resistance
- T = extreme temperature resistance
- 8 = electrical Arc, short-circuit resistance
- 9 = molten metal projections resistance

Marking (EN170) 2C-1,2 = UV resistance

Article	Colours	Description	Standard	٥	
VISOR TORIC	Clear	Clear polycarbonate injected visor. Thickness 1,9/2,0 mm. Electric Arc pn Universal fixing. Suitable for faceshield holder VISOR HOLDER and VISOR PICO2 support). 39 x 20 cm.	totection. H (BALBI2 and C EN166 1AT 89 EN170 UV 2C-1.2	162 g	x 20
VISORPC		WISORG 🚜 🖺 VISORPC N	MINI 🚲 VISORG MIN	l	6
































Article	Colours	Description	Standard		
VISORPC	Clear	Pack of 2 clear polycarbonate visors with plastic edge. Universal fixing. Suitable for BALBI2 - PICO2 - VISOR HOLDER faceshield holder. 39 x 20 cm.	EN166 1BT	100 g	
VISORG	Black	Pack of 2 gauze visors with plastic edge. Universal fixing. Suitable for BALBI2 - PICO2 - VISOR HOLDER faceshield holder. $39 \times 20 \text{ cm}$.	EN1731	104 g	
VISORPC MINI	Clear	Pack of 2 clear polycarbonate visors with plastic edge. Universal fixing. Suitable for VISOR-HOLD MINI. 36 x 17 cm.	EN166 1BT	90 g	
VISORG MINI	Black	Pack of 2 gauze visors with plastic edge. Universal fixing. Suitable for VISOR-HOLD MINI. 36 x 17 cm.	EN1731 S	94 g	

EYEWEAR PROTECTION Safety visors

BALBI 2

















Article	Colours	Description	Standard		
BALBI 2	Yellow	Faceshield with front protection + VISORPC visor: clear polycarbonate visor with plastic edge. 39 x 20 cm.	EN166 1BT / 3BT	260 g	v 20
PICO 2	Yellow-Black	Faceshield with front protection + VISORG visor: gauze visor with plastic edge. 39 x 20 cm.	EN1731 F F	264 g	X 20

VISOR HOLDER





















Article	Colours	Description	Standard	9
VISOR HOLDER	····· Black	Faceshield holder suitable for ZIRCON, QUARTZ and BASEBALL DIAMOND safety helmets. To combine with VISORPC, VISORG and VISOR-TORIC visors, universal fixing.	C € EN166	x 20
VISOR-HOLD MINI		Faceshield holder suitable for GRANITE WIND and GRANITE PEAK safety helmets. To combine with VISORPCMINI and VISORGMINI.	EN1731	







SKULL PROTECTION Safety helmets

BASEBALL DIAMOND V UP







Article	Colours	Description	Sizes	Standard	<u>•</u>	
	Yellow	ADO CALLAND WAS A STANDARD TO A STANDARD WAS				
BASEBALL DIAMOND	White	ABS safety helmet with innovative design. Tested in «reverse» position. Polyamide cap: 3 fabric bands with 8 attachment points. Terry sweatband. Rotor® clamping system (patented): head circumference	Adiustable	EN397 MM LD -10°C +50°C	405 a	v 20
V UP	Blue	53 to 63 cm. 2 possible positions around the head (high/ low) for better comfort. Retro-reflective band. Electrical insulation	Aujustable	440VAC EN50365	425 y	X 20
	Red	1000 VAC/ 1500 VDC. Sold with 4 chin attachment points.		CLASS 0		

BASEBALL DIAMOND V



















Fluorescent colours and silver band for high visibility BASEBALL DIAMOND BASEBALL DIAMOND UP

















	4
٠.	
V	

Article	Colours	Description	Sizes	Standard	<u>•</u>	
BASEBALL DIAMOND V	Orange					
	White					
	Blue	ABS safety helmet. Innovative "baseball cap" shape to improve vision when looking up. Also tested for front back wearing, to reduce		EN397		
	Yellow	encumbrance. Textile harness: 3 textile straps with 8 fixing points. Foam sweat band. Innovative button adjustment "colour to colour" for head	Adjustable	-20°C +50°C 440 VAC EN50365 CLASS 0	368 g	x 20
	Black	sizes 53/63 cm. 2 possible positions of the headband (top/low) for a				
	Red	better comfort. Electrical insulation up to 1 000 V.A.C. or 1 500 V.D.C.		OLFIGO O		
	Green					
HARNESS V	Black	Bag of 10 spare harnesses for BASEBALL DIAMOND safety helmet. Textile lining, foam sweat band, adjustment with button.				x 10

SKULL PROTECTION Safety helmets

SUPER QUARTZ
















ABS-PC shell







More resistant helmet due to plastic anchorages moulded over the textile straps



Article	Colours	Description	Sizes	Standard		
SUPER QUARTZ	White	ABS-PC safety helmet. Polyamide harness: 3 textile bands with 8 fixing points. Foam sweat band. Innovative button adjustment "colour to colour" for head sizes 53/63 cm. 2 possible positions of the headband (high/low) for better comfort. Electrical Insulation up to 1 000 V.A.C. or 1 500 V.D.C.	Aujustable	EN397 MM LD +150°C -30°C 440VAC EN50365 CLSS 0	410 g	x 40



SKULL PROTECTION Safety helmets

QUARTZ UP IV









Article	Colours	Description	Sizes	Standard	2	
	Green		100000000000000000000000000000000000000			
	Orange					
OLIA DET LID III	White	Ventilated UV-resistant high density polypropylene (PP) safety helmet. Polyamide cradle: 3 textile bands with 8 fixing points. Foam sweat band.		C C EN397	200	40
QUARTZ UP IV	Blue	Innovative adjustable ROTOR® system: head sizes 53/63 cm. 2 possible positions of the headband (high/low) for better comfort.	Adjustable	+50°C -30°C	322 g	x 40
	Yellow	positions of the fleadballd (high/low) for better conflort.				
	Red					

plastic anchorages moulded over the textile straps QUARTZ UP IV - QUARTZ UP III

QUARTZ UP III













Article	Colours	Description	Sizes	Standard		
	Red Green			EN397		
Quartz up III	White Blue	harness: 3 textile bands with 8 fixing points. Foam sweat band. Innovative adjustable ROTOR® system: head sizes 53/63 cm. 2 possible positions of the headband (high/low) for better comfort. Electrical	Adjustable	**MM	322 g	x 40
	Yellow	Insulation up to 1 000 V.A.C. or 1 500 V.D.C.		CLASS 0		
	Orange					

FORESTIER 2













Article	Colours	Description	Sizes	Standard	<u> </u>	
FORESTIER 2	Orange	Forester's type helmet consisting of: QUARTZ UP III safety helmet: UV-resistant high density polypropylene. Polyamide cradle: 3 textile bands with 8 fixing points. SUZUKA2 ear defenders. VISOR HOLDER faceshield holder. VISORG gauze visor. Plastic shell packaging.	Adjustable	EN397 MM +50°C -30°C 440VAC EN50365 CLASS 0 EN1731 FF EN352-3 SNR 27 dB H29 M 25 L 18	900 g	x 10

SKULL PROTECTION Safety helmets



€<u></u>

SKULL PROTECTIONHelmets accessories - Marking

BASGAMMA	Black	Bag of 5 thermoformed sweat bands for GRANITE PEAK & WIND, BASEBALL DIAMOND, SUPER QUARTZ and QUARTZ UP safety helmets.		x 20
Article DVALANIC IIICALDIA	Colours Black	Description Bag of 10 chin straps, 4 fixing points for work at height. Safety-breaking	Sizes Adjustable	, ,
Article DYNAMIC JUGALPHA	Colours Black	Description Bag of 10 chin straps. 4 fixing points for work at height. Safety-breaking system. Suitable for ZIRCON, QUARTZ, QUARTZ UP, SUPER QUARTZ and BASEBALL DIAMOND safety helmets.	Sizes Adjustable	x 20
		Bag of 10 chin straps. 4 fixing points for work at height. Safety-breaking system. Suitable for ZIRCON, QUARTZ, QUARTZ UP, SUPER QUARTZ and		, ,






SKULL PROTECTION Bump cap

AIR COLTAN
















4 versions of colour matching the range of MACH 2 CORPORATE - PANOSTYLE HV -DMACH clothing











COLTAAIGR - 7 cm









COLTAAIBMSH - 5cm COLTAAIBM - 7 cm











Article	Colours	Description	Sizes	Standard		
	Fluorescent yellow-Grey					
	Light grey-Dark grey				000	
AIR COLTAN	Black-Red	Cotton with mesh fabric. Lined with polyethylene and comfortable EVA	Adjustable	(€ EN812	200 g	x 20
	Navy blue-Black	foam shell to absorb shocks. Adjustable size by buckle 55/62 cm.				
COLTAN	Navy blue				210 g	



HEARING PROTECTION Ear defenders

PIT-STOP





Electric wireless external 6 AAA batteries not included LED indicates activated system



with synthetic foam. Coolmax® headband for extra comfort, adjustable in height. ON/OFF and volume switch button on each cup, for right/left use separately. 2 omni directional microphones outside, connected to 2 loudspeakers inside EN352-1 SNR 26 dB H 30 M 23 L 16 PIT-STOP Black the cups. Hunting system: amplification of voices and alarm signals to avoid Adjustable 286 g x 20 the risk of insulation on the job. System of amplification shuts off automatically and reverts to passive ear defender mode, in the case of impulsive noise which reaches 80/82 dB: protection against hazardous noises. Requires 6 batteries AAA, not included.

YAS MARINA







Foldable: reduced encumbrance







Article	Colours	Description	Sizes	Standard	٥	
YAS MARINA	Grey-Orange	Foldable ear defenders with ABS cups. Pads filled with synthetic foam. Double plastic headband (POM), adjustable in height, with metallic insert and soft, ventilated reinforcement for a better comfort.	Adjustable	C E EN352-1 SNR 32 dB H 33 M 31 L 25	312 g	x 20
SILVERST	ONE 2					



Without headband: Easy to wear with all helmets and burn caps





Article	Colours	Description	Sizes	Standard	•	
SILVERSTONE 2	Fluorescent yellow	Ear defenders for wearing around the neck. Metal arch and ABS cups, padded with synthetic foam.	Adjustable	EN352-1 SNR 30 dB H 32 M 28 L 21	240 g	x 20

HEARING PROTECTION Ear defenders

INTERLAGOS









HV colour







Article	Colours	Description	Sizes	Standard	<u>°</u>	
INTERLAGOS	Grey Fluorescent yellow	Ear defenders with ABS cups. Pads filled with synthetic foam. Double plastic headband (POM), adjustable in height, with metallic insert and soft, ventilated reinforcement for a better comfort.	Adjustable	C EN352-1 SNR 33 dB H 33 M 31 L 25	303 g	x 20



HEARING PROTECTION Ear defenders

MAGNY-COURS









Article	Colours	Description	Standard	•	•
MAGNY-COURS	Beige-Black	Ear defenders with ABS cups. Pads filled with synthetic foam. Metallic headgear: internal/textile EVA, internal/PVC material. Adjustable in height. High performance level due to the multi layer technology with AIR ROOM inside the cups.	C € EN352-1 SNR 32 dB H 34 M 29 L 23	338 g	x 20

MAGNY HELMET







Suitable for all our safety helmets













Article	Colours	Description	Standard	•	
MAGNY HELMET	Grey	Ear defenders for safety helmets. Adjustable in height. Metallic arms and ABS cups padded with synthetic foam. Can be used on their own or with «VISOR HOLDER» faceshield holder. Suitable for ZIRCON, QUARTZ, GRANITE and BASEBALL DIAMOND safety helmets.	C E EN352-3 SNR 32 dB H 34 M 31 L 23	286 g	x 20

₹

HEARING PROTECTION Ear defenders



HEARING PROTECTION Disposable earplugs

CONICFIR050











Article	Colours	Description	Standard	
CONICFIR050	Navy blue-Orange	Box of 50 pairs of reusable TPR earplugs with fabric cord.	ANSI S3.19 NRR 25 dB EN352-2 SNR 29 dB H 27 M 24 1 24	x 20

CONICMOVE01





CONICMOVE01BR







Ergonomic and stable headband

Earplugs can move on the headband





Round earplugs very comfortable



Article	Colours	Description	Standard	
CONICMOVE01	Blue-Green	PU earplugs with headband in polypropylene which can be worn under the chin. Ideal for intermittent or occasional wear.	EN352-2 SNR 19 dB 0-T-H / 22 dB U-T-C H 0-T-H 22 / U-T-C 25 M 0-T-H 15 / U-T-C 19 L 0-T-H 13 / U-T-C 17	x 100
CONICMOVE01BR	Green	Bag of 10 pairs of spare earplugs for CONICMOVE01.		x 200


HEARING PROTECTION



Article	Colours	Description	Standard	
REUSABLE EARPLUGS				
CONICAPOI	Blue- Green	PU earplugs with headband in polypropylene which can be worn under the chin. Ideal for intermittent or occasional wear.	ANSI S3.19 NRR 22 dB EN352-2 SNR 24 dB H 25 M 20 L 19	x 200
CONICAP01BR	Green	Bag of 10 pairs of spare earplugs for CONICAP01.		x 200
Article	Colours	Description	Standard	9
DISPOSABLE EARPLUGS				
CONICCO200	Yellow	Dispenser box of 200 pairs disposable polyurethane earplugs with plastic cord. Ø 12mm. Individual plastic bag of 2 earplugs.	ANSI S3.19 NRR 32 dB EN352-2 SNR 37 dB H 36 M 34 L 33	x 5
Article	Colours	Description	Standard	Ŷ
CONIC200	Yellow	Dispenser box of 200 pairs disposable polyurethane earplugs. Ø 12 mm. Individual plastic bag of 2 earplugs.	ANSI S3.19 NRR 32 dB EN352-2 SNR 37 dB H 36 M 34 L 33	x 5
CONIC500	Yellow	Box of 500 pairs disposable polyurethane earplugs. Ø 12 mm. Refill unit for CONICDISPLAY.	ANSI S3.19 NRR 32 dB EN352-2 SNR 37 dB H 36 M 34 L 33	x 5
CONIC DISPLAY	Grey	Dispenser for earplugs including a refill of 500 pairs of CONIC500 earplugs. Can be fixed on the wall or lay SNR 37 dB	ANSI S3.19 NRR 32dB EN352-2 SNR 37 dB H 36 M 34 L 33	x 4







RESPIRATORY PROTECTION Disposable respiratory


M1300V












M1200VPLUS











Article	Colours	Description	Standard	
M1300V	AA/I-it-	Box of 5 non woven synthetic fibre disposable masks FFP3. Wide adjustable straps. Moulded mask. Nose clip for adjustment. Complete ultra-soft face joint ring. High performance exhalation valve.	C C EN149	10
M1200VPLUS	White	Box of 5 non woven synthetic fibre disposable masks FFP2. Wide adjustable straps. Moulded mask. Nose clip for adjustment. Complete ultra-soft face joint ring. High performance exhalation valve.	NIOSH N99	X 10

RESPIRATORY PROTECTION Disposable respiratory

Article	Colours	Description	Standard	
M1300V2	White	Box of 10 non woven synthetic fibre disposable masks FFP3. Moulded mask. Nose clip for adjustment. EVA edge for extra comfort under nose clip. High performance exhalation valve. DOLOMIA optional test for longer continuous wear time.	C € EN149	x 10
The state of the s				
M1200V	White	Box of 10 non woven synthetic fibre disposable masks FFP2. Moulded mask. Nose clip for adjustment. Foam edge under nose clip. High performance exhalation valve. DOLOMIA optional test for longer continuous wear time.	EN149 NIOSH	x 10
The state of the s				
M1200VW	White	Box of 10 active charcoal non woven synthetic fibre disposable masks FFP2 for organic vapours (for concentration < VME). Moulded mask. Nose clip for adjustment. Foam edge under nose clip. High performance exhalation valve. Hygienic individual plastic bag. DOLOMIA optional test for longer continuous wear time.	EN149 NIOSH N95	x 10
M1100V	White	Box of 10 non woven synthetic fibre disposable masks FFP1. Moulded mask. Nose clip for adjustment. Foam edge under nose clip. High performance exhalation valve. DOLOMIA optional test for longer continuous wear time.	C € EN149	x 10
M1200	White	Box of 20 non woven synthetic fibre disposable masks FFP2. Moulded mask. Nose clip for adjustment. Foam edge under nose clip. DOLOMIA optional test for longer continuous wear time.	C € EN149	x 10
			NIOSH N95	
M1100	White	Box of 20 non woven synthetic fibre disposable masks FFP1. Moulded mask. Nose clip for adjustment. Foam edge under nose clip. DOLOMIA optional test for longer continuous wear time.	C € EN149	x 10
M1300VB	White	Box of 10 non woven synthetic fibre disposable masks FFP3. Nose clip for adjustment. High performance exhalation valve. Hygienic individual plastic bag.	C € EN149	x 10
M1200VB	White	Box of 10 non woven synthetic fibre disposable masks FFP2. Nose clip for adjustment. High performance exhalation valve. Hygienic individual plastic bag. DOLOMIA optional test for longer continuous wear time.	EN149	x 10
* 0			N95	
M1195B	White	Box of 30 non woven synthetic fibre disposable masks FFP1. Nose clip for adjustment. Foam edge under nose clip. DOLOMIA optional test for longer	CE	x 10
		continuous wear time.	EN149 NIOSH	
The second			N95	
		-		



Article	Colours	Description	Sizes	Standard	Ŷ
M9200 - ROTOR GALAXY		Silicone full face mask with innovative ROTOR® system adjustment (patented), one- hand use even when wearing gloves. Wide polycarbonate screen (210°). Inside silicone half-mask to reduce mist and increased comfort (3 inhalation valves, an exhalation valve, phonic system). Adjustable sizes: S, M, L. Compatible with EN148-1 type cartridges as M9000 and M8000 range, sold separately. Storage bag included.			
	Black-Orange		Adjustable	C € EN136	x 6
M9300 - STRAP GALAXY		Silicone full face mask with strap adjustment. Wide polycarbonate screen (210°). Inside silicone half-mask to reduce mist and increased comfort (3 inhalation valves, an exhalation valve, phonic system). Adjustable size. Shoulder strap to hold the mask when not in use. Compatible with EN148-1 type cartridges M9000 and M8000 range, sold separately. Storage bag included			





Article	Colours	Description	Standard	
M9000 A2	Black	Kit of 4 A2 filtering cartridges for M9200 ROTOR GALAXY, M9300 STRAP GALAXY full face masks.	EN148-1 EN14387 A2	x 10
() ((and) () ()				
M9000 A2B2E2K2	Black	Kit of 4 A2B2E2K2 filtering cartridges for M9200 ROTOR GALAXY, M9300 STRAP GALAXY full face masks.	EN148-1 EN14387 A2B2E2K2	x 10
M9000A2B2E2K2P3	Black	Kit of 4 A2B2E2K2P3 filtering cartridges for M9200 ROTOR GALAXY, M9300 STRAP GALAXY full face masks.	EN148-1 EN14387 A2B2E2K2P3	x 10
M9000 A2P3	Black	Kit of 4 A2P3 filtering cartridges for M9200 ROTOR GALAXY, M9300 STRAP GALAXY full face masks.	EN148-1 EN14387 A2P3R	x 10
M9000 P3	Black	Kit of 4 P3R filtering cartridges for M9200 ROTOR GALAXY, M9300 STRAP GALAXY full face masks.	EN148-1 EN143 P3R	x 10

PEI

RESPIRATORY PROTECTION Reusable respiratory

M6300 JUPITER

























Article	Colours	Description	Sizes	Standard		
M6300 JUPITER	Division of	Comfort half mask mono-filter: Half mask body in polypropylene (PP) - Thermoplastic (TPE) overmould. Elastic straps. To be used with 1 filter cartridge, M6000 series, sold separately. Shell packaging.	0	((05
M6400 JUPITER	Black-Grey	Comfort half mask bi-filter: Half mask body in polypropylene (PP) - Thermplastic (TPE) overmould. Elastic straps. To be used with 2 filter cartridges, M6000 series, sold separately. Shell packaging.	One size	66	EN140	X 25

M6100 JUPITER

































Article	Colours	Description	Sizes	Standard	9
M6100 JUPITER	····· Blue	Comfort half mask in tri-material: Half mask body in Thermo-plastic Elastomer (TPE) - Support for cartridge anchorage in polyethylene HD (HDPE) - Valve protective housing in polypropylene (PP). Elastic straps. To be used with 1 filter cartridges, M6000P3, M6000PREP3 or M6000A1, sold separately.	····· Adiustable	(€ EN140	x 15
M6200 JUPITER	olue	Comfort half mask in tri-material: Half mask body in Thermo-plastic Elastomer (TPE) - Support for cartridge anchorage in polyethylene HD (HDPE) - Valve protective housing in polypropylene (PP). Elastic straps. To be used with 2 filter cartridges, M6000 series, sold separately.	····· Aujustable	C EN140	X 13

Article	Colours	Description	Sizes Stan	dard
M6000 A1	Grey	Pack of 2 A1 filtering cartridges for M6200-JUPITER half-mask and M6100-JUPITER half mask.	EN1	× 30
M6000 A2	Grey	Pack of 2 A2 filtering cartridges for M6200-JUPITER half-mask.	EN1 A2	4387 × 30
THE PARTY OF THE P				
M6000 A1B1E1K1	Grey	Pack of 2 A1B1E1K1 filter cartridges for M6200-JUPITER half-mask.	EN1 A1B1E	4387
M6000 PREP3	Grey	Set of 2 P3 pre-filters and 2 adapters for M6200-JUPITER half-mask and M6100-JUPITER half mask. To use with A1, A2 or A1B1E1K1 filters.	EN1 P3R	
M6000 P2	Grey	Pack of 2 P2 filter cartridges for M6200-JUPITER half-mask and M6100-JUPITER half mask.	EN1 P2R	
The state of the s				
M6000 P2 CLIP	Grey	Set of 2 P2 filter cartridges for M6200-JUPITER and M6100-JUPITER half masks + 20 spare disposable filters.	EN1 P2NR	
M6000 P3	Grey	Pack of 2 P3 filter cartridges for M6200-JUPITER half-mask and M6100-JUPITER half mask.	EN1 P3R	_
The state of the s				

HAND PROTECTION



#

Supported or Not supported?

▶ SUPPORTED: WHAT TYPE OF SUPPORT?

• Cotton: Natural fibre

Exceptional comfort - Excellent capacity to absorb moisture - Insulating properties.

• Polyamide: Synthetic fibre, also called Nylon

Resistance to traction and abrasion - Elasticity and shape memory - Washable.

• Polvester: Synthetic fibre

Resistance to traction and abrasion - Possibility to blend with cotton to enhance comfort.

• Kevlar®: Para-aramid fibre

Heat and Cut Resistance - Carbonised between 425° and 475° - Self extinguishing - Softness and high dexterity - Washable.

• Taeki®: Synthetic High-strength polyethylene fibre

Exceptional mechanical properties (abrasion and cut resistance) - Softness and high dexterity - Washable.

Econocut®: High performance polyethylene fibre (Light version)

Good mechanical properties - Combines resistance (abrasion, cut) and very good price/quality ratio.


▶ NON- SUPPORTED:

Different types of non supported gloves :

- **Flocked** (finished with a deposit of cotton particles): Pleasant to the touch, limits transpiration and facilitates donning and removal.
- **Chlorinated** (finished by washing the glove in chlorinated water) : Gives a velvety touch and limits the effects of latex protein allergies.

Different types of disposable glove :

- **Powdered** (finished with a deposit of powder): Pleasant to the touch, limits transpiration and facilitates donning and removal.
- **Non powdered** (finished by washing the glove in chlorinated water) : Gives a velvety touch and limits the effects of latex protein allergies.



PLUS: How to identify sizes?

Implementation of a colour-coding system for High-Tech gloves and some leather gloves: Uniform sizes for easy identification.

7	8	9	10	11	12
Yellow	Brown	Black	Blue	Grey	Green
Yellow	Brown	Black	Blue	G	rey

HAND PROTECTION

LEATHER GLOVES


Grain or Split?

► Full grain leather: External part.

Advantages: dexterity, comfort and touch accuracy.

► Split leather: Internal part.

Advantages : greater resistance to abrasion, suitable for heavy-duty work.



Which type of leather?

▶ Cowhide

Full grain or Split : Suppleness, dexterity and good resistance to abrasion and tearing.

Pigskin

Full grain and split: Highly breathable thanks to its porous structure. Softer and more supple in damp working conditions.



▶ Goatskin

Full grain only: Very highly supple, used for delicate applications, can have good resistance to abrasion depending on the thickness used.

▶ Lambskin

Full grain only: Suppleness and dexterity.

SYNTHETIC GLOVES


	LATEX	NITRILE	NEOPRENE	PVC	POLYURETHANE
Strengths	Supple, elastic, impermeable to water Good mechanical Resistances (perforation and cutting) Good cold protection	Very good resistances to abrasion, to perforation and not sensitive to heat Repels oil and grease Suitable for some chemical products	Very good resistances to abrasion and to heat Repels oil, grease and hydrocarbons Suitable for aggressive chemical environments	Good mechanical resistance and to cold Repels acids and hydrocarbons Suitable for aggressive chemical environments	ALWAYS SUPPORTED Good resistance to abrasion and to tearing Micro porous and highly elastic High sensitivity
Elasticity/Flexibility	444	44	44	*	**
Abrasion	*	444	444	44	***
Acids	44	-	444	444	*
Bases (Lime, Sodium hydroxide)	444	44	444	44	*
Oils/Grease	-	444	444	44	*
Hydrocarbons	-	44	***	444	*
Aromatic solvents (styrene)	-	444	-	-	-
Ketone solvents	**	-	***	-	-
Acetates (degreasing agents)	-	44	*	*	-
Precautions for use TO AVOID	Petroleum products, oil, grease and acids	Ketones, acids, alcohols	Chloride solvents	Ketones and aromatic/ chloride solvents	Chemical products

CUT RESISTANT GLOVES

Full range



The fibres



Level 4 and 5 cut resistance

High performance

polyethylene fibre




TAEKI®S **Level 4 cut resistance**

High performance polyethylene fibre



Maximum abrasion performance. Soft fibre: High level of comfort. Gauge 13: High level of dexterity.



Excellent cut resistance. **Good** abrasion performance. Economical fibre: good price. Gauge 13: high level of dexterity.



HIGH-TECH GLOVES Handling of sharp-edged objects

CUT RESISTANCE LEVEL 5 - TAEKI® 5

VENICUT50



















TAEKI® 5 high performance polyethylene:

- Excellent cut resistance
- Maximum abrasion performance
- Heat resistance up to 250°C



Split leather :

- Very good abrasion resistance
- · Ideal for heavy work



Article	Colours	Description	Sizes	Standard		•
VENICUT50	Yellow-Grey	TAEKI® 5 High performance polyethylene fibre. Cowhide on palm and fingertips. Gauge 10.	09 / 10	C EN388 4543	EN407 X, 2, X, X, X, X	x 60

VENICUT52









- Excellent cut resistance
- Maximum abrasion performanceHeat resistance up to 250°C



- Latex coating :
 Good abrasion resistance
- Anti slip rough texture Excellent grip



Article	Colours	Description	Sizes	Standard		Ŷ
VENICUT52	Yellow-Black	TAEKI® 5 High performance polyethylene fibre. Latex coating on palm and fingertips. Gauge 10.	07 / 08 / 09 / 10	C EN388 4542	EN407 X, 2, X, X, X, X	x 60

VENICUT55















TAEKI® 5 high performance polyethylene:
• Excellent cut resistance
• Maximum abrasion performance
• Heat resistance up to 100°C





Article	Colours	Description	Sizes	Standard		
VENICUT55	Yellow-Grey	TAEKI® 5 High performance polyethylene fibre. Gauge 10.		C € EN388 3 5 4 X	Yi'	x 120
VENICU						H







Food compatibility

TAEKI® 5 high performance polyethylene:
• Excellent cut resistance
• Maximum abrasion performance
• Heat resistance up to 100°C



Article	Colours	Description	Sizes	Standard		
VENICUT5M	Yellow-Grey	TAEKI® 5 High performance polyethylene fibre. Knitted sleeve with thumbhole. Length 45 cm. Gauge 13.	One size	C EN388 454X	EN407 X, 1, X, X, x, X	x 60

HIGH-TECH GLOVES Handling of sharp-edged objects

CUT RESISTANCE LEVEL 5 & 4

VENICUT42
















TAEKI® S:

- Maximum abrasion performance
- Excellent cut resistance
- Soft fibre: High level of comfort
- Gauge 13: High level of dexterity



PU coating:

- Flexibility and dexterity Silicone free :
- Limit the Environmental risks of manufacture



Article	Colours	Description	Sizes	Standard	
VENICUT42	Grey	TAEKI® S High performance polyethylene fibre. Polyurethane coating on Palm and fingertips. Gauge 13.	07 / 08 / 09 / 10	C € EN388	x 60

VENICUT41















- Maximum abrasion performance • Excellent cut resistance
- Soft fibre: High level of comfort
- . Gauge 13: High level of dexterity



Nitrile coating :

- Excellent grip and protection in greasy and oily environments
- Excellent mechanical performances



Article	Colours	Description	Sizes	Standard	Û
VENICUT41	1 Grey-Black	TAEKI® S High performance polyethylene fibre. Nitrile coating on Palm and fingertips. Gauge 13.	07 / 08 / 09 / 10	C € EN388	x 60

HIGH-TECH GLOVES Handling of sharp-edged objects

CUT RESISTANCE LEVEL 5 & 4

Article	Colours	Description	Sizes	Standard	
VENICUT58G3	Grey	ECONOCUT® high performance polyethylene fibre. Polyurethane coating on palm and fingertips. Elastic cuff 6 cm. Gauge 13.	07 / 08 / 09 / 10	C€	x 40
00-				EN388 4 5 4 3	






















x 40


















Grey-Black ECONOCUT® high performance polyethylene fibre. Nitrile coating on palm and fingertips. Elastic cuff 6 cm. Gauge 13.

07 / 08 / 09 / 10



x 40





















HIGH-TECH GLOVES Precision work

POLYURETHANE COATING

VE702GR









Silicone free



Backing colour:

- Handling of soiled objects
- Seamless knit :
- More comfort



Article	Colours	Description	Sizes	Standard	Ŷ
VE702GR	Grey	100% polyamide. Polyurethane coating on palm and fingertips. Gauge 13.	06 / 07 / 08 / 09 / 10	C EN388	x 240

VE702











Silicone free

Second skin effect





Article	Colours	Description	Sizes	Standard	
VE702	White	100% polyamide. Polyurethane coating on palm and fingertips. Gauge 13.	06 / 07 / 08 / 09 / 10	C €	x 240

HIGH-TECH GLOVES Precision work

POLYURETHANE COATING

Article	Colours	Description	Sizes	Standard	
VE702PG	Grey	100% polyester. Polyurethane coating on palm and fingertips. Gauge 13.	06/07/08/ 09/10	CE	x 240
A STANLAR				EN388 4121	
VE702P	White	100% polyester. Polyurethane coating on palm and fingertips. Gauge 13.	06/07/08/ 09/10	CE	x 240
SECTION AND THE PROPERTY OF TH				EN388 4121	



HIGH-TECH GLOVES Handling in oily environments

NITRILE COATING

VE727





















Article	Colours	Description	Sizes	Standard	
VE726	Grey-Black	100% polyamide Spandex. Nitrile/Polyurethane coating on palm and fingertips. Gauge 15.	07 / 08 /	EN388 3131	x 120
VE713	Black	100% polyamide. Double nitrile coating on palm, fingers and half back. Gauge 13.	09 / 10	EN388 4121	x 240

HIGH-TECH GLOVES Handling in oily environments

NITRILE COATING

Article	Colours	Description	Sizes	Standard	
VE722	Grey-Black	100% polyester. Foam nitrile coating on palm and fingertips. Gauge 13.	07 / 08 / 09 / 10	CE	x 120
				EN388 4121	
VE715	Black-Grey	100% polyester. 3/4 nitrile coating on palm and fingertips. Gauge 13.	07/08/ 09/10	EN388 4121	x 120
		169 Till			



VE712GR







Black-Grey 100% polyester. Nitrile coating on palm and fingertips. Gauge 13.





x 240

07 / 08 / 09 / 10

 ϵ

HIGH-TECH GLOVES General handling

EOS NOCUT VV910

















Very good resistance to abrasion and cutting

Double nitrile coating to work in oil environments:


· First smooth nitrile coating: Oil permeability

Second foam nitrile coating: Good grip

Wash in cold water

Kevlar® thread for a longer durability of the glove





Flexible reinforcements for better protection against impact and pinching.



Reinforcement between the thumb and index finger and on the palm



Protection of the metacarpals 5 J







8 cm cuff: safety and comfort

HDPF thread for a larger durability of the glove

Protection of the metacarpals about a force of 5 J (One weight of 1 kg on a distance of 50 cm). Tested under the European standard EN13594 6.8.2 (Hand's back test).

Article	Colours	Description	Sizes	Standard	
EOS NOCUT VV910	Yellow-Grey-Black	Cut resistance support with high performance polyethylene. Neoprene reinforcement on back and fingertips. Smooth nitrile coating/foam nitrile on palm and fingertips. Embossed inside reinforcement on palm. Kevlar® thread on all the	08 / 09 / 10 / 11	EN388 4 5 4 3 EN1621-1	x 60

EOS VV900

















8 cm wrist in neopren: safe and comfort


Tear release fastening: a perfect adjustment. Limit the problems caused at the wrist during prolonged use

Wash in cold water Yellow colour for better visibility

Very good abrasion



Available only with header card



Double thickness of polyamide/ polyurethane on palm with PVC dots: antislip



Flexible reinforcements for better impact and pinching















Protection of the metacarpals about a force of 2 J (One weight of 1 kg on a distance of 20 cm). Tested under the European standard EN13594 6.8.2 (Hand's back test).

Article	Colours	Description	Sizes	Standard	
EOS W900	Yellow-Grey-Black	Polyester/polyurethane back. PVC reinforcements. Polyamide/polyurethane palm with PVC dots. Kevlar® seams. 8 cm cuff in neoprene.	08 / 09 / 10 / 11 / 12	C EN388 4233	x 60



Article	Colours	Description	Sizes	Standard	
EOS OBM W911	Blue-Yellow	Nitrile on cotton jersey lining. Double coating. Length: 40 cm.	08/09/ 10/11	EN1621-1	x 60



- · Protection against oils
- Very good abrasion and cut resistance
- Waterproof

Sweat and moisture absorption





Protection of the metacarpals about a force of 5 J (One weight of 1 kg on a distance of 50 cm). Tested under the European standard EN13594 6.8.2 (Hand's back test).

NYSOS VV904













The support with its soft weave (seamless) makes it very comfortable for extended wear and allows good dexterity and grip



Glove with single coating reducing the effects from impacts, shock and vibration



Flexible reinforcements for better protection against impact and pinching



Protection of the metacarpals 5 J



Anti-vibration and anti-impact





Protection of the metacarpals about a force of 5 J (One weight of 1 kg on a distance of 50 cm). Tested under the European standard EN13594 6.8.2 (Hand's back test).

Article	Colours	Description	Sizes	Standard	
NYSOS VV904	Yellow-Black	Polyester/Cotton. Palm and fingertips reinforced with Chloroprene rubber pads (0.8 cm thick). Neoprene back reinforcement. Gauge 7.	10/11	EN 1SO10819 EN1621-1	x 60

COLD PROTECTION

HERCULE VV750













Very good cold protection

3/4 Coating:

- Full protection of the fingers against cold and water
- Long lifespan



Scratch acrylic support:

- Cold protection
- Scratching: Excellent comfort, keeps hands warm in cold conditions Polyamide support:
- High flexibility



Article	Colours	Description	Sizes	Standard	
HERCULE W750	Black	Inside: 100% acrylic gauge 7. Outside: 100% polyamide gauge 13. 3/4 foam nitrile coating on palm, fingers and half back.	09 / 10	C E EN388 3231 EN511 X X X X	x 60



LATEX COATING

APOLLON VV733













Yellow flashy support :

High Visibility



- · Very soft coating, excellent dexterity
- Breathable coating, prevents perspiration build up







Article	Colours	Description	Sizes	Standard		
APOLLON VV733	Fluorescent yellow-Black	100% high quality polyester - Flashy Yellow color. Latex coating on palm and fingertips. Gauge 13.	07 / 08 / 09 / 10	C € EN388 3131	x 120	

LATEX COATING

VE730OR













Article	Colours	Description	Sizes	Standard	
VE7300R	Yellow-orange	50% cotton 50% polyester. Rough latex coating on palm and fingertips. Gauge 10.	08/09/10	C E EN388	x 120

LATEX COATING

Article	Colours	Description	Sizes	Standard	
VE630	Grey-Black	100% polyester. Latex coating on palm and fingertips. Gauge 13.	07/08/ 09/10	EN388 3121	x 120
VE799	White	65% cotton 35% polyester. Transparent full coating in natural latex on full hand and laminated red latex on palm and fingertips. Gauge 10.	10	EN388 3131	x 120

SYNTHETIC GLOVES Heavy works

NITRILE ON JERSEY LINING

Article	Colours	Description	Sizes	Standard	
NI170	Blue	Nitrile on cotton jersey lining. 6-cm canvas safety cuff. Ventilated back.	10	EN388 4211	x 120
	Divo	Nitrill on eather inner Union Companyon and thought Fully control	00/10/11		v.100
NI175	Blue	Nitrile on cotton jersey lining. 6-cm canvas safety cuff. Fully coated.	09/10/11	EN388 4211	x 120
NI150	Blue	Nitrile on cotton jersey lining. Knitted wrist. Ventilated back.	07/08/ 09/10	EN388 4 2 1 1	x 120
NI155	Blue	Nitrile on cotton jersey lining. Knitted wrist. Fully coated.	10	EN388 4211	x 120
NI015	Yellow	Light nitrile on cotton jersey lining. Knitted wrist. Ventilated back.	07/08/09/ 10/11	EN388 4111	x 120



SYNTHETIC GLOVES Heavy works

LATEX ON JERSEY LINING

VENIZETTE VE920















Resistant to 100°C heat contact for 15 secs.

Maximum abrasion resistance Suppleness

- Cotton jersey lining :

 Better mechanical and thermal protection
- Better comfort





Article	Colours	Description	Sizes	Standard	9
VENIZETTE VE920	Blue	Latex on cotton jersey lining. Length: 30 cm. Thickness: 1,25 mm.	6/7 - 7/8 - 8/9 - 9/10 - 10/11	EN388 4121 EN374-3 AKL A2 > 30 mn K 6 > 480 mn L 6 > 480 mn	x 120

SYNTHETIC GLOVES Works requiring chemical resistance

PVC ON JERSEY LINING

BASF PVCC400













PVC:

- Excellent resistance to abrasion
- Repels oils chemical products and petrol derivatives

Hexamoll® DINCH® - Innovative plasticizer by BASF

BASF is committed to sustainable and innovative products and has therefore introduced Hexamoll® DINCH®, the non-phthalate plasticizer:

- Hexamoll DINCH is safe for sensitive applications
- Complies with regulations (REACH)
- Hexamoll® DINCH® is environmentally friendly
- Safeguard Hexamoll® DINCH® in Food Contact Applications
- Work Safe in protective gloves





Length 40 cm :

• Forearm protection





Article	Colours	Description	Sizes	Standard	
PETRO VE766	Blue	Chemical PVC. PVC on a jersey cotton medium. Length: 62 cm. Thickness: 1.30 mm.	08 / 09 / 1	0 C C EN388 41 2 1 EN374-2 EN374-2 EN374-2 EN374-2 EN374-2	n x 60

- PVC:
 Excellent resistance to abrasion
 Repels oils chemical products and petrol derivatives





SYNTHETIC GLOVES Heavy works

PVC ON JERSEY LINING

PETRO VE780











Anti-slip grained-texture

Good abrasion resistance





Article	Colours	Description	Sizes	Standard	
PETRO VE780	Blue	PVC on cotton jersey lining. Rough-textured palm. Length: 30 cm.	08/09/10	EN388 4121 A2 > 30 mn K 6 > 480 mn L 3 > 60 mn	x 120

PETRO VE760









Cold protection





Article	Colours	Description	Sizes	Standard	9
PETRO VE760	Orange	PVC on cotton jersey lining. Acrylic lining. Length: 30 cm.	10	4221 AKL A2 K6	

SYNTHETIC GLOVES Heavy works

PVC ON JERSEY LINING

Article	Colours	Description	Sizes	Standard	
PVC7335	Red	PVC on cotton jersey lining. Length: 35 cm. Thickness 0,90 mm.	10	EN374-2	
				EN374-3	3
PVC7327	Red	PVC on cotton jersey lining. Length: 27 cm. Thickness 0,90 mm.	10	EN388 4111 EN374-2	
7)					



SYNTHETIC GLOVES
Works requiring chemical resistance

NEOPRENE ON JERSEY LINING

TOUTRAVO VE511


















- Waterproof (Water, Alcohol, and cleaners)
- Excellent protection against chemicals, greases and hydrocarbons

Sweat and moisture absorption







- Cotton jersey lining :

 Better mechanical and thermal
- protection (neopren quality) Better comfort all day

Article	Colours	Description	Sizes	Standard	
TOUTRAVO VE511	Black	Neoprene on cotton jersey lining. Length: 38 cm. Thickness 1,40 mm.	9/10 - 10/11	EN388 2132 EN374-2 EN374-2 EN374-2 EN374-2 J KL J 2 > 30 mm K 6 > 480 m L 4 > 120 m	n x 60



SYNTHETIC GLOVES
Works requiring chemical resistance

NEOPRENE - UNSUPPORTED

TOUTRAVO VE509













NEOPRENE - UNSUPPORTED RESISTANCE

• Abrasion

ADVANTAGE Waterproof

(Water, Alcohol, and cleaners)

Good heat resistance

• Excellent protection against chemicals, greases and hydrocarbons



Article	Colours	Description	Sizes	Standard	
TOUTRAVO VE509	Black	Neoprene with cotton flocklining. Length: 38 cm. Thickness: 0,75 mm.	6/7 - 7/8 - 8/9 - 9/10 - 10/11	EN388 4 11 0 EN374-3 A8CUKL A 3 > 60 mn B 3 > 60 mn C 1 > 10 mn I 3 > 60 mn J 2 > 30 mn K 6 > 480 mn L 4 > 120 mn	x 120

SYNTHETIC GLOVES Heavy works

NITRILE ON JERSEY LINING

NITREX VE803













Maximum abrasion resistance Suppleness

Sweat and moisture absorption





Article	Colours	Description	Sizes	Standard	•
NITREX VE803	Green	Nitrile on cotton jersey lining. Length: 33 cm. Thickness: 0,85 mm.	9/10 - 10/11	EN374-3 JK JG > 490 mm K G > 480 mm X L 3 > 60 mm X	60

SYNTHETIC GLOVES Works in industry

NITRILE - UNSUPPORTED



Article	Colours	Description	Sizes	Standard	
NITREX VE840	Green	Nitrile with cotton flocklining. Length: 40 cm. Thickness: 0.50 mm.	7/8 - 8/9 - 9/10	EN388 4002 AJK A2>30mn J6>480mn K6>480mn	

SYNTHETIC GLOVES Works in industry

Article	Colours	Description	Sizes	Standard	
NITRILE - UNSUPPORTED					
NITREX VE801	Green	Nitrile with cotton flocklining. Length: 33 cm. Thickness: 0,40 mm.	07/08/09/ 10/11	EN388 3101 EN374- JKL JG > 480 r K6 > 480 r L 3 > 60 m	-3 mn mn
TO THE LAND				EN374-	

LATEX - UNSUPPORTED

DUOCOLOR VE330



Blue-Yellow

Latex with cotton flock lining, double-dipped. Length: 30 cm.

Thickness: 0,50 mm.











ZEPHIR VE210



Pink

Latex with cotton flock lining. Length: 30 cm. Thickness: 0,38 mm.

6/7 - 7/8 -8/9 - 9/10

6/7 - 7/8 -8/9 - 9/10

CE

EN388 1010

EN374-3 ABK A 2 > 30 mn B 2 > 30 mn K 4 > 120 mn



x 144

x 144











SYNTHETIC GLOVES Disposable

NITRILE

VENITACTYL V1400B100







Nitrile:

- Nitrile:

 Waterproof and airtight

 Flexibility, elasticity and tactility

 No allergies risks

 Protection against chemical products (occasional contact)


Powder-free glove :

• Protection of the object as no risk of leaving particles



Article	Colours	Description	Sizes	Standard	
VENITACTYL 1400B100	Blue	Powder-free nitrile. Suitable for food industry. AQL 1,5. Box of 100 disposable gloves.	6/7 - 7/8 - 8/9 - 9/10	C €	x 10

SYNTHETIC GLOVES Disposable



VINYL

VENITACTYL V1371



Transparent

Powdered vinyl. Suitable for food industry. AQL 1,5. Box of 100 disposable gloves.

6/7 - 7/8 -8/9 - 9/10

 ϵ

x 10







LEATHER GLOVES General handling





LEATHER GLOVES General handling



KNITTED GLOVES Handling requiring cut and heat resistance

KEVLAR®

KPG10











- Optimal cut peformance and good resistance to heat
 Excellent balance between heat resistance and dexterity

Ambidextrous Washable

10-cm knitted wrist :

Better vein protection



Article	Colours	Description	Sizes	Standard	
KPG10	Yellow	Kevlar® Technology outside. 100% cotton lining Gauge 7.	09	EN388 EN407	x 36



LEATHER GLOVES Welders works

GOATSKIN/LAMBSKIN/COWHIDE LEATHER

TERK400









Kevlar® Preox Alu:

High resistance to radiating heat

Thickness: 1,20 to 1,40 mm

Heat-resistant leather (HR) :

- Better Resistance to contact heat
- Reduction of the reactivity on flames contact
- Flexible leather





Article	Colours	Description	Sizes	Standard	
TERK400	Orange-Grey	Heat-resistant cowhide split leather palm (HR). Aluminised Kevlar Preox® back. Wool fleece lining. 20 cm cuff. Kevlar® Technology sewn. American assembly. Length: 40 cm. Thickness: 1,20 mm to 1,40 mm.	10	EN388 EN4143 EN12477 TYPEA	x 36

Kevlar® seams

TER250











Heat-resistant leather (HR):

- Better Resistance to contact heat
- Reduction of the reactivity on flames contact
- Flexible leather





Article	Colours	Description	Sizes	Standard	9
TER250	Brown-Grey	Heat-resistant cowhide split leather palm (HR). Wool fleece lining on palm. 20 cm cuff with canvas lining. Kevlar® Technology sewn. American assembly. Length: 40 cm.	10	EN388 4133 EN12477 TYPEA	



LEATHER GLOVES Welders works

COWHIDE LEATHER



KNITTED GLOVES Small handling

COTTON

Article	Colours	Description	Sizes	Standard	
TP169	White	65% polyester 35% cotton. PVC dots on palm. Gauge 7.	07/09	EN388 2131	x 300
CP149	Beige	Brushed drill cotton lining 270 g/m². French assembly. PVC dots on palm and full thumb, index and little finger.	08/10	C€	x 300




DISPOSABLE WEAR

TO FIND THE SUITABLE **PRODUCT FOR YOUR JOB** Suitable protection 104 DT117 106 DT221 107 DT115 108 DT215 108 **BLOUSPO** 110 P0106 110 TABP002 110 P0110 111 MANCHBE 111 MASOU 111 SURCHPE 111

► SMS (SPUN BOUND, MELT BLOWN, SPUN BOUND POLYPROPYLENE – NON WOVEN POLYPROPYLENE, MELT BLOWN, NON WOVEN) + CHEMICAL BARRIER – DT3XX

The combination of the two high performance polypropylene layers (chemical barrier) and 3 polypropylene layers (SMS) provides exceptional protection and provides a breathable fabric. The melt blown is incorporated with warm air to form a chemical barrier. The other two layers make the combination flexible and breathable.



MATERIALS

What material to choose?

▶ POLYETHYLENE (PE)


Is a flexible plastic fibre which provides good chemical resistances.

▶ POLYPROPYLENE (PP)

Is a nonwoven breathable fibre which provides excellent comfort.


► LAMINATED WOVEN MICROPOROUS MATERIAL - DT1xx

The combination of a polypropylene layer and a Polyethylene layer (PE) ensures outstanding properties and excellent protection against most chemical products and particles. The fabric is very resistant and lint free.




► SMS (SPUN BOUND, MELT BLOWN, SPUN BOUND POLYPROPYLENE – NON WOVEN POLYPROPYLENE, MELT BLOWN, NON WOVEN) - DT2xx

The combination of the three polypropylene layers provides exceptional protection and provides a breathable fabric. The melt blown is incorporated with warm air to form a chemical barrier. The other two layers make the combination flexible and breathable.



PERFORMANCES

What performance to choose according to your needs?







Article	Colours	Description	Sizes	Standard		
		Overall with elasticated hood. Non woven Deltachem®. Zip		EN14605 TYPE 3B TYPE 4B	EN14126	
DT300	Yellow	Fastening under double flap. Elasticated around the head, waist, cuffs and ankles. Individual pack.	M/L/XL/XXL	EN ISO 13982-1 TYPE 5B EN13034 TYPE 6B	EN1073-2 CLASS 2 EN1149-5	x 20





DISPOSABLE WEARChemical protection overalls

DT117











Deltatek 5000.



Article	Colours	Description	Sizes	Standard		
DT117	White	Overall with elasticated hood. Non-woven Deltatek® 5000. Fastening with zip under flap (top and bottom opening). Elasticated waist and ankles. Knitted wrist. Individual airtight pack.	M/L/XL/XXL	EN ISO 13982-1 TYPE 5-B EN13034 TYPE 6-B	EN14126 EN1073-2 CLASS 1 EN1149-5	x 20

DT221








Deltatek 6000.

Breathable



DELTATEK® 6000
100 % polypropylene SMMS*.
* Non woven Spunbound (x1), Melt
Blown (x2), Spunbound (x1)
The SMMS* process allows good
product breathability.



Article	Colours	Description	Sizes	Standard		9
DT221	White	Overall with elasticated hood. Non-woven Deltatek® 6000. Fastening with zip under flap (top and bottom opening). Elasticated round head, waist and ankles. Knitted wrist. Individual airtight pack.	M/L/XL/XXL	EN ISO 13982-1 TYPE 5 EN13034 TYPE 6	EN1073-2 CLASS 1 EN1149-5	x 20



DISPOSABLE WEARChemical protection overalls

DT115







Antistatic

ESSENTIAL version Microporous lamined



Article	Colours	Description	Sizes	Standard	
DT115	White	Overall with elasticated hood. Non-woven 70% polypropylene / 30% polyethylene. Fastening with zip under flap. Elasticated round head, waist, cuffs and ankles. Individual pack.	M/L/XL/XXL	EN ISO 13982-1 TYPE 5 EN13034 TYPE 6	x 50

DT215





Breathable Comfortable

ESSENTIAL version




Article	Colours	Description	Sizes	Standard		
DT215	White	Overall with elasticated hood. Non-woven 100% polypropylene SMS. Fastening with zip under flap. Elasticated round head, waist, cuffs and ankles. Individual pack.	M/L/XL/XXL	EN ISO 13982-1 TYPE 5	EN13034 TYPE 6	x 50




DISPOSABLE WEAROveralls - Coats - Aprons - Headwear






WORKWEAR

TO FIND THE SUITABLE PRODUCT FOR YOUR JOB






SIZES

Order the right size by taking the correct measurements

To take the correct measurements, take the measurements directly on the body, without tightenning.

▶ I.E. :

- The measurements outlined in the tables are for the **body**, not the garment.
- For wearing a garment over another, the width required is provided.



A	В	C
Chest measurement	Height	Waist measurement

SIZE EQUIVALENCE TABLE

MALE	XS	S	M	L	XL	XXL	3XL
FEMALE	S	M	L	XL	XXL	-	-

MALE	В	XS 156/164	S 156/164	M 164/172	L 172/180	XL 180/188	XXL 188/196	3XL 196/204
	EU	42/44	44/46	48/50	52/54	56/58	60/62	64/66
JACKET / BOMBER /	IT	36/38	38/40	42/44	46/48	50/52	54/56	58/60
BODYWARMER / OVERALL	DE	46/48	48/50	52/54	56/58	60/62	64/66	68/70
Chest measurement	cm	78/86	86/94	94/102	102/110	110/118	118/129	129/141
(A)	inch	321/2/34	34/37	37/40	40/43	43/461/2	461/2/501/2	501/2/551/2
	EU	32/34	34/36	38/40	42/44	46/48	50/52	54/56
TROUSERS /	IT/DE	36/38	38/40	42/44	46/48	50/52	54/56	58/60
DUNGAREES Waist measurement	cm	58/66	66/74	74/82	82/90	90/98	98/106	106/117
(C)	inch	23/26	26/29	29/32	32/351/2	351/2/381/2	381/2/411/2	411/2/46
TEE-SHIRT (A)	cm	76/79	80/88	89/97	98/106	107/115	116/124	125/133

FEMALE	В	156/164	164/172	172/180	180/188	188/196
	EU	36/38	38/40	42/44	46/48	50/52
JACKET / SMOCK /	UK	8/10	10/12	14/16	18/20	22/24
BODYWARMER Chest measurement	IT/DE	40/42	42/44	46/48	50/52	54/56
(A)	cm	82/86	86/94	94/102	102/113	113/125
	EU	/	38/40	42/44	46/48	50/52
TROUSERS	IT/DE	/	42/44	46/48	50/52	54/56
Waist measurement	cm	/	70/78	78/86	86/97	97/102
(C)	inch	/	271/2/31	31/34	34/38	38/40











DMACHCOM DMACHS	L DMACHPAN DMACHVES
-----------------	---------------------









DMACHCOM	DMACHSAL	DMACHPAN	DMACHVES









WORKWEAR D-Mach

DMACHCOM











A	rticle	Colours	Description	Material	Sizes	
	МАСНСОМ	Black-Red Grey-Orange Grey-Yellow	bias (top and bottom opening). 9 pockets including	Twill 65% polyester 35% cotton 245 g/m².	S/M/L/XL/ XXL/3XL CE	x 10

DMACHVES

















Material

 $\label{eq:continuous} \mbox{Jacket. Cuffs with press studs fastening. 4 pockets.} \qquad \mbox{Twill 65\% polyester 35\% cotton 245 g/m}^2.$





Sizes

S/M/L/XL/ XXL/3XL

	•	
C€	x 10	

DMACHPAN

Colours

Black-Red

Grey-Orange

Grey-Yellow

Description











Article

DMACHVES





Article	Colours	Description	Material	Sizes	
	Black-Red				
DMACHPAN	Grey-Orange	Trousers. Elasticated waist on both sides. 6 pockets including 1 ruler.	Twill 65% polyester 35% cotton 245 g/m ² .	S/M/L/XL/ XXL/3XL	x 10
	Grey-Yellow				

WORKWEAR D-Mach

DMSAL

DMACHSAL















120

























МССОМ	MCSAL	MCPAN	MCVES	MCCHE
-------	-------	-------	-------	-------











WORKWEAR Mach 2 Corporate

МССОМ













Article	Colours	Description	Material	Sizes	(
	Light grey-DarK grey				
MCCOM	Navy blue-Black	Overalls. Elasticated waist at the back. 8 pockets including 1 ruler. 2 Hand slits.	Twill 65% polyester 35% cotton 245 g/m².	S/M/L/XL/ XXL/3XL	(€ x 10
	Beige-Grey				

MCVES















Article	Colours	Description	Material	Sizes	
	Light grey-DarK grey				
MCVES	Navy blue-Black	Jacket Adjustable bottom of garment with press stud flap. 6 pockets.	Twill 65% polyester 35% cotton 245 g/m ² .	S/M/L/XL/ C€	x 10
	Beige-Grey				

MCPAN

















Article	Colours	Description	Material	Sizes		
	Light grey-DarK grey					
MCPAN	Navy blue-Black	Trousers. Elasticated waist on both sides. Preformed knees. 9 pockets including 1 ruler.	Twill 65% polyester 35% cotton 245 g/m².	S/M/L/XL/ XXL/3XL	C€	x 10
	Beige-Grey					

WORKWEAR Mach 2 Corporate

MCSAL















Article	Colours	Description	Material	Sizes	()
	Light grey-DarK gre				
MCSAL	Navy blue-Black	Dungarees. Adjustable elasticated braces. 10 pockets including 1 ruler.	Twill 65% polyester 35% cotton 245 g/m².	S/M/L/XL/ XXL/3XL	C € x 10
	Beige-Grey				

MCCHE




















Sleeves can be lifted up with tabs and buttons

Article	Colours	Description	Material	Sizes		
	Light grey-DarK grey					
MCCHE	Navy blue-Black	Shirt with long sleeves. Fastening with zip under velcro flap. 3 pockets.	Twill 65% polyester 35% cotton 200 g/m².	S/M/L/XL/ XXL/3XL	C€	x 10
	Beige-Grey					

127





WORKWEAR Mach 2

M2VES















Article	Colours	Description	Material	Sizes	•
	Grey-Orange				
M2VES	Navy blue-Royal blue	Jacket. Raglan sleeves. Cuffs with press stud fastening. 4 pockets including 1 on the sleeve.	Twill 65% polyester 35% cotton 245 g/m².	S/M/L/XL/ XXL/3XL	C € x 10
	Black-Grey				

M2PAN













Kneepad pockets M2PAN - M2SAL - M2COM



Article	Colours	Description	Material	Sizes	9
	Grey-Orange				
M2PAN	Navy blue-Royal blue	Trousers. Elasticated waist on both sides. 7 pockets including 1 ruler.	Twill 65% polyester 35% cotton 245 g/m².	S/M/L/XL/ XXL/3XL	E x 10
	Black-Grey				

M2COM













Badge holder M2VES - M2COM

Kneepad pockets M2PAN - M2SAL - M2COM



Article	Colours	Description	Material	Sizes	
	Grey-Orange				
M2COM	Navy blue-Royal blue	Overalls. Zip fastening under bias. Elasticated waist. Cuffs with press stud fastening. 9 pockets including 1 on the sleeve.	Twill 65% polyester 35% cotton 245 g/m ² .	S/M/L/XL/ XXL/3XL C€	x 10
	Black-Grey				

WORKWEAR Mach 2

M2SAL













Kneepad pockets M2PAN - M2SAL - M2COM



Article	Colours	Description	Material	Sizes	
	Grey-Orange				
M2SAL	Navy blue-Royal blue	Dungarees. Adjustable elasticated braces. 8 pockets including 1 ruler.	Twill 65% polyester 35% cotton 245 g/m².	S/M/L/XL/ XXL/3XL	₹ x 10
	Black-Grey				

M2GIL

















Article	Colours	Description	Material	Sizes	
M2GIL	Grey-Orange Navy blue-Royal blue	Multipocket vest. Bias finishing. 13 pockets.	Twill 65% polyester 35% cotton 245 g/m².	S/M/L/XL/ XXL/3XL CE	x 10
M2BER			-		





Article	Colours	Description	Material	Sizes	
IVIZDLI1	Grey-Orange Navy blue-Royal blue	Bermuda. Elasticated waist on both sides. 7 pockets including 1 ruler.	Twill 65% polyester 35% cotton 245 g/m².	S/M/L/XL/XXL CE	x 10





WORKWEAR Panostyle

M6COM











Article	Colours	Description	Material	Sizes	
	Grey-Orange			XS/S/M/L/XL/ C€ XXL/3XL	
M6COM	Brown-Green	Overalls. Front zip fastening with bias finishing.	Twill 65% polyester 35% cotton 235 g/m².		x 10
	Grey-Green	Elasticated waist. Elasticated cuffs. 7 pockets.			
	Navy blue-Orange				

M6VES













Article	Colours	Description	Material	Sizes	()
M6VES	Grey-Orange				
	Brown-Green	Jacket. Front zip fastening with bias finishing.	Twill 65% polyester 35% cotton 235 g/m².	XS/S/M/L/XL/ CE	x 10
	Grey-Green	Elasticated cuffs. 4 pockets.	This consposed to a colon 200 gm.	XXL/3XL	
	Navy blue-Orange				

M6PAN













Article	Colours	Description	Material	Sizes	
M6PAN	Grey-Orange				
	Brown-Green	Trousers. Elasticated waist on both sides. 5 pockets	Twill 65% polyester 35% cotton 235 g/m².	XS/S/M/L/XL/ €	x 10
	Grey-Green	including 1 ruler.		XXL/3XL	
	Navy blue-Orange				

WORKWEAR Panostyle

M6SAL











Article	Colours	Description	Material	Sizes	
	Grey-Orange				
M6SAL	Brown-Green	Dungarees. Elasticated waist on both sides.	Twill 65% polyester 35% cotton 235 g/m².	XS/S/M/L/XL/ (€ XXL/3XL	x 10
	Grey-Green	Adjustable elasticated braces. 6 pockets.	v	XXL/3XL	
	Navy blue-Orange				

M6GIL













Article	Colours	Description	Material	Sizes	
M6GIL	Grey-Orange				
	Brown-Green	Multipocket vest. Front zip fastening with bias	Twill 65% polyester 35% cotton 235 g/m².	XS/S/M/L/XL/ C€	x 10
	Grey-Green	finishing. Bias finishing. 6 pockets.		XXL/3XL	
	Navy blue-Orange				

WORKWEAR Mach Spring

MSGIL











Multipockets



Article	Colours	Description	Material	Sizes	
MSGIL	Beige	Stonewashed multipocket vest. Bias finishing. 13 pockets.	Twill 65% polyester 35% cotton 245 g/m 2 . Polyester mesh lining.	S/M/L/XL/ XXL/3XL	(x 10

MSPAN











Kneepad pockets







Convertible legs with zip (3 lengths)



Article	Colours	Description	Material	Sizes	
MSPAN	Beige	3 in 1 stonewashed trousers. 7 pockets including 1 ruler.	Twill 65% polyester 35% cotton 245 g/m ² .	S/M/L/XL/ XXL/3XL	x 10

WORKWEAR

PALAOS







PALAOSHV







Article	Colours	Description	Material	Sizes	
	Bugatti blue				
PALAOS	······ Orange	Overall. Opening with double zip and press studs tab. Raglan sleeves. Elasticated waist at the back. 5 pockets including 1 meter.	Twill 100% Cotton 290 g/m ² .	S/M/L/XL/ XXL/3XL/4XL C €	x 10
PALAOSHV	- Tanga				

WORKWEAR Lady - Caps - Belts

LAETITIA











	Article	Colours	Description	Material	Sizes	
LACTITU	LACTITIA	White	Slimfit jacket. Long sleeves. 3 pockets including	Ripstop canvas 65% polyester 35% cotton	38/40→50/52 (€	10
	LAETITIA	Green	1 on the sleeve	180 g/m².	38/40→50/52 €	X 10
	VERONA		AT	OLL 🚜 🏗		





Article	Colours	Description	Material	Sizes	
	Red-Grey				
VERONA	Black-Grey Grey-Orange	Cap (To match the MACH range).	Twill 65% polyester 35% cotton 245 g/m².	One size	x 100
	Navy blue-Royal b	lue			
ATOLL	Grey	Belt.	100% polyester.		

WORKWEAR High Visibility Workwear

PHVES













Article	Colours	Description	Material	Sizes	Standard	
PHVES	Fluorescent yellow- Navy blue Fluorescent orange- Navy blue	Jacket. Elasticated cuffs. High visibility: Class 2 - Silver colour - Shoulder-belt and parallel assembly. 2 pockets.	Twill 54% cotton 46% polyester 260 g/m². Retro-reflective sewn bands.	S/M/L/XL/ XXL/3XL	C €	x 10

PHPAN












internal kneepad pocket



	Article	Colours	Description	Material	Sizes	Standard	
	DUDAN	Fluorescent yellow- Navy blue	Trousers. Elasticated waist on both sides. High visibility: Class 2 - Silver	Twill 54% cotton 46% polyester 260 g/m².	S/M/L/XL/	C 6 M EN ISO 20471	v 10
PHPAN	FIIFAIN	Fluorescent orange- Navy blue	colour. 5 pockets including 1 ruler pocket.	Retro-reflective sewn bands.	XXL/3XL CC 2		x 10

OUTDOOR WEAR



MATERIALS



Material made up of 2 layers.

- Outer layer
- Membrane

Breathable - Impermeable - Comfortable




SIZES

Order the right size by taking the correct measurements

To take the correct measurements, take the measurements directly on the body, without tightening.

▶ I.E. :

- The measurements outlined in the tables are for the **body**, not the garment.
- \bullet For wearing a garment over another, the width required is provided.



A	В	C	
Chest measurement	Height	Waist measurement	

SIZE EQUIVALENCE TABLE

MALE	В	XS 156/164	S 156/164	M 164/172	L 172/180	XL 180/188	XXL 188/196	3XL 196/204
JACKET / BOMBER / PARKA / VEST Chest measurement (A)	EU	44/46	46/48	48/50	50/52	52/54	54/56	56/58
	IT	36/38	38/40	42/44	46/48	50/52	54/56	58/60
	DE	48/50	50/52	52/54	54/56	56/58	58/60	60/62
	cm	90/94	94/98	98/102	102/106	106/110	110/114	114/118
	inch	351/2/37	37/381/2	381/2/40	40/411/2	41 1/2 / 43 1/2	431/2/45	45/46 ^{1/2}
TROUSERS Waist measurement (C)	EU	/	34/36	38/40	42/44	46/48	50/52	54/56
	IT/DE	/	38/40	42/44	46/48	50/52	54/56	58/60
	cm	/	66/74	74/82	82/90	90/98	98/106	106/117
	inch	/	26/29	29/32	32/351/2	35 ^{1/2} /38 ^{1/2}	38 ^{1/2} /41 ^{1/2}	411/2/46
UNDERWEAR Chest measurement (A)	EU	/	34/36	38/40	42/44	46/48	50/52	54/56
	IT/DE	/	38/40	42/44	46/48	50/52	54/56	58/60
	cm	/	78/86	86/94	94/102	102/110	110/118	118/123
Waist measurement (C)	inch	/	301/2/34	34/37	37/40	40/431/2	431/2/461/2	461/2/481/2
	cm	/	66/74	74/82	82/90	90/98	98/106	106/117
	inch	/	26/29	29/32	32/35 ^{1/2}	35 ^{1/2} /38 ^{1/2}	38 ^{1/2} /41 ^{1/2}	411/2/46



MILTON









WATERPROOF AND BREATHABLE Water vapour resistance Ret < 20 m² Pa/W with ISO11092 and EN31092



Article	Colours	Description	Material	Sizes		
MILTON	Black	Parka. Waterproof seams. Fastening with zip under velcro storm flap. Removable wadded hood. Adjustable bottom of garment with elastic drawstring. 5 pockets.	94% polyester 6% elasthane fabric, 2 laminated layers. Yokes: Polyurethane-coated Oxford polyester fabric. Quilted Taffeta polyester lining.	S/M/L/XL/ XXL/3XL	C€	x 10

DUNCAN













Article	Colours	Description	Material	Sizes	Standard	
DUNCAN	Grey	Parka. Waterproof seams. Fastening with zip under velcro storm flap. Removable hood. Underarm ventilation with eyelets. Adjustable bottom of garment with elastic drawstring. 5 pockets.	PVC-coated Ripstop polyester fabric. Top lining: Wadded polyester polar fleece. Bottom lining: Wadded polyester Taffeta.	S/M/L/XL/ XXL/3XL	EN14058 3 3 X 0,271m² K/W X EN343 3 1*	x 10

HELSINKI













Article	Colours	Description	Material	Sizes	Standard	
HELSINKI	Navy blue	Parka. Waterproof seams. Fastening with zip under press studs storm flap. Adjustable cuffs with drawstring. 6 pockets.	PVC-coated polyester fabric. Wadded polyester Taffeta lining.	S/M/L/XL/ XXL/3XL	EN342 0,436m J/W (B) X X EN343 3 1-	x 10

DARWIN II ***





























Article	Colours	Description	Material	Sizes	Standard	Û
DARWIN II	Navy blue	Parka. Waterproof seams. Fixed hood. Adjustable waist and bottom of garment with drawstring. Knitted cuffs. 6 pockets.	PVC-coated polyester fabric. Quilted polyester Taffeta lining.	XS/S/M/L/ XL/XXL	EN343	x 10
GOTEBORG	Navy blue	Parka. Waterproof seams. Collar with polar fleece lining. Fastening with zip under velcro storm flap. Removable hood. Adjustable bottom of garment with elastic drawstring. 5 pockets.	PVC-coated Twill polyester fabric. Top lining: Wadded polyester polar fleece. Bottom lining: Wadded polyester Taffeta.	S/M/L/XL/ XXL/3XL	EN14058 3.3 X 0.250 m² K/W X EN343 3 1*	x 10



RANDERS









Article	Colours	Description	Material	Sizes	
RANDERS	Grey	Quilted bomber jacket with removable sleeves (To match the D-MACH range). Fastened with a zip under the storm flap with press studs. Knitted cuffs and bottom of narment 5 pockets	Quilted polyurethane-coated polyamide fabric. Lining: Quilted in polyester Taffeta.	S/M/L/XL/ XXL/3XL CE	x 10



RENO











Colours	Description	Material	Sizes	
Navy blue	Pember include with removable alegans. Coller with			
Black	polar fleece lining. Knitted cuffs and bottom of	Polyurethane-coated Oxford polyester fabric. Polyester polar fleece lining.	S/M/L/XL/ C€	x 10
Green	garment. 5 роскетs.			
			NA.	
	Black	Navy blue Bomber jacket with removable sleeves. Collar with Black polar fleece lining. Knitted cuffs and bottom of garment. 5 pockets.	Navy blue Bomber jacket with removable sleeves. Collar with Black polar fleece lining. Knitted cuffs and bottom of garment. 5 pockets. Polyurethane-coated Oxford polyester fabric. Polyester polar fleece lining.	Navy blue Bomber jacket with removable sleeves. Collar with polar fleece lining. Knitted cuffs and bottom of garment. 5 pockets. Navy blue Bomber jacket with removable sleeves. Collar with Polyurethane-coated Oxford polyester fabric. S/M/L/XL/ Polyester polar fleece lining.



Article	Colours	Description	Material	Sizes	
BARI	Navy blue	Bomber jacket. Waterproof seams. Raglan sleeves. Elasticated bottom of garment. Underarm ventilation with eyelets. 6 pockets.	Polyurethane-coated Taslon polyamide fabric. Polyester body lining. Wadded polyester Taffeta sleeve lining.	S/M/L/XL/ XXL/3XL C€	x 10

OUTDOOR WEAR Bodywarmers

FIDJI













Extra comfort opening on both sides



OUTDOOR WEAR Bodywarmers

STOCKTON















Article	Colours	Description	Material	Sizes	•
	Navy blue-Royal bl				
STOCKTON	Grey-Orange	Multipocket bodywarmer. Adjustable bottom with elastic drawstring. 7 pockets.	Quilted twill 65% polyester 35% cotton 235 g/m ² . Wadded polyester Taffeta lining.	S/M/L/XL/ XXL/3XL	(x 10
	Black-Grey		Tradeou porfector randa ininig.		

M2PAW









Kneepad pockets





Article	Colours	Description	Material	Sizes	
MODAW	Black-Grey	Warm trousers. Elasticated waist on both sides. 7	Twill 65% polyester 35% cotton 245 g/m ² .	S/M/L/XL/	x 10
M2PAW	Grey-Orange	pockets including 1 ruler.	100% flanel cotton lining.	XXL/3XL	X 10

OUTDOOR WEAR Bodywarmers

SIERRA

















			UIZUS	
/ blue				
/ blue-Red	Multipocket bodywarmer. Elasticated on both sides	65% polyester 35% quilted cotton canvas.	S/M/L/XL/	00
a	and back. 7 pockets.	Wadded polyester Taffeta lining.	XXL/3XL	X 20
n				
r	blue-Red	Multipocket bodywarmer. Elasticated on both sides and back. 7 pockets.	Multipocket bodywarmer. Elasticated on both sides and back. 7 pockets. Multipocket bodywarmer. Elasticated on both sides wadded polyester 35% quilted cotton canvas. Wadded polyester Taffeta lining.	blue-Red Multipocket bodywarmer. Elasticated on both sides and back. 7 pockets. Multipocket bodywarmer. Elasticated on both sides Wadded polyester 35% quilted cotton canvas. Wadded polyester Taffeta lining. S/M/L/XL/ XXL/3XL

SACHA











Article	Colours	Description	Material	Sizes	
SACHA	Green	Bodywarmer. 4 pockets	Ripstop canvas 65% polyester 35% cotton 180 g/m². Wadded polar fleece polyester lining.	38/42/46/50 (€	x 10

OUTDOOR WEAR Rain


400















Article	Colours	Description	Material	Sizes	Standard	•
400	Navy blue	Rain jacket and trousers. Waterproof seams. JACKET: Fixed hood. Fastening with zip under storm flap.			FN040	
	Yellow	Raglan sleeves. Adjustable cuffs with press-studs. 2 pockets. TROUSERS:	PVC-coated polyester fabric.	M/L/XL/XXL	C E EN343	x 20
	Royal blue	Elasticated waist. Adjustable bottom of legs with press-studs. 2 hand slits.				
	Green	ieys willi piess-stuus. 2 Hanu siits.				

304







Ventilation back flap Underarm ventilation eyelets





Article	Colours	Description	Material	Sizes	Standard	
304	Yellow	Rain jacket and trousers. Sealed seams. JACKET: Fixed hood. Fastening with zip under press-studs flap. Raglan sleeves. Elasticated inside cuffs. 2 pockets. TROUSERS: Elasticated waist. Fly closed with press-studs. Adjustable bottom of legs with press-studs. 2 hand slits.	PVC-coated polyester support. Double sided coating.	M/L/XL/XXL	C € (3) 3 1*	x 10

MA400







Ventilation back flap Underarm ventilation eyelets



Article	Colours	Description	Material	Sizes	Standard	
MA400	Yellow	Rain coat. Waterproof seams. Fixed hood. Fastening with zip under storm flap. Elasticated inside cuffs. 2 pockets.	PVC-coated polyester fabric.	M/L/XL/XXL	C € (\$\frac{\mathbb{E}}{3}\) \\ \frac{3}{1*}\\ \]	x 20

305







Length 1,20 m


Ventilation back flap Underarm ventilation eyelets



Article	Colours	Description	Material	Sizes	Standard	
305	Yellow	Rain coat. Sealed seams. Fixed hood. Fastening with double press-stud flap. Raglan sleeves. Elasticated inside cuffs. 2 pockets.	PVC-coated polyester support. Double side coating.	M/L/XL/XXL	C € (\$\frac{\text{EN343}}{\text{3}}\frac{\text{3}}{\text{1*}}	x 10

TECHNICAL WEAR

TO FIND THE SUITABLE PRODUCT FOR YOUR JOB Suitable A 🕮 🕮 🦥 protection 168 TONP3 168 TONV3 168 BORCO 169 BORPA 169 BORVE 169 OPTIMUM 162 FIDJIHV 163 ICEBERG 166 NORDLAND 166 C0600 173 MAICO 170 MAIPA 170 MAIVE 170 CAFR1 171 CHEFR 172 POLFR 172 VESER 172 171 SSVFR VESTE19A 174 VESTE19N 174 PANTA19A 174 174 PANTA19N CAGOULE19A 175 CAGOULE19N 175 COMBI19A 175 COMBI19N 175 **GUETRE19A** 175 GUETRE19N 175 MANTEAU19A 175



RETRO-REFLECTIVE TECHNOLOGY

They reflect the light of vehicle headlights back to their source and improve visibility distance of a pedestrian by 30 to 160 metres.

3M SCOTCHLITE™ TECHNOLOGY

 Micro-ball technology: glass micro-balls encased in a reflective resin.



175

MANTEAU19N

SIZE EQUIVALENCE TABLE

Workwear

MALE	В	XS 156/164	S 156/164	M 164/172	L 172/180	XL 180/188	XXL 188/196	3XL 196/204
	EU	42/44	44/46	48/50	52/54	56/58	60/62	64/66
JACKET / BOMBER /	IT	36/38	38/40	42/44	46/48	50/52	54/56	58/60
BODYWARMER / OVERALL	DE	46/48	48/50	52/54	56/58	60/62	64/66	68/70
Chest measurement	cm	78/86	86/94	94/102	102/110	110/118	118/129	129/141
(A)	inch	321/2/34	34/37	37/40	40/43	43/461/2	461/2/501/2	501/2/551/2
	EU	32/34	34/36	38/40	42/44	46/48	50/52	54/56
TROUSERS /	IT/DE	36/38	38/40	42/44	46/48	50/52	54/56	58/60
DUNGAREES Waist measurement	cm	58/66	66/74	74/82	82/90	90/98	98/106	106/117
(C)	inch	23/26	26/29	29/32	32/35 ^{1/2}	35 ^{1/2} /38 ^{1/2}	381/2/411/2	411/2/46
TEE-SHIRT (A)	cm	76/79	80/88	89/97	98/106	107/115	116/124	125/133

Outdoor Wear

MALE	В	XS 156/164	S 156/164	M 164/172	L 172/180	XL 180/188	XXL 188/196	3XL 196/204
	EU	44/46	46/48	48/50	50/52	52/54	54/56	56/58
	IT	36/38	38/40	42/44	46/48	50/52	54/56	58/60
JACKET / BOMBER / PARKA / VEST	DE	48/50	50/52	52/54	54/56	56/58	58/60	60/62
Chest measurement (A)	cm	90/94	94/98	98/102	102/106	106/110	110/114	114/118
(~)	inch	351/2/37	37/381/2	381/2/40	40/411/2	411/2/431/2	431/2/45	45/46 ^{1/2}
	EU	/	34/36	38/40	42/44	46/48	50/52	54/56
TROUSERS	IT/DE	/	38/40	42/44	46/48	50/52	54/56	58/60
Waist measurement	cm	/	66/74	74/82	82/90	90/98	98/106	106/117
(C)	inch	/	26/29	29/32	32/35 ^{1/2}	351/2/381/2	381/2/411/2	411/2/46
UNDERWEAR	EU	/	34/36	38/40	42/44	46/48	50/52	54/56
Chest measurement	IT/DE	/	38/40	42/44	46/48	50/52	54/56	58/60
(A)	cm	/	78/86	86/94	94/102	102/110	110/118	118/123
Waist measurement	inch	/	301/2/34	34/37	37/40	40/431/2	431/2/461/2	461/2/481/2
(C)	cm	/	66/74	74/82	82/90	90/98	98/106	106/117
	inch	/	26/29	29/32	32/35 ^{1/2}	351/2/381/2	381/2/411/2	411/2/46

TECHNICAL WEAR Outdoor high visibility

OPTIMUM











Article	Colours	Description	Material	Sizes	Standard	
OPTIMUM	Fluorescent yellow- Navy blue Fluorescent orange- Navy blue	Parka 4 in 1: removable bodywarmer. Parka: Waterproof seams. Fastening with zip under storm flap. Fixed hood. Polar fleece collar. High visibility: Class 3 - Silver colour - Shoulder-belt and parallel assembly. 4 pockets. Removable jacket: Waterproof seams. Removable sleeves. High visibility: Class 2 - Silver colour - Shoulderbelt assembly. 4 pockets.	PVC-coated Oxford polyester fabric. Fixed polyester Taffeta lining. PVC-coated Oxford polyester removable bodywarmer with removable sleeves in polyester polar fleece. Quilted polyester Taffeta lining. Retro-reflective sewn bands.	S/M/L/XL/ XXL/3XL	EN ISO 20471 PARKA/BODYWARMER 3/2 EN343 PARKA 3 1*	x 10

EASYVIEW















Article	Colours	Description	Material	Sizes	Standard	
EASYVIEW	Fluorescent yellow- Navy blue Fluorescent orange- Navy blue	Warm parka Waterproof seams. Fixed hood. Fastening with zip under velcro storm flap. High visibility: Class 3 - Silver colour - Shoulder-belt and parallel assembly. 4 pockets.	Polyurethane-coated Oxford polyester fabric. Quilted polyester Taffeta lining. Retro-reflective sewn bands.	S/M/L/XL/ XXL/3XL	EN ISO 20471	x 10











Article	Colours	Description	Material	Sizes	Standard	
Article	Colours	Description	Material	51268	Stanuaru	
FIDJI HV	Fluorescent yellow- Navy blue	Reversible body warmer. Zip fastening. 4 pockets. High visibility: Class 2 - Silver colour - Shoulderbelt assembly.	Polyurethan-coated Oxford polyester fabric on 1 side. Quilted polyester taffeta fabric on 1 side. Retro-reflective sewn bands.	S/M/L/XL/ XXL/3XL	C €	x 10

GILP4













Article	Colours	Description	Material	Sizes	Standard	
GII P4	Fluorescent yellow	Vest. Fastening with velcro band. High visibility:				
	Fluorescent orange	Class 2 - Silver colour - Shoulder-belt assembly.	Polyester fabric.	1.000	(6 N EN ISO 20471	100
	Fluorescent yellow	Vest. Fastening with velcro band. High visibility:	Polyester fabric. Retro-reflective sewn bands.	L/XXL	СС Ш2	x 100
GILP2	Fluorescent orange	Class 2 - Silver colour - Parallel assembly.				

TECHNICAL WEAR High Visibility Workwear

PHVES













Article	Colours	Description	Material	Sizes	Standard	
PHVES	Fluorescent yellow- Navy blue Fluorescent orange- Navy blue	Jacket. Elasticated cuffs. High visibility: Class - 2 - Silver colour - Shoulder-belt and parallel assembly. 2 pockets.	Twill 54% cotton 46% polyester 260 g/m². Retro-reflective sewn bands.	S/M/L/XL/ XXL/3XL	C €	x 10

PHPAN











internal kneepad pocket



Article	Colours	Description	Material	Sizes	Standard	
PHPAN	Fluorescent yellow- Navy blue Fluorescent orange- Navy blue	Trousers. Elasticated waist on both sides. High visibility: Class 2 - Silver colour. 5 pockets including 1 ruler pocket.	Twill 54% cotton 46% polyester 260 g/m². Retro-reflective sewn bands.	S/M/L/XL/ XXL/3XL	C € EN ISO 20471	x 10

TECHNICAL WEAR Chill Room and Cold Store

NORDLAND











Article	Colours	Description	Material	Sizes	Standard	Ŷ
NORDLAND	Grey	Parka. Waterproof seams. Removable hood. Collar with polar fleece lining. Fastening with double zip under press stud storm flap. Adjustable waist and bottom with elastic drawstring. 7 pockets.	Polyurethane-coated Oxford polyester fabric. Quilted polyester Taffeta lining.	S/M/L/XL/ XXL/3XL	C € 0.705 m².K/W X 3 X X	x 5

ICEBERG



protection











Article	Colours	Description	Material	Sizes	Standard	
ICEBERG	Grey	Warm Salopette. Waterproof seams. Adjustable waist with elastic drawstring. Adjustable braces. Preformed and reinforced knees. 5 pockets.	Polyurethane-coated Oxford polyester fabric. Quilted polyester Taffeta lining.	S/M/L/XL/ XXL/3XL	EN342 0.705 m².K/W X 3 X	x 5



TECHNICAL WEAR Anti-acid - Flame retardant - Antistatic

TONC3

































TONP3

















Article	Colours	Description	Material	Sizes	Standard	
TONC3		Coverall, concealed stud Mandarin collar, Zip front fastening with concealed studded flap. Elasticated rear waist band, Raglan sleeve with concealed adjustable cuffs. 4 pockets including 1 on the leg.			EN13034 TYPE 6	
TONV3	Navy blue	Jacket, concealed stud Mandarin collar. Concealed Stud front fastening. Raglan sleeve with concealed adjustable cuffs. Side elastication and 2 side pockets with flap over.	60% Modacrylic 37% cotton 3% antistatic fibre 250 g/m².	S/M/L/XL/ XXL/3XL/4XL	EN ISO 11612 AI, BI, CI, X, EI, FI EN1149-5	x 5
TONP3		Trousers. Fastening with hidden press studs. Side elastication. 4 pockets including 1 on leg.				

TECHNICAL WEAR Anti-acid - Flame retardant - Antistatic

BORCO





























Article	Colours	Description	Material	Sizes	Standard	
RORCO	Navy blue	Overalls. Straight collar closed with hidden press studs. Fastening with hidden press studs.				
BONGO	Orange Elasticated waist at the back. Half elasticated cuffs. 6 pockets including 1 ruler pocket. 2 hand slits.				EN13034 TYPE 6	
		Jacket. Straight collar closed with hidden press studs. Fastening with hidden press studs. Half	Ripstop 55% Modacrylic/	S/M/L/XL/	EN531 AB1 C1 XX	
BORVE	Navy blue	elasticated cuffs. 3 pockets including 1 inside chest pocket.	Staciflam® 42% cotton 3% antistatic fibre 295 g/m².	S/M/L/XL/ XXL/3XL/4XL	EN533 3/50X75°C 3/50/60°C BORCOOV	x 5
					EN1149-5	
BORPA	Navy blue	Trousers. Fastening with hidden press studs. Side elastication. 4 pockets including 1 on leg.				

TECHNICAL WEAR Flame retardant



Article	Colours	Description	Material	Sizes	Standard	
MAICO		Overalls with high Mandarin collar, zip fastening with concealed studded cover, raglan sleeve with half elasticated cuffs, rear elasticated waistband. 7 pockets including ruler pocket and trouser access on both sides.			EN14116 3/500/75	
MAIVE	Navy blue	Jacket. High collar. Raglan sleeves. Half elasticated cuffs. 4 pockets including 2 inside pockets.	Twill 100% flame retardant cotton 310 g/m ² .	S/M/L/XL/ XXL/3XL/4XL	EN531 AB1 C1 XX	x 5
MAIPA		Trousers. Elasticated waist on both sides. 5 pockets including 1 ruler pocket.				









Preformed elbows MAIVE- MAICO

3M Scotchlite™ retro-reflective sewn bands

50 washes at 60°C



Article	Colours	Description	Material	Sizes	Standard	9
	Blue	Overalls with high Mandarin collar, zip fastening with			EN14116	
MAICO	Orange	concealed studded cover, raglan sleeve with half elasticated cuffs, rear elasticated waistband. 7 pockets including ruler pocket and trouser access on both sides.	Twill 100% flame retardant cotton 310 g/m ² .	S/M/L/XL/ XXL/3XL/4XL	3/5-01/60 EN531 A B1 C1 XX	x 5
	Red	511 55 th 51 to 10 to 51			•	

CAFR1





SSVFR















Article	Colours	Description	Material	Sizes	Standard		
CAFR1 SSVFR	Navy blue	Hood with flap covering shoulders. Underwear set. Long sleeve tee-Shirt and Long Johns.	50% Aramid knitwear 48% Viscose 2% Antistatic fibre 200 g/m².	One size S/M/L/XL/ XXL/3XL/4XL	EN14116 3/12H/60	EN1149-5	x 50

TECHNICAL WEAR Flame retardant - Antistatic

CHEFR











Article	Colours	Description	Material	Sizes	Standard		
CHEFR	Navy blue	Long Sleeve shirt,concealed stud fastening and cuffs. 2 pockets.	Ripstop 55% Modacrylic/ Staciflam® 42% cotton 3% antistatic fibre 180 g/m².	S/M/L/XL/ XXL/3XL/4XL	EN14116 37 501 / 75 EN531 A B1 C1 XX	EN1149-5	x 10

VESFR











Article	Colours	Description	Material	Sizes	Standard			
VESFR	Navy blue	Polar Fleece jacket. 2 pockets.	Polar 60% Modacrylic 38% cotton 2% antistatic fibre 430 g/m².	S/M/L/XL/ XXL/3XL/4XL	C € Sy 12H/ 60	EN1149-5	x 10	

POLFR











Article	Colours	Description	Material	Sizes	Standard		
POLFR	Navy blue	Long Sleeve Polo shirt with concealed stud collar.	Piqué knit Modacrylic/Cotton Antistatic fibre 280 g/m².	S/M/L/XL/ XXL/3XL/4XL	C € S/12H/60	EN1149-5	x 10

TECHNICAL WEAR Chemical protection overalls

CO600















Article	Colours	Description	Material	Sizes	Standard	
C0600	Green	Chemical protective overall type 3, liquid-tight. Raglan sleeves. Sealed seams. Zip fastening with studded cover flap and Velcro straps. Fixed elasticated hood, elasticated at wrist and ankles.	Polyester support with double sided PVC 380 g/m² coating.		C € TYPE 3	x 10

Protective aprons

TABALPV







Article	Colours	Description	Material	Sizes	Û
TABALPV	White	Apron. Adjustment buckle on the neck. Dimensions: 120 cm x 90 cm. Thickness: 0,30 mm.	100% PVC.	One size	x 50

TECHNICAL WEAR Flame retardant

VESTE19A - VESTE19N







PANTA19A - PANTA19N







Article	Description	Material	Sizes	Standard	
VESTE19A	Heat and projection resistant jacket. Straight bottom of sleeve. Snap and adhesive band closure.	Pre-oxyded PAN/Para-Aramide REFLESPACE® aluminization 515 g/m². Lining with 100% cotton PROBAN® 310 g/m².		EN ISO 11612 A1, B1, C3, D3 E3, F1	x 1
VESTE19N	Available on demand.	VISCOSE with REFLESPACE® aluminization 580 g/m². Lining with 100% cotton PROBAN® 310 g/m².	M/L/XL/ XXL/3XL		x 1
PANTA19A	Heat and protection resistant trousers. Straight bottom of leg. Snap and adhesive band closure.	Pre-oxyded PAN/Para-Aramide REFLESPACE® aluminization 515 g/m². Lining with 100% cotton PROBAN® 310 g/m².			x 1
PANTA19N	Floritation Annalists and demand	VISCOSE with REFLESPACE® aluminization 580 g/m ² . Lining with 100% cotton PROBAN® 310 g/m ² .			x 1



Article	Description	Material	Sizes	Standard	G
CAGOULE19A	Heat and protection resistant hood. Assembled on adjustable headband. Side ventilation slits.	Pre-oxyded PAN/Para-Aramide REFLESPACE® aluminization 515 g/m². Lining with 100% cotton PROBAN® 310 g/m².	ONE SIZE		x 1
CAGOULE19N	Available on demand.	VISCOSE with REFLESPACE® aluminization 580 g/m². Lining with 100% cotton PROBAN® 310 g/m².			x 1
COMBI19A	Heat and protection resistant overall. Straight sleeve and bottom of leg. Zip fastener protected by adhesive flap. Available on demand.	Pre-oxyded PAN/Para-Aramide REFLESPACE® aluminization 515 g/m². Lining with 100% cotton PROBAN® 310 g/m².	M/L/XL/	EN ISO 11612 A1, B1, C3, D3, E3, F1	x 1
COMBI19N		VISCOSE with REFLESPACE® aluminization 580 g/m². Lining with 100% cotton PROBAN® 310 g/m².			x 1
MANTEAU19A	Heat and protection resistant coat. Straight bottom of sleeve. Snap and adhesive band closure.	Pre-oxyded PAN/Para-Aramide REFLESPACE® aluminization 515 g/m². Lining with 100% cotton PROBAN® 310 g/m².	XXL/3XL		x 1
MANTEAU19N	Available on demand.	VISCOSE with REFLESPACE® aluminization 580 g/m². Lining with 100% cotton PROBAN® 310 g/m².			x 1
GUETRE19A	Heat and protection resistant gaiters. Back opening	Pre-oxyded PAN/Para-Aramide REFLESPACE® aluminization 515 g/m². Lining with 100% cotton PROBAN® 310 g/m².	ONE SIZE		x 1
GUETRE19N	with flap. Available on demand.	VISCOSE with REFLESPACE® aluminization 580 g/m². Lining with 100% cotton PROBAN® 310 g/m².			x 1

FOOT PROTECTION



TO FIND THE SUITABLE PRODUCT FOR YOUR JOB

	REPRESE	JUREL OF	CECON CECON	HING HING	STRA	STRA	STORES	THOMME OIL	AT MINI	AG HAT	HERE	
1	6	1	A		444			峄	Fa.	本	Suitable protection	PAGES
Wal		•									TREK WORK	180
PREMIUM			•			•					X-RUN	182
				•							OUTDOOR	184
											COMPOSITE TECH	186
z		•									PRO TECH	188
											SPORTSWEAR	190
EVOLUTION											LIGHT WALKERS	192
ш		•		•				•			4 X 4 INDUSTRY	196
		•									X-LARGE INDUSTRY	200
		•		•							ESD	202
		•									CLASSIC +	204
IAL		•									CLASSIC INDUSTRY	205
ESSENTIAL		•									WINTER BOOT	208
ESS		•									RAIN BOOT	208
											AGRO	209

RANGES













	TREK WORK	X-RUN	OUTDOOR .	COMPOSITE TECH	PROTECH	SPORTSWEAR
Material	PU / NITRILE RUBBER	PU / RUBBER	PU / PU	PU / RUBBER	PU / PU	PU / RUBBER
Advantages	Ladder grips Flex-Zone for increased flexibility Slip-resistant cleated outsole	 Flex zones Anti slip rubber TPU foot arch reinforcement 	Ladder grips V STAB SYSTEM Flex-Zone	• Lightness • Comfort	Ladder gripsV STAB SYSTEMFlex-Zone	PU midsole for effective cushioning Rubber outsole for improved abrasion resistance Crampon design specially designed for optimum grip
Performances	SRC HRO HI CI	SRC HRO	SRC	SRC HRO	SRC	SRC HRO



















LIGHT WALKERS COMPOSITE COMPOSITE COMPOSITE	AGRO	4X4 INDUSTRY	X LARGE Industry	CLASSIC +	CLASSIC Industry
PU / PU	PU / PU	PANORUBBER® NITRILE RUBBER	PU / PU	PU / PU	PU / PU
Step rolling Tige Mesh / Croûte velours pour une meilleure ventilation du pied Available in ESD version (VIAGI S1P Black-Red)	Microfibre upper	Slip resistance on all type of slippery surfaces Oil resistances Hydrolysis resistance Heat resistance	 Areas of integrated bending (PANOFLEX® system) Shock absorber Available in ESD version (SAULT S3) 	• Lifespan and comfort	Lifespan and comfort JUMPER2 S3 FUR: / JUMPER2 S3 FUR HC PU resistant to -30°C
SRC	SRC	SRC HRO HI CI	SRC	SRC	SRC





Article	Colours	Description	Sizes	Standard	•	
TW400 S3 SRC	Black	Upper: Full grain leather, S3 water resistant treatment, mit rubber scuff cap. Lining: Polyamide Cambrelle absorbing. Insole: Removable preformed - Polyester on PU. Midsole: Cemented - PU with Panoshock® shock absorber. Outsole: Rubber Nitrile. Non metallic footwear.	39 → 48	C € EN ISO 20345 S3 HRO CI HI SRC	710 g	x 5



PREMIUM



Article	Colours	Description	Sizes	Standard	<u> </u>	
XR502 S3 SRC	Black	Upper: Nubuck leather and nylon mesh, S3 water resistant treatment. Lining: Polyamide absorbing. Insole: Removable preformed - Polyamide on EVA. Midsole: Cemented - PU with shock absorber Panoshock®. Outsole: Rubber. Non metallic shoe.	39 → 47	C EN ISO 20345 S3 HR0 SRC	590 g	x 5



PREMIUM



The nature sports and walking shoe dedicated to safety. Comfortable, technical and performance, the shoes of OUTDOOR range will take you far!

- 1- Flex-Zone
- 1- Flex-Zone
 2- V STAB SYSTEM3- Ladder lateral grips
 4- Crampons with hooks on all types of indoor and outdoor surface areas
 5- SRC standards





OHIO3 S3




















Article	Colours	Description	Sizes	Standard		
OHI03 S3	Black	Upper: Full grain leather, S3 water resistant treated. Lining: Polyester. Insole: Removable preformed - Polyamide on EVA. Outsole: Sole: Injected - Dual density PU.	36 → 47	C € EN ISO 20345 SRC SRC	650 g	x 5
	A113 S1D SD	C			ا لمبيد ا	Jم















Article	Colours	Description	Sizes	Standard	<u> </u>	
AURIBEAU3	Green-Black	Upper: Split suede leather and mesh. Lining: Polyester. Insole: Removable preformed - Polyamide on EVA. Outsole: Sole: Injected - Dual density PU.	36 → 47	C EN ISO 20345 SIP SRC	620 g 600 g	λ 3

SHOES Composite Tech

SAGA S3 SRC



LIGHT - ULTRA FLEXIBLE












Ultra flexible anti-perforation


composite insole












Article Colours Description Sizes Standard Upper: Nubuck leather, S3 water resistant treatment. Lining: Polyester. 730 g x 5 SAGA S3 SRC 39 → 48 Beige Insole: Removable - polyester on EVA. Outsole: Cemented - PU/Rubber.

NON-METALLIC







PHOENIX S3 SRC



















PHOCEA S3 SRC



Article	Colours	Description	Sizes	Standard	
PHOENIX S3 SRC PHOCEA S3 SRC	Black	Upper: Pigmented split leather, S3 water resistant treatment. Lining: Polyamide mesh. Insole: Removable preformed - Polyamide on EVA. Midsole: Injected - PU bi-density.	36 → 47	C € EN ISO 20345 S3 SRC	620 g 600 g

PROTON S1P SRC

























Article	Colours	Description	Sizes	Standard		
PROTON S1P SRC PRISM S1P	- Black	Upper: Pigmented split leather. Lining: Polyamide mesh. Insole: Removable preformed - Polyamide on EVA. Midsole: Injected - PU bi-density.	36 → 47	C EN ISO 20345 SIP SRC	610 g 590 g	x 5





D-SPIRIT S1P SRC





















Article	Colours	Description	Sizes	Standard		
D-SPIRIT S1P SRC	Black	Upper: Leather/mesh. Lining: Polyester. Insole: Removable - Polyester on EVA. Outsole: Cemented - PU/Rubber. Non metallic footwear.	38 → 47	C EN ISO 20345 STP HRO SRC	520 g	x 5

D-SPIRIT S3 SRC





















Article	Colours	Description	Sizes	Standard		
D-SPIRIT S3 SRC	Black	Upper: Leather, S3 water resistant treatment. Lining: Polyester. Insole: Removable - Polyester on EVA. Outsole: Cemented - PU/Rubber. Non metallic footwear.	36 → 47	C EN ISO 20345 S3 HRO SRC	520 g	x 5

D-STAR S3 SRC























Article	Colours	Description	Sizes	Standard		
D-STAR S3 SRC	Black	Upper: Leather, S3 water resistant treatment. Lining: Polyester. Insole: Removable - Polyester on EVA. Outsole: Cemented - PU/Rubber. Non metallic footwear.	38 → 47	C € EN ISO 20345 S3 HR0 SRC	550 g	x 5

SHOES Light Walkers



ASTI S1P SRC





















Article	Colours	Description	Sizes	Standard		
ASTI S1P SRC	Beige			- 11100 00015		
	Grey-Blue		U. 36 → 48	C EN ISO 20345 SIP SRC	550 g	x 10
	Black					

VIRAGE S1P SRC





















Article	Colours	Description	Sizes	Standard		
VIRAGE S1P SRC	Grey-Green Black-Red	Upper: Suede split leather and polyester mesh. Lining: Polyester. Insole: Removable preformed - Polyester on EVA. Outsole: Injected - Dualdensity PU. Non metallic footwear.	36 → 48	C EN ISO 20345 SIP SRC	610 g	x 10

SHOES Light Walkers

RIMINI II S1P SRC



















Article	Colours	Description	Sizes	Standard		
	Beige-Grey	Upper: Suede split leather and nylon mesh (breathable). Lining:	39 → 47		600 g	
RIMINI II S1P SRC	Grey-Navy blue	Polyamide absorbing. Insole: Fixed - Polyamide on EVA.		C € S1P		x 10
	Grey-Black	Outsole: Injected - Dual-density PU.	36 → 47	3110		

MIAMI S1P SRC





















					0	\sim
Article	Colours	Description	Sizes	Standard		
MIAMI S1P SRC	Grey-Navy blue	Upper: Polyester and cotton.Insole: Removable- Polyamide on EVA. Midsole: injected - Single density PU.	35 → 46	C EN ISO 20345 S1P SRC	350 g	x 10





Exclusive Panorubber® outsole providing resistance to hydrolysis and protection from heat and cold. The products of 4x4 INDUSTRY range meet the requirements of the petrochemical industry and construction.

PANORUBBER® OUTSOLE

1- SLIP RESISTANCE Rubber outsole SRC standard Slip resistance on all type of slippery floor 2- OIL RESISTANCE

Rubber/Nitrile outsole 3- RESISTANCE TO HYDROLYSIS

The material remains stable and keeps its shapes during variations in temperature and humidity 4- HEAT RESISTANCE



Ultra flexible anti-perforation composite insole Except LANTANA - NAVARA -KORANDA NON-METALLIC No metal part in the shoe Except LANTANA - NAVARA -KORANDA

Composite toe cap 200-joule, lighter than steel Non conductive material Except LANTANA - NAVARA -KORANDA

NON-METALLIC Except LANTANA - NAVARA -KORANDA

CAMARO S3 SRC



















FRONTERA S3 SRC



KORANDA S3 SRC



Article	Colours	Description	Sizes	Standard		
CAMARO S3 SRC		Upper: Full grain leather, S3 water resistant treatment, with TPU toe cap. Lining: Polyamide Cambrelle absorbing. Insole: Removable preformed -			820 g	
FRONTERA S3 SRC	Brown	Polyamide Cambrelle on EVA. Midsole: Injected - Panorubber®. Outsole: Rubber Nitrile.	36 → 48	EN ISO 20345 S3 HR0 HI CI	750 g	x 5
KORANDA S3 SRC	Black	Upper: Pigmented split leather, S3 water resistant treatment, with TPU toe cap. Lining: Polyamide absorbing. Insole: Removable - Polyamide on EVA. Midsole: Injected - Panorubber®. Outsole: Rubber Nitrile.		SRC	720 g	

LANTANA S1P SRC



















NAVARA S1P SRC





Article	Colours	Description	Sizes	Standard		
LANTANA S1P SRC	Didok	Upper: Buffalo pigmented split leather. Lining: Polyamide absorbing. Insole: Removable - Polyamide on EVA. Midsole: Injected - Panorubber®. Outsole: Rubber Nitrile.	36 → 48	C EN ISO 20345 S1P HRO HI CI SRC	700 g 670 g	x 5



DELTA FUSION S3 SRC













Specially designed and tested for foundry and aluminium heavy industries Resistance in hot and hard working conditions (molted metal)

PANORUBBER® OUTSOLE

- 1- SLIP RESISTANCE
- · Rubber outsole SRC standard
- Slip resistance on all type of slippery floor
- Outsole studs design developed by DELTAPLUS® LAB for optimal traction and grip 2- OIL RESISTANCE
- Rubber/Nitrile outsole
- 3- RESISTANCE TO HYDROLYSIS
- The material remains stable and keeps its shapes during variations in temperature and humidity
- 4- HEAT RESISTANCE
 HRO standard: 300° Contact-heat resistant sole assembly (1 mins)
- HI standard: Isolation of the foot in the shoe against the heat. Raising the temperature does not exceed 22°C after 30 mins in a sand bath at 150°C










EN ISO 20349 Standard 2010 HI-1 Steel and Aluminum Protection against thermal risks and splashes of molten metal (foundry - welding)

Article	Colours	Description	Sizes	Standard		
DELTA FUSION S3 SRC	Black	Upper: Fireproof Buffalo «C» leather,1.8-2 mm . Lining: Polyamide absorbing. Insole: Removable - non-woven on latex Foam. Midsole: Inlected - Panorubber®. Outsole: Rubber nitrile.	36 → 48	C € EN ISO 20349 EN ISO 20345 S3 HRO SRC	910 g	x 5







CADEROUSSE S3 SRC




















SAULT S3 SRC



MONTBRUN S3 SRC



Article	Colours	Description	Sizes	Standard		
CADEROUSSE S3 SRC	Black	Upper: Full grain leather, S3 water resistant treatment. Lining: Acrylic furlined. Insole: Preformed removable - Felt. Outsole: Injected - Dualdensity PU with bump cap.	39 → 48	EN ISO 20345 S3 CI SRC	880 g	. x5
SAULT S3 SRC		Upper: Pigmented split leather, S3 water resistant treatment. Lining:	33 7 40	EN ISO 20345	800 g	
MONTBRUN S3 SRC		Polyamide. Insole: Removable preformed - Polyamide on EVA. Outsole: Injected - Dual-density PU with bump cap.		S3 SRC	740 g	

CAROMB S1P SRC















MAZAN S1P SRC





Article	Colours	Description	Sizes	Standard		
CAROMB S1P SRC MAZAN S1P SRC	· Grey-Blue	Upper: Suede split leather and polyamide nylon. Lining: Polyamide. Insole: Preformed removable - Polyamide on EVA. Outsole: Injected - Dual-density PU with bump cap.	39 → 48	C EN ISO 20345 STP SRC	740 g 710 g	x 5



What does the regulation say?

Areas with potentially explosive atmospheres called **ATEX** and the protection of workers against the risks of explosion are regulated by 1999/92/EC Directive.

The use of a qualified footwear dissipating electrostatic charges, is recommended in these areas as part of a comprehensive system of prevention of explosion risk.

Requirements for the design, implementation of systems controlling electrostatic discharge (ESD) that can damage electronic components are defined by the EN61340-5-1 standard.


The device said ESD must offer resistance between $10^5 \Omega$ and $3.5 10^7 \Omega$).

To be used in an ESD system, a shoe must at least be qualified according to EN61340-4-3 standard and offer resistance less than $10^8 \Omega$ (and greater than $10^5 \Omega$), it is then dissipative.

SAULT ESD and **VIAGI ESD** perform particularly well because they have not only reached a maximum resistance between 10⁵ and 3.5 10⁷ (sigle ohm), but **these tests were conducted under severe restraints: the climatic environment class number 1 (high drought: 15% humidity rate).**

Due to their low resistance level, **SAULT ESD** and **VIAGI ESD** are a particularly efficient part of global grounding system (gloves, clothing, carpet, seat, etc ...).

Thus, their performances help this system to achieve the level of resistance required for 🌑 compliance.



RISK OF ELECTROSTATIC DISCHARGE (ESD*)

The static electricity on the operators must be controlled in the following application areas, because it can:



- > generate electrostatic sparks that can ignite explosive atmospheres: plastic industry, mining, oil and gas industry, chemical industry ...
- > damage sensitive equipment against electric shock: various electronic industries ...
- > generate particles that may be deposited on the painting: car industry, house appliances ...

* Electrostatic Discharge

SAULT S3 SRC ESD






















Audinto	0-1	Description	0:	Oberedend	0	
Article	Colours	Description	Sizes	Standard		
SAULT S3 SRC ESD	Black	Upper: Pigmented split leather, S3 water resistant treatment. Lining: Polyamide. Insole: Removable preformed - Polyamide on EVA. Outsole: Injected - Dual-density PU with bump cap.	39 → 48	EN ISO 20345 S3 SRC EN61340 CLASS 1	800 g	x 5

VIAGI S1P SRC ESD























Article	Colours	Description	Sizes	Standard		
VIAGI S1P SRC ESD	Black-Red	Upper: Suede split leather and polyester mesh. Lining: Polyester. Insole: Removable preformed - Polyester on EVA. Outsole: Injected - Dual-density PU. Non metallic footwear.	36 → 48	EN ISO 20345 STP SRC EN61340 CLASS 1	580 g	x 10



Article	Colours	Description	Sizes	Standard		
GARGAS II ISO 18KV	Black	Upper: Pigmented split leather. Lining: Polyamide absorbing. Insole: Removable - Polyamide on EVA. Outsole: Injected - Dual-density PU.	35 → 48	ASTM 18 KV WI/75/C/75 EH PR	570 g	x10
GARGAS II S1P SRC	Black	Upper: Pigmented split leather. Lining: Polyamide absorbing.	35 → 48	CE	630 g	x 10
		Insole: Removable - Polyamide on EVA. Outsole: Injected - Dual-density PU.		EN ISO 2034 S1P SRC	5	
GOULT II S1P SRC	Black	Upper: Pigmented split leather. Lining: Polyamide absorbing. Insole: Removable - Polyamide on EVA.	35 → 48	CE	610 g	x 10
		Outsole: Injected - Dual-density PU.		EN ISO 2034 S1P SRC	5	

2 2

SHOES Classic Industry

Article	Colours	Description	Sizes	Standard	<u> </u>	
COBRA 3 S3 SRC	Black	Upper: Pigmented split leather, S3 water resistant treatment. Lining: Polyamide mesh. Insole: Fixed - Polyamide on EVA. Outsole: Injected - Dual-density PU. Para aramid seams Flap	36 → 47	EN ISO 203 WG HI-1 EN ISO 203 S3 SRC		x 10
BRISBANE S1 SRC	Grey	Upper: Suede split leather. Lining: Polyamide mesh. Insole: Fixed - Polyamide on EVA. Outsole: Injected - Dual-density PU.	36 → 48	EN ISO 203	540 g	x 10
VOYAGER SIP SRC	Grey-Blue	Upper: Suede split leather. Lining: Polyamide mesh. Insole: Fixed - Polyamide on EVA. Outsole: Injected - Dual-density PU.	36 → 45 46 → 47	EN ISO 203 STP SRC	620 g	x 10 x 5
MIRAGE S1P SRC	Grey-Blue	Upper: Suede split leather. Lining: Polyamide mesh. Insole: Fixed - Polyamide on EVA. Outsole: Injected - Dual-density PU.	$36 \rightarrow 45$ $46 \rightarrow 47$	EN ISO 203 SIP SRC	600 g	x 10 x 5
FENNEC II S1 SRC	Grey	Upper: Suede split leather. Lining: Polyamide absorbing. Insole: Fixed - Polyamide on EVA. Outsole: Injected - Dual-density PU.	$36 \rightarrow 45$ $46 \rightarrow 47$	EN ISO 203	600 g	x 10 x 5
FENNEC II S1P SRC	Grey	Upper: Suede split leather. Lining: Polyamide absorbing. Insole: Fixed - Polyamide on EVA. Outsole: Injected - Dual-density PU.	36 → 45 46 → 47	EN ISO 203 SIP SRC	620 kg	x 10 x 5

SHOES Classic Industry

Article	0.1					
	Colours	Description	Sizes	Standard		Î
JUMPER2 S3 FUR HC SRC	Black	Upper: Pigmented leather croupon, S3 water resistant treatment. Lining: Polyester fur. Insole: Removable preformed - Felt. Outsole: Sole: Injected - Dual density PU.	36 → 45 46 → 48	EN ISO 203	690 g 45	x 1 x 5
		PU formula sole keeping its properties until -30°C		SRC		
JUMPER2 S3 FUR SRC	Black	Upper: Pigmented split leather, S3 water resistant treatment. Lining: furlined polyester. Insole: Removable - Polyamide on EVA.	36 → 45 46 → 48	CE	680 g	x 1
		Outsole: Injected - Dual-density PU. Outsole with special PU material resistant to -30°C		EN ISO 203 S3 CI SRC	45	
JUMPER2 S3 BUMPER SRC	Black	Upper: Pigmented split leather, S3 water resistant treatment, with TPU toe cap. Lining: Polyamide mesh.	36 → 45 46 → 48	CE	650 g	x 1
S. L. C. C. C. C. C. C. C. C. C. C. C. C. C.		Insole: Fixed - Polyamide on EVA. Outsole: Injected - Dual-density PU.		EN ISO 203 S3 SRC	45	
JUMPER2 S3 SRC	Black	Upper: Pigmented split leather, S3 water resistant treatment. Lining: Polyamide mesh. Insole: Fixed - Polyamide on antibacterial latex.	36 → 45 46 → 48	C€	660 g	x 1
To the second se		Outsole: Injected - Dual-density PU.		EN ISO 203 S3 SRC	45	
JET2 S3 SRC	Black	Upper: Pigmented split leather, S3 water resistant treatment. Lining: Polyamide mesh. Insole: Fixed - Polyamide on antibacterial latex.	36 → 45 46 → 47	C€	630 g	x 1 x 5
Desa		Outsole: Injected - Dual-density PU.		EN ISO 203 S3 SRC	45	

4 2 2

Article	Colours	Description	Sizes	Standard		
JUMPER2 S1P SRC	Black	Upper: Pigmented split leather. Lining: Polyamide mesh. Insole: Fixed - Polyamide on EVA. Outsole: Injected - Dual-density PU.	36 → 45 46 → 47	EN ISO 203 STP SRC	660 g 45	x 10 x 5
JET2 S1P SRC	Black	Upper: Pigmented split leather. Lining: Polyamide mesh. Insole: Fixed - Polyamide on EVA. Outsole: Injected - Dual-density PU.	$36 \rightarrow 45$ $46 \rightarrow 47$	EN ISO 203 SIP SRC	630 g 45	x 10 x 5
JUMPER2 S1 SRC	Black	Upper: Pigmented split leather.	36 → 45	C€	590 g	x 10
JOINT ERZ 31 JRC		Lining: Polyamide mesh. Insole: Fixed - Polyamide on EVA. Outsole: Injected - Dual-density PU.	46 → 47	EN ISO 203 S1 SRC		x 5
JET2 S1 SRC	Black	Upper: Pigmented split leather. Lining: Polyamide mesh. Insole: Fixed - Polyamide on EVA. Outsole: Injected - Dual-density PU.	$36 \rightarrow 45$ $46 \rightarrow 47$	EN ISO 203	590 g 45	x 10 x 5

BOOTSWinter Boot - Rain Boot

SAKHA S3 SRC Beige Upper: Cowhide leather, water resistant treatment S3 with TPP heal protection. Lining: Aerylic fur. Insole: Removable preformed - Polyseter on PA. Outsole: Injected - Dual density PU with front PU reinforcement. SAMARA S3 SRC Black Upper: Cowhide leather, water resistant treatment S3 with TPP heal protection. Lining: aerylic fur. Insole: Removable preformed - Polyseter on PA. Outsole: Injected - Dual density PU with front PU reinforcement.							
SAMARA S3 SRC Bisck Upper Control Indian value resistant treatment S3 with 1PH hed protection. Lings payle to PM. Union PV reinforcement. SAMARA S3 SRC Bisck Upper Control Indian Indian value resistant treatment S3 with 1PH hed protection. Lings payle to PM. Union: Permovale preferred - Physical repetred - Dail density PU with front PU reinforcement. Sign Sign Sign Sign Sign Sign Sign Sign	Article	Colours	Description	Sizes	Standard		
SAMARA S3 SRC Back Upper: Cowhide leather, water resistant treatment S3 with TFR heal protection. Uning: acrylic fur. Inside: Removable proformed - Polyster on PAA. Outsole: Injected - Dual density PU with front PU reinforcement. Back Upper: Pigmented split leather. Ling: Polyamide. Inside: removable: Polyamide on EVA. Outsole: Dual-Density PU AMAZONE S5 SRA Black Upper: Pigmented split leather. Ling: Polyamide on EVA. Outsole: Dual-Density PU AMAZONE S5 SRA Black Upper: Pigmented split leather. Ling: Polyamide on EVA. Outsole: Dual-Density PU AMAZONE S5 SRA Black Upper: Pigmented split leather. Ling: Polyamide on EVA. Outsole: Dual-Density PU AMAZONE S5 SRA Black Upper: Pigmented split leather. Ling: Polyamide on EVA. Outsole: Dual-Density PU AMAZONE S5 SRA Black Upper: Pigmented split leather. Ling: Polyamide on EVA. Outsole: Dual-Density PU AMAZONE S5 SRA Black Upper: Pigmented split leather. Ling: Polyamide on EVA. Outsole: Dual-Density PU AMAZONE S5 SRA Black Upper: Pigmented split leather. Ling: Polyamide on EVA. Outsole: Dual-Density PU AMAZONE S5 SRA Black Upper: Pigmented split leather. Ling: Polyamide on EVA. Outsole: Dual-Density PU AMAZONE S5 SRA Black Upper: Pigmented split leather. Ling: Polyamide on EVA. Outsole: Dual-Density PU AMAZONE S5 SRA Black Upper: Pigmented split leather. Ling: Polyamide on EVA. Outsole: Dual-Density PU AMAZONE S5 SRA Black Upper: Pigmented split leather. Ling: Polyamide on EVA. Outsole: Dual-Density PU AMAZONE S5 SRA Black Upper: Pigmented split leather. Ling: Polyamide on EVA. Outsole: Dual-Density PU AMAZONE S5 SRA Black Upper: Pigmented split leather. Ling: Polyamide on EVA. Outsole: Dual-Density PU AMAZONE S5 SRA Black Upper: Pigmented split leather. Ling: Polyamide on EVA. Outsole: Dual-Density PU AMAZONE S5 SRA Black Upper: Pigmented split leather. Ling: Polyamide on EVA. Outsole: Dual-Density PU AMAZONE S5 SRA Black Upper: Pigmented split leather. Ling: Polyamide on EVA. Outsole: Dual-Density PU AMAZONE S5 SRA	SAKHA S3 SRC	Beige	TPR heel protection. Lining: Acrylic fur. Insole: Removable preformed - Polyester on EVA. Outsole: Injected - Dual density PU with front PU reinforcement.	39 → 48	EN ISO 2034 S3 CI		x 5
ONTARIO S1P SRC Black Upper: Pigmented split leather. Lining: Polyamide. Insule: removable - Polyamide on EVA. Outsole: Dual-Density PU AMAZONE S5 SRA Black Upper: PVC. No Lining. No Insule. Outsole: Injected PVC/Nitrile. S5 SRA Black Upper: PVC. SNo Lining. No Insule. Outsole: Injected PVC/Nitrile.	SAMARA S3 SRC	Black	Upper: Cowhide leather, water resistant treatment S3 with TPR heel protection. Lining: acrylic fur. Insole: Removable preformed - Polyester on EVA. Outsole: Injected - Dual density		EN ISO 2034 S3 CI		x 5
Lining: Polyamide on EVA. Outsole: Dual-Density PU EN ISO 20345 SIP SRC AMAZONE S5 SRA Black Upper: PVC. No Lining. No Insole. Outsole: Injected PVC/Nitrile. EN ISO 20345 SIP SRC 1100 g x6 SIP SRC							
AMAZONE S5 SRA Black Upper: PVC. No Lining. No Insole. Outsole: Injected PVC/Nitrile. S5 SRA EN ISO 20345 S5 SRA	ONTARIO S1P SRC	Black	Lining: Polyamide. Insole: removable - Polyamide on EVA.	35 → 47	EN ISO 2034 S1P		х5
No Insole. Outsole: Injected PVC/Nitrile. EN ISO 20345 S5 SRA	AMAZONE S5 SRA	Black	Upper: PVC.	36 → 47	CE	1100 g	x 5
	The second secon	Green	No Insole: Outsole: Injected PVC/Nitrile.		EN ISO 2034 S5	5	

SHOES Agro

Article C	Colours	Description	Sizes	Standard		(
ROBION3 S2 SRC	Vhite	Upper: Microfibre. Lining: Polyamide. Insole: Preformed removable - Polyester on EVA. Outsole: Injected - PU bi-density. • Water resistant upper in microfibre • Machine wash up to 30° C, easy to maintain • Absorbent non woven lining for quick dry	35 → 47	C € EN ISO 203 S2 SRC	450 g	1
MAUBEC 3 SBEA SRC	Vhite	Upper: Microfibre. Lining: Polyamide. Insole: Preformed removable - Polyester on EVA. Outsole: Injected - PU bi-density. • Water resistant upper in microfibre • Machine wash up to 30° C, easy to maintain • Absorbent non woven lining for quick dry	35 → 47	EN ISO 203 SB A E SRC	460 g	

Accessoires

45400

Article	Colours	Description	Sizes	Standard		Ŷ
LACET XL	Black-Grey	Round polyamide laces. Length: 120 cm.			10 g	x 500
	Black	Round polyamide laces. Length: 100 cm.			10 g	x 500
22180						

Spare soles. Polyamide.

Black







60 g x 350

35/36 **→** 47/48

FALL PROTECTION

TO FIND THE SUITABLE PRODUCT FOR YOUR JOB







TO FIND THE SUITABLE PRODUCT _ **FOR YOUR JOB** Suitable protection EX220 224 HAR22 224 HAR24 224 HAR23 225 HAR23GIL 225 EX118200A 228 229 RIPLIGHT 2 HA201 229 ELARA280 230 ELARA320 230 ELARA140 231 ELARA270 231 ELARA150 232 232 AN208150CC 235 235 AN218150CCC 235 AN218RCDD 235 FIXBLOC AN105 239 MEDBLOC AN13006C 238 239 AN315 240 240 240 AN319 ASCORD ANO60 240 242 242 LV105 LV102100 243 LV102150 243 TETRANCHOR LV115 242 DAYAK LV120G 243 245 L0005200 L0007100R 245 L0007150 245 L0007150CD 245 AM022X2 251 244

AM025X2

	REPORT	TUREL P	S CONTROL OF THE PARTY OF THE P	PENERAL PROPERTY OF THE PROPER	STRA	JUSTERING SERVICE	STORES	A OHO OH C	AS WHAT	ME WHILL	guitale la	
	6	1			444			煄	<u></u>	州	Suitable protection	PAGES
		•	•								EX120	226
		•	•			•					HAR11	226
											HAR12	226
	•	•	•							•	HAR14	226
											HAR12GIL	227
		•	•	•	•	•			•		HAR12GILNO	227
											EX021	228
		•	•		•						ELARA190	232
		•									ELARA130	233
		•	•								ELARA160	233
											AN201200CC	236
		•									AN201200CD	236
ESSENTIAL										•	AN211200CCC	236
SSE		•								•	AN211200CDD	236
ш		•									AN203200CC	237
		•	•								AN203200CD	237
		•								•	AN213200CCC	237
		•	•							•	AN213200CDD	237
											FENNEC ANO6310	241
		•	•								FENNEC AN06320	241
		•									FENNEC ANO6330	241
	•	•	•	•				•	•	•	L0030	245
		•								•	L0031	245
	•	•	•	•				•	•	•	L0032	245
								•		•	AM002X5	251
		•	•	•	•	•		•	•		TC105	250



251

FALL PROTECTION SYSTEMS

FALL ARREST













RESCUE AND SUSPENSION HARNESSES



EN361 + EN358

RESTRAINT SYSTEMS





EN1498-B








HARNESS

CHOOSING YOUR HARNESS



CHOOSING YOUR SIZE

REF	SIZES	1	2	3	4
GT	S-M-L	<195 cm	<110 cm	<115 cm	<65 cm
XX	XL-XXL	>190 cm	>105 cm	>110 cm	>60 cm







DONNING A HARNESS




FALL ARREST

ENERGY ABSORBER





SELF RETRACTABLE FALL ARRESTER







TEMPORARY AND PERMANENT LIFELINES





CLEARANCE









AFTER SALES SERVICE

MANDATORY GENERAL ANNUAL INSPECTION


EN365

Instructions for periodic inspections shall include inter alia:

- A recommendation for the frequency of periodic inspections, taking into account factors such as regulation, the type of equipment, frequency of use, and environmental conditions. This recommendation shall include a clause stating that the periodic
- inspection should be conducted at least once every twelve months;
- A warning to emphasise that periodic inspections should be carried out by a competent person in strict compliance with the manufacturer periodic inspection procedures.







Up to 10 years from the date of manufacture or 7 years from the usage date for textile PPE

Up to 20 years from the date of manufacture for metallic PPE

VISUAL INSPECTION FOR:

Harnesses, belts, lanyards, ropes, energy absorbers, non removable reels (e.g. AN102), connectors, components of our kits (except ELARA270), temporary anchors (tripod, LV201 ...)

MECHANICAL INSPECTION FOR:

Removable reels, rescue equipment (e.g. TC013)



LOCAL AFTER SALES SERVICES



Info on www.deltaplus.eu



Training centres www.dpgtraining.com



SCHEDULE THE INSPECTION

1. MICROCHIP

A microchip, read by NFC, is placed below fall protection PPE's labels.

Almost all smartphones have the NFC (Near Field Communication).







2. MOBILE APP

Free download of APP DELATPLUS «ID CARD» to read and write the product traceability.









3. www.deltaplus.eu

Users can manage the cycle life of its PPE fall protection portofolio, programming the review, the end of life, the optimal stock.







HOW TO SCHEDULE THE ANNUAL INSPECTION

Register on the site www.deltaplus.eu





Or:

- Schedule by the user
- Schedule by the employer
- Label on the storage area of the product
- Use the following organisations for the scheduling:
- the dealer
- the Delta Plus manufacturer
- the Service Center



BODY SUPPORTFall arrester and suspension harnesses

JAGUAR HAR36TCP






















Article	Description	Sizes	Standard	<u>^</u>
JAGUAR HAR36TCP	Two colour harness with belt: 2 fall arrest anchorage points (dorsal-sternal). Positioning belt with thermoformed back and shorts. 2 work positioning attachment points (lateral). 1 suspension point. 8 adjustable buckles, of which 4 are automatic. 1 Ventral blocker.	S/M/L XL/XXL	EN358 EN361 EN567 EN362	2.4 kg x 5

Most of our products have been tested with a mass constraint greater than 40% to 50% of the normative requirements (140 kg or 150 kg). Find this information in the technical specifications of our products.

GALAGO HAR35TC



















2 accessory attachment holders incorporated into the belt



2 quick release buckles to adjust or remove the shoulder straps to get a shorts belt EX320TC

Article	Description	Sizes	Standard	•	
GALAGO HAR35TC	Two colour harness with belt: 2 fall arrester anchorage points (back - front). Positioning belt with thermoformed back and shorts. 2 work positioning attachment points (lateral). 1 suspension point. 8 adjustable buckles. 1 karabiner.	S/M/L XL/XXL	EN358 EN361 EN813 EN362	1.9 kg	x 5

GALAGO HAR35TCA

















Automatic buckles



Article	Description	Sizes	Standard	•	
GALAGO HAR35TCA	Two colour harness with belt: 2 fall arrest anchorage points (dorsal-sternal). Positioning belt with thermoformed back and shorts. 2 work positioning attachment points (lateral). 1 suspension point. 8 adjustable buckles, of which 4 are automatic. 1 carabiner.	S/M/L XL/XXL	EN358 EN361 EN813 EN362	2.6 kg	x 5

BODY SUPPORTFall arrester harnesses

EOLIEN HAR35

















Pocket for phone or fall detector carrier





Soft padding on the shoulders and straps on the legs Removable back protector

Article Description Sizes Standard Two colour harness with positioning belt. 3 fall arrester attachment points (back- front right side - front left side). 4 adjustable buckles in light alloy. 2 automatic buckles. Positioning belt with thermoformed back closed with wide Velcro for more comfort. 120° rotation. 2 lateral anchorage **C** € EN358 EN361 S/M/L **EOLIEN HAR35** 2 kg х 5 XL/XXL points. 1 adjustment loop. Sponge back lining.

Most of our products have been tested with a mass constraint greater than 40% to 50% of the normative requirements (140 kg or 150 kg). Find this information in the technical specifications of our products.

ANATOM HAR32

















Pocket for phone or fall detector carrier



Soft padding on the shoulders and straps on the legs





Article	Description	Sizes	Standard	<u> </u>
ANATOM HAR32	Two colour harness. 2 fall arrester anchorage points (back - front). 4 adjustable buckles.	S/M/L XL/XXL	(€ EN361	1.4 kg x 5

BODY SUPPORTFall arrester harnesses

HAR24












Fall indicator













«Riplight System II®»



Rotation 120° 2 accessory attachment holders incorporated into the belt

Article	Description	Sizes	Standard		
HAR24	Harness with extensible «Riplight System II®», patented waves with positioning belt. 2 fall arrester anchorage points (back - front). 4 adjustable buckles. Positioning belt with thermoformed back closed with wide Velcro. 120° rotation. Large thermoformed back with sponge lining. 2 lateral anchorage points for work positioning.	S/M/L XL/XXL	C € EN358 EN361	1.8 kg	x 5










































Article	Description	Sizes	Standard	<u></u>	
HAR22	Elasticated harness with extensible «Riplight System II ®» patented waves. 2 fall arrester anchorage points (back - front). 4 adjustable buckles.	S/M/L	EN361	1 kg	
		XL/XXL	CE	x 5	5
EX220	Positioning belt with thermoformed back closed with wide Velcro for more comfort. 120° rotation. 2 lateral anchorage points. 1 adjustment loop. Sponge back lining.		EN358	0.8 kg	

Most of our products have been tested with a mass constraint greater than 40% to 50% of the normative requirements (140 kg or 150 kg). Find this information in the technical specifications of our products.

HAR23











Fall indicator









«Riplight System II®»



Article	Description	Sizes	Standard		
HAR23	Elasticated harness with extensible «Riplight System II $^{\otimes}$ » patented waves. 3 fall arrester attachment points (back- right front side - left front side). 4 adjustable buckles.	S/M/L XL/XXL	C € EN361	1.3 kg	x 5

HAR23GIL











Fall indicator









«Riplight System II®»



Article	Description	Sizes	Standard		
HAR23GIL	Extensible harness with work vest not removable: Harness (Ref. HAR23). Vest: Polyester and Oxford polyamide. Polyester mesh lining. Zip closure. 2 zip pockets. Retro-reflective pipings. Adjustable size by elastic cords.	S/M/L XL/XXL	(€ EN361	1.8 kg	x 5

BODY SUPPORT Fall arrester harnesses

Article	Description	Sizes	Standard		
HAR14	2 fall arrester anchorage point harness (back - front), 2 adjustment loops. 2 adjustable lateral plates. Positioning belt with broad thermoformed back. Sponge lining, 2 anchorage points for work positioning.	S/M/L XL/XXL	C € EN358 EN361	1.1 kg	x 10
	67891112 667891112				
HAR12	2 fall arrester anchorage point harness (back - front). 2 adjustment loops. 2 adjustable lateral plates.	S/M/L XL/XXL	C € EN361	0.7 kg	x 10
	678911 678911 678911				
HAR12MFB	2 fall arrester anchorage point harness (back - front) with 45 mm chest strap. 2 adjustment loops. 2 adjustable lateral plates. Available		CE	10.8 kg	x 10
	on demand 1 2 4 5 9 6 7 8 9 11		EN361		
	*F				
HAR11	1 fall arrester anchorage point harness (back). 2 adjustment loops. 2 adjustable lateral plates.	S/M/L XL/XXL	C € EN361	0.6 kg	x 10
	† 1 2 4 5 9				
W/					
EX120	Positioning belt with thermoformed back. 2 lateral anchorage points for work positioning. 1 adjustment loop. Sponge back lining.	One size	C € EN358	0.4 kg	x 10
	† (1) (12)				
	*r				

Most of our products have been tested with a mass constraint greater than 40% to 50% of the normative requirements (140 kg or 150 kg). Find this information in the technical specifications of our products.

Article	Description	Sizes	Standard	2	
HAR12GILNO	Harness with work vest not removable: Harness (Ref. HAR12). Vest: 100% polyester. Polyester Mesh lining. Zip closure. 4 pockets including 1 phone pocket. Adjustable size by zip.	S/M/L XL/XXL	€ EN361	1.2 kg)
	† 12459 678911 				
HAR12GIL	Harness with high visibility vest not removable: Harness (Ref. HAR12). Vest: Twill 54% polyester 46% cotton. Sewn retroreflective tape. Polyester mesh lining. Zip closure. 4 pockets including 1 phone pocket. Adjustable size by zip.	S/M/L XL/XXL	EN361 EN471 1 2	1.2 kg	>









ANCHORAGE - WORK POSITIONING Work positioning systems

EX118



















Recommended accessory for the proper use of this product: 1 AM002 connector



Article	Description	Sizes	Standard		
EX118200A EX118400A	Adjustable work positionning lanyard via stainless steel tensioner. Adjustable length. Stranded rope Ø 14 mm equipped with a wear indicator. Thimble loop. Splice protection. Protective sheath. 1 hook.	0.20 to 2 m 0.40 to 2 m	C € EN358 EN362	0.9 kg 1.1 kg	x 5
EX021			←		







Article	Description	Sizes	Standard		
EX021	Adjustable work positionning lanyard via reducer. Adjustable length. Stranded rope Ø 12 mm. Protective sheath on the splices.	1.10 to 2 m	(€ EN358	0.3 kg	x 15

FALL ARRESTER SYSTEMS Fall arrester accessories

HA203
























Article	Description		Sizes		
HA203	Pair of straps enabling blood circulation in the legs after a fall while waiting for help. Adjustable positioning on the side straps. Ease and speed of implementation. Carrying case.	for any type of harness by	One size	300 g	x 25
RIPLIGH	IT 2 HA201				#





Article	Description	Sizes		
RIPLIGHT 2 HA20	RIPLIGHT SYSTEM II® gives elasticity to your harness by removing the stress points. «Clips» easily on our harness straps. For optimum comfort, it is recommended to use three pairs of expandable waves. Sold in pairs.	One size	30 g	x 100

229

FALL ARRESTER SYSTEMS Kits

ELARA320





















Article	Description	Sizes	Standard		
ELARA320	POSITIONNING & SCAFFOLDING - ready for use fall arrest kit: 2 fall arrester anchorage point harness (back - front). 2 adjustment loops. 2 adjustable side plates. Positioning belt (Ref. HAR14). Adjustable work positioning lanyard via reducer. Length of 1.1 to 2 m. Stranded rope Ø 12 mm (Ref. EX021). Fall arrester with energy absorber in double stranded rope (Y) Ø 12mm. Length 2 m. 1 AM002 carabiner and 2 AM022 hooks (Ref. AN211200CDD) 2 connectors AM002.	S/M/L	EN355 EN361 EN358 EN362	3.6 kg	x 5

ELARA280



















Article	Description	Sizes	Standard		
ELARA280	SCAFFOLDING - ready for use fall arrester kit: 2 fall arrester anchorage point harness (back - front). 2 adjustment loops. 2 adjustable side plates. (Ref. HAR12). Fall arrester with energy absorber in double stranded rope (Y) Ø 12mm. Length 2 m. 1 AM002 carabiner and 2 AM022 hooks (Ref. AN211200CDD)	S/M/L	EN355 EN361 EN362	2.8 kg	x 5

Most of our products have been tested with a mass constraint greater than 40% to 50% of the normative requirements (140 kg or 150 kg). Find this information in the technical specifications of our products.

ELARA270



















Article	Description	Sizes	Standard		
ELARA270	VERTICAL & HORIZONTAL 10 M - Ready for use fall arrester kit: 2 fall arrester anchorage point harness (back - front). 2 adjustment loops. 2 adjustable side plates. (Ref. HAR12). Self retractable fall arrester with steel strap. Length 10 m. ABS case. 1 automatic swivel connector and fall indicator AM016 (Ref. AN12010T). Lanyard and anchorage point in tubular strap, length 2 m (Ref. L0030). 2 connectors AM002.	S/M/L	EN360 EN354 C € EN795 TYPE B EN361 EN362	8.5 kg	x 1

ELARA140























Article	Description	Sizes	Standard		
ELARA140	VERTICAL & HORIZONTAL 2.50 M - Fall arrester kit ready for use: 2 fall arrester anchorage point harness (back - front). 2 adjustment loops. 2 adjustable side plates. (Ref. HAR12). Self retractable fall arrester with 46 mm strap with energy absorber. Protection case. 1 connector AM002 (Ref. AN102). 1 connector AM002.	S/M/L XL/XXL	EN360 EN361 EN362	2.1 kg	x 5

231

FALL ARRESTER SYSTEMS Kits

ELARA170

























Article	Description	Sizes	Standard		
ELARA170	ROOF - ready for use fall arrester kit: 2 fall arrester anchorage point harness (back - front). 2 adjustment loops. 2 adjustable side plates. (Ref. HAR12). Sliding non opening fall arrester set	S/M/L XL/XXL	EN353-2 EN361	3.3 kg	v E
ELARA150	with fall indicator on stranded rope anchorage line Ø 12 mm, length 20 m. (Ref. AN063/20). 2 connectors AM002.	S/M/L	EN362	2.4 kg	ХЭ

ELARA190



















Article	Description	Sizes	Standard		
ELARA190	SCAFFOLDING - ready for use fall arrester kit: 2 fall arrester anchorage point harness (back - front). 2 adjustment loops. 2 adjustable side plates. (Ref. HAR12). Fall arrest with energy absorber with lanyard strap, length 2 m, equipped with 1 connector AM002 and 1 AM022 hook	S/M/L XL/XXL	C € EN355 EN361 EN362	1.8 kg	x 5

FALL ARRESTER SYSTEMS

Most of our products have been tested with a mass constraint greater than 40% to 50% of the normative requirements (140 kg or 150 kg). Find this information in the technical specifications of our products.

ELARA130











RESTRAINT KIT

Storage bag





Article	Description	Sizes	Standard			
ELARA130	RESTRAINT - ready for use kit: 1 fall arrester anchorage point harness (back). 2 adjustment loops, 2 adjustable side plates with lanyard in irremovable stranded rope Ø 12 mm. Length 1.50 m. 1 connector AM002.	S/M/L	C € EN358 EN362	1.3 kg	x 5	

ELARA 160





Storage bag





Article	Description	Sizes	Standard	<u></u>	
ELARA160	CLASSIC - ready for use fall arrester kit: 1 fall arrester anchorage point harness (back). Two adjustment loops, 2 adjustable side plates with fall arrester with not removable energy absorber in stranded rope Ø 12mm, length 2 m. 1 karabiner AM002.	S/M/L XL/XXL	C € EN355 EN361 EN362	1.5 kg	x 5



FALL ARRESTER SYSTEMS Energy absorbing lanyards

AN245200CDD



















Article	Description	Sizes	Connector 1	Connector 2	Standard	•	
AN245200CDD	Fall arrest with energy dissipater in double elastic strap (Y). Thimble loops. Equipped with 1 carabiner AM002 + 2 AM022 hooks.	1.40 to 2 m	1 x AM002	2 x AM022	C € EN355 EN362	2 kg	x 5

AN235200CD



















Article	Description	Sizes	Connector 1	Connector 2	Standard	<u> </u>	
AN235200CD	Fall arrest with energy absorber elastic strap. Thimble loops. Equipped with 1 AM002 carabiner + 1 AM022 hook.	1.40 to 2 m	1 x AM002	1 x D	C € EN355 EN362	1.3 kg	x 5

FALL ARRESTER SYSTEMS Energy absorbing lanyards

AN218150CCC

































Article	Description	Length	Connector 1	Connector 2	Standard	<u> </u>
AN218150CCC	Fall arrester with energy absorber in double braided rope (Y) Ø 10.5 mm. Thimble loops.	4.50	1 v (**)	2 x AM002	<i>C C</i> EN355	1.2 kg
AN208150CC	Fall arrester with energy absorber in braided rope Ø 10.5 mm. Thimble loops.	···· 1,50 m	AM002	1 x AM002	EN362	0.8 kg

AN218RCDD



























Article	Description	Length	Connector 1	Connector 2	Standard		Û
AN218RCDD	Fall arrester with energy absorber in double braided rope Ø 12 mm (Y), adjustable by means of two gear rings on the rope.	150 . 2	1v (**)	2 x AM022	(C EN355	2 kg	v E
AN208RCD	Fall arrester with energy absorber in braided rope Ø12 mm, simple and adjustable by means of a gear ring on the rope.	·· 1,50 → 2 m	AM002	1 x AM022	EN362	1.3 kg	х 5

FALL ARRESTER SYSTEMS Energy absorbing lanyards

AN201200CC













Article	Description	Length	Connector 1	Connector 2	Standard	<u> </u>	
AN201200CC AN201200CD	Fall arrester with energy absorber in stranded rope Ø 12 mm. Thimble loops.	2 m	1 x AM002	1 x AM002	EN362	0.8 kg 1.2 kg	x 5
AN21120							











Article	Description	Length	Connector 1	Connector 2	Standard		
AN211200CCC AN211200CDD	Fall arrester with energy absorber in stranded rope (Y) Ø 12 mm. Thimble loops.	2 m	1 x AM002	2 x AM002 2 x AM022	C € EN355 EN362	1.3 kg 2 kg	x 5

AN203200CC













Article	Description	Length	Connector 1	Connector 2 St	tandard	<u> </u>	
AN203200CC AN203200CD	Fall arrester with energy absorber in lanyard webbing. Thimble loops.	2 m	1 x AM002	1 x AM002 1 x AM022	E € EN355 EN362	0.7 kg 1 kg	x 5

AN213200CCC



























Article	Description	Length	Connector 1	Connector 2 Standard	<u> </u>	
AN213200CCC AN213200CDD	Fall arrester with energy absorber in double lanyard webbing (Y). Thimble loops.	2 m	1 x AM002	2 x AM002 C EN355 EN362	1.3 kg	x 5

FALL ARRESTER SYSTEMS Retractable fall arresters

MEDBLOC AN13006C








Easy to use

150 Kg tested



Compact: 139mm

178mm















Article	Description	Length	Connector 1	Standard			
MEDBLOC AN13006C	Self retractable fall arrester with polyester webbing 25 mm. ABS protection. Swivel with fall indicator. 1 carabiner AM002.	6 m	1 x AM002	C € EN360 EN362	1.8 kg	x 5	

Most of our products have been tested with a mass constraint greater than 40% to 50% of the normative requirements (140 kg or 150 kg). Find this information in the technical specifications of our products.

PROTECTOR ROUND

















Article	Description	Sizes	Connector	Standard		
AN12006T		6 m			7 kg	
AN12010T	Self retractable fall arrester with galvanized steel cable. ABS protection. Fall indicator. Inertia braking system. 1 carabiner AM016.	10 m	1 x AM016	C € EN360 EN362	7.5 kg	x 1
AN12015T		15 m			8 kg	

MINIBLOC AN102

































41	
180	
100	
15	
2	
7	
-	
(
1 8	

Article	Description	Length	Connector 1	Standard		
MINIBLOC AN102	Self retractable fall arrester with 46 mm strap with energy absorber. Protection case. 1 carabiner AM002.	2,50 m	1 x AM002	(90)	1.1 kg	
FIXBLOC AN105	Self retractable fall arrester with 17 mm polyester/Aramid Kevlar® strap. Plastic case. Inertia locking system. 1 automatic swivel connector with fall indicator. 1 karabiner AM002.	1,90 m		C € EN360 EN362	0.9 kg	x 5

FALL ARRESTER SYSTEMS Fall arresters on rope

ASCORD AN060

















Non-inverting device

Energy absorber with fall indicator



AN315

















Article	Description	Length	Connector 1	Standard		
ASCORD ANO60	Fall arrester sliding on anchorage line stranded rope Ø 14 mm (rope sold separately). Opening type fall arrester equipped with automatic locking, non-inverting device, energy absorber with fall indicator. 1 carabiner AM002.		(2)		0.7 kg	x 5
AN315		10 m	1 x AM002	C € EN353-2 EN362	1.5 kg	x 10
AN317	Anchorage line stranded rope Ø 14 mm for ASCORD®. End spliced with thimble loop.	20 m			2.8 kg	x 5
AN319		30 m			4.1 kg	x 5

FALL ARRESTER SYSTEMS Fall arresters on rope

FENNEC











Recommended accessory for the proper use of this product: 1 connector AM002





Article	Description	Length	Standard		
FENNEC AN06310		10 m		1.3 kg	x 10
FENNEC AN06320	Sliding non opening fall arrester set with fall indicator on stranded rope anchorage line \emptyset 12 mm. Wear indicator. 1 loop spliced on high end.	20 m	(€ EN353-2	2.2 kg	_
FENNEC AN06330		30 m		3 kg	X J

ANCHORAGE - WORK POSITIONING Anchorage devices









Article	Description	Standar	rd 🔔
LV100	Stainless steel anchorage mounting plate with screws Ø 12 mm.	C € f	50 g
V105	Anchorage with stainless steel eye 0 12 mm. Overall length 140 mm. Ro Thread length 80 mm.		уреа х 175 g
V504A		TETRANCHOR LV115	1
		(*F	
		Helps manage the anchor point connectors	
The same of			
		TETRANCHOR MINISTER COMPANIES 21 Terress	A C(COST)

Article	Description	Sizes	Standard		
LV105	Anchorage with stainless steel eye Ø 12 mm. Overall length 140 mm. Rod length (under flange) 100 mm. Thread length 80 mm.		EN795 TYPE A	175 g	x 10
	«Rigging plate». Device for multi-point anchoring with 4 holes	One size	C EN795 TYPE A TS16415	200 g	x 20

ANCHORAGE - WORK POSITIONING Anchorage devices



Article	Description	Length	Standard	
LV400	Telescopic rod with 5 sections. Closed length 2m. Open Length 8	m. Material insulates to 30kV. Adjustable		5 kg x 1
LV401	Automatic lock hook in aluminium with double opening action. Op	pening 90 mm R> 23kN.	C € EN795 TYPE B EN362	1.3 kg x 10
LV102100		DAYAK LV120G	· T	A m
*F		(*F		
‡ 2 3 4 1 ↔ 6 7 8 1	13	† ← 6 8 12		
			K	
		-		

Article	Description	Length Standard	
LV102100	Anchorage ring with high tenacity polyester strap. Width 45 mm. End loop with shrinkage and	1 m	200 g
LV102150	steel anchor D.		300 g
DAYAK LV120G	Transportable anchorage point, galvanized steel, for door frame or window of 63 to 123 cm. Adjustable with clamping screw.		7 kg x 1



ANCHORAGE - WORK POSITIONING Lanyards

LO147150CDD











Article	Description	Length	Connector 1	Connector 2	Standard	•	
L0147150CDD	Double lanyard in braided rope Ø 10.5 mm.	1,50 m	1 x AM002	2 x AM022	C € EN354 EN362	1.45 kg	x 5
					EN354	0.3 kg	x 15
LO04715	0AD					<u> </u>	**









Article	Description	Sizes	Connector 1	Connector 2	Standard		Q
L0047150AD	Lanyard in braided rope Ø 10.5 mm. 2 thimble loops	1.50 m	1 x AM010	1x AM022	EN354 EN362	0.83 kg	
L0045200	ends.	2 m			C€	0.18 kg	x 1
L0047100		1 m			EN354	0.14 kg	
L0147150	Double lanyard in braided rope Ø 10.5 mm. 3 thimble loops ends.	1.50 m				0.3 kg	

ANCHORAGE - WORK POSITIONING Lanyards

LO007150CD

































Article	Colours	Description	Sizes			Standard		
L0007150CD			1.50 m	1 x AM002	1 x AM022	EN354 EN362	0.87 kg	
L0007100	White	Lanyard in stranded rope Ø 12 mm. 2 thimble loops.	1 m			CE	0.2 kg	x 15
L0007150		2 4	1.50 m			EN354	0.22 kg	
L0005200			2 m				0.26 kg	

LO030













EVOLUTION











Article	Description	Length Standard		Î
L0030		2 m	130 g x	. 15
L0031	Lanyard and anchorage point in tubular webbing. 2 sewn loops. Width 25 mm.	1,50 m (€ EN795 TYPE B	100 g x	15
L0032		1 m	70 g x	: 15

SUSPENSION Rope access work







RESCUEFall arrest and rescue, confined space





4

TRA20	Telescopic aluminium tripod. Height adjustable from 1.20 m to 1.97 m. Maximum wheelbase on ground 1.89 m. 3 central anchor points, 2 anchor points on the legs. Ability to set the TRA101 or TRA102 adjuster plate or the TRA103 steps.			19.6 kg	
TRA22	Telescopic aluminium tripod. Height adjustable from 1.20 m to 1.97 m. Maximum wheelbase on ground 1.89 m. 3 central anchor points, 2 anchor points on the legs. Equipped with TRA101 and TRA102 adjuster plates. TRA103 steps not included.	Adjustable	EN795 TYPE B	21.8 kg	
TRA30	Telescopic aluminium tripod. Height adjustable from 1.45 m to 2.15 m. Maximum wheelbase on ground 1.50 m. 1 central anchor point for fall arrester. Ability to set a TRA101 or TRA102 adjuster plate for a retractabke fall arrester.		TS16415	20 kg	x 1
TRA32	Telescopic aluminium tripod. Height adjustable from 1.74 m to 3.02 m. Maximum wheelbase on ground 2.62 m. 3 central anchor points, 2 anchor points on the legs. Equipped with TRA101 or TRA102 adjuster plates or the TRA103 steps.		C€	22.24 kg	
TRA101	Aluminium mounting plate for a self retracting fall arrest. To set on tripod TRA20 and TRA30.			1.3 kg	
TRA102	Aluminium mounting plate for hoist. To set on tripod TRA20 and TRA30.	One size		1.7 kg	
TRA103	Step to access the tripod head and the pulley. Sold individually.			500 g	x 10
TR00420	Manual winch with Ø 5 mm cable. Lenght 20 m.	20 m		18.7 kg	w 0
TR00430	Manual winch with Ø 5 mm cable. Lenght 30 m	30 m		19.7 kg	XΖ
TRBAG	Storage bag with wheels for tripod.	··· One size		1.7 kg	x 10
TRBAG3	Storage bag with wheels for TRA30 and TRA32.	OHE SIZE		1.7 kg	X 1U

Safety pin















249

RESCUERescue & evacuation

Most of our products have been tested with a mass constraint greater than 40% to 50% of the normative requirements (140 kg or 150 kg). Find this information in the technical specifications of our products.



CONNECTING SYSTEMS Connectors





A UNIQUE IMAGE IN YOUR SHOP


















A

A UNIQUE IMAGE IN YOUR SHOP













PLV017 H 120 x W 35 x D 55 cm Cardboard display with 3 shelves





PLV010 H 166 x W 60 x D 60 cm Shoes display





PLV012GR H 79 x W 29 x D 14 cm PVC chest dummy with hanger





PLV3A + PLV13B H 210 x W 100 x D 60 cm Fall arrest display





A TRAINING CENTRE DEVOTED TO OCCUPATIONAL HEALTH AND SAFETY

Special PPE courses designed for both distributors and users.

▶ INFORMATION AND TRAINING TO BETTER UNDERSTAND THE ISSUES OF PERSONAL PROTECTION

- Act within the framework of health and safety at work.
- Argue a range of personal protection.
- Understand the technical features of personal protection.
- Follow a study of work position and recommend a solution for personal protection.
- Identify and assess risks, adjust the performance of protection.
- Comply with requirements for recording, storage, maintenance, product control.
- Read and understand the product certification.
- Know the legal, regulatory and normative environment.

> THEREFORE WE ADDRESS:

- For sales teams to organize and deepen their knowledge of PPE to develop their sales and give more meaning to their job as their business proposals.
- For companies that use PPE to identify the most appropriate answers to the risks of their work environment, to choose the most efficient products and follow up the necessary review of PPE category III.

> TRAINING IS INDISPENSABLE:

For example, particularly when it is about Fall protection PPE Category III against fatal and irreversible risks.

It allows:

- Awareness of work at height
- Analysis of risk situations
- Securing workstations
- Finding protection solutions
- Providing more productivity
- Providing technical expertise in inspection, maintenance and repair of products


EN365

USERS: "It is essential that staff are trained, that their competence is controlled and they have written instructions enabling them to choose, use, maintain and periodically revise the PPE or other equipment."

AUDITORS: "It is possible that a competent person has to be trained by the manufacturer (i.e.) significant security related knowledge necessary for the disassembly, reassembly, or evaluation of PPE or other equipment."

OUR TRAINING OFFER:

Several training modules adapted to different audiences: users, distributors, technical inspection services and repair.



REGULATORY FRAMEWORK

THE DIRECTIVE (EUROPEAN UNION)

89/686 directive is intended for Personal Protective Equipment (PPE) manufacturers and determines conditions for market trade. It defines the essential requirements in terms of design, manufacture and test methods for PPE with which PPE must comply in order to ensure the safety of the users.

STANDARDIZATION

Its aim is to draw up test methods and product standards defining the technical specifications for products. The respect of these standards is evidence of conformity to Directive 89/686/EEC and allows CE marking.

CATEGORIZATION

Taking into account the level of accident risk protection, the Directive defines categories of PPE and determines the manufacturer's obligations:

- PPE category 1: Protection against Minor Risks.
- PPE category 2: All PPE that is not category 1 or 3.
- PPE category 3: Protection against disability or fatality.

CERTIFICATION PROCEDURE



- PPE category 2 and 3: EC type examination of PPE by an independent body for
 which compliance with the Directive 89/686/EEC is verified using standards that are
 in accordance with the Directive. Issuance of the EC type Examination Certificate
 (confidential document).
 - PPE category 1, 2 and 3: CE marking on the product.
- PPE category 3: Control by an independent body that ensures compliance of the manufacture with of examined PPE:
 - Or control of the final product (procedure called 11A),
 - Or control of the production (procedure called 11B).
 - PPE category 1,2 and 3: Establishment by the manufacturer of the EC Compliance
 Declaration which shows the user the compliance of the PPE with the 89/686/EEC
 Directive.

OTHER ACCREDITATIONS (EXCEPT EUROPEAN UNION)

Some of our products are accredited under the regulations of many countries. The products concerned (and / or their packaging) bear the following markings:

USA	ANSI, ASTM, NIOSH
Argentina	(S) (UL (S) AR 1983
Brésil	CA
Ukraine	23
Common Economic Space (Russia, Belarus Kazakhstan)	EAC



HEAD PROTECTION

SAFETY EYEWEAR

Safety eyewear provides protection from spray and splatter from particles, liquids and dust, and from chemical product fumes and radiation.

► HOW TO PROTECT YOURSELF?

Select the most suitable protective glasses or shields.

- Identify the type of risk: spray, radiation, other, ...
- **Determine the type of protection:** spectacles-type safety glasses, goggles, face mask, cover goggles, . . .
- **Note the protective features:** scratch-resistant, fog-resistant, tinted, ...
- Select the type of eve-piece: one-piece or double lens.
- Choose the frame type: design, classical, ...

▶ STANDARDS

EN166: applies to all types of individual protection of the eye which protects from hazards likely to damage the eye, except for nuclear radiation, x-rays, laser emissions and infrared emitted by low-temperature sources. Does not apply to eye protection for which separate standards exist (anti-laser eye protection, sunglasses for general use,...)


EN175: Specifications for the safety requirements for eye and face protection equipment for welding and related techniques (filters frames/media).


EN169: Specifications of level numbers and requirements relating to the transmittance of filters to protect operators for welding and related techniques. Specification of requirements for welding filters with double number of levels.

EN170: Specifications of level numbers and of requirements relating to the transmittance of the filters for protection against ultraviolet radiation.

EN172: Specification of level numbers and requirements relating to the transmittance of filters for protection against solar radiation, industrial use.

MARKING





• SYMBOL MEANING - EN166:

1: optical class allowing permanent wear of the spectacles.

Mandatory performances

- **S:** Increased robustness: steel ball of 22 mm diameter at 5.1 m/s.
- **F**: Low energy impact: steel ball of 6 mm diameter at 45 m/s.
- **B**: Medium energy impact: steel ball of 6 mm diameter at 120 m/s.
- A: High energy impact: steel ball of 6 mm diameter at 190 m/s.

Optional performances

- 3: Liquid resistance (droplets or splashes).
- **4**: Large dust particles resistance (size of $> 5 \mu m$).
- **5**: Gas and fine dust particles resistance (size $< 5 \mu m$).
- 8: Short circuit electric arc resistance.
- **9**: Resistance to splashes of molten metal and penetration of hot solids.
- **T:** (F B A) High speed particles at extreme temperatures 5°C / + 55°C.
- **N**: Resistance to fogging of lenses.
- **K**: Resistance to surface damage by fine particles (anti-scratch).

▶ FILTERS

Special filters can eliminate certain parts of light and a high proportion of the electro-magnetic spectrum (ultraviolet rays, infrared rays...).

				SPECT	ACLES LENS M	ARKING						
EN166												
				UV FILTER	S (EN170)	IR FILTERS (EN171)	SUN FILTER	WELDING (EN169)				
		Minimal		2	2C	4	5	6				
Lens colour		transmission factor of visible light	SCALE Nr	Colours perception may be alterated Colours perception is not alterated			Without IR protection specification	With IR protection specification	no code nr			
CLEAR	INDOOR	80,0%	1,1				5-1,1	6-1,1				
	INDOOR	74,4%	1,2	2-1,2	20-1,2	4-1,2						
OKE		58,1%	1,4	2-1,4	2C-1,4	4-1,4	5-1,4	6-1,4				
LIGHT SMOKE	OUTDOOR + INDOOR	43,2%	1,7	2-1,7	20-1,7	4-1,7	5-1,7	6-1,7				
TIG		29,1%	2	2-2	2C-2	4-2	5-2	6-2				
SMOKE	OUTDOOR	17,8%	2,5	2-2,5	2C-2,5	4-2,5	5-2,5	6-2,5				
SM	OUTDOOR	8,0%	3,1				5-3,1	6-3,1				
		8,5%	3	2-3	2C-3	4-3			3			
		3,2%	4	2-4	2C-4	4-4	5-4,1	6-4,1	4			
		1,2%	5	2-5	2C-5	4-5			5			
		0,44%	6			4-6			6			
Œ		0,16%	7			4-7			7			
eldin		0,061%	8			4-8			8			
for w	MIG-TIG	0,023%	9			4-9			9			
ARK (MIG-110	0,085%	10			4-10			10			
VERY DARK (for welding)		0,0032%	11						11			
5		0,0012%	12						12			
		0,00044%	13						13			
		0,00016%	14						14			
		0,000061%	15						15			
		0,000023%	16						16			

Lens marking is composed by 2 numbers (separated in the middle by a "-"):


CODE NUMBER :	from 2 to 6. Welding lens have no code number.
SCALE NUMBER :	$from 1.1 \ (the \ highest \ \% \ of \ transmission \ in \ visible \ light, \ the \ clearest \ lens)$ $to \ 16 \ (the \ lowest \ \% \ of \ transmission \ in \ visible \ light, \ the \ darkest \ lens)$
DELTA PLUS range :	The yellow coloured possibilities are available in the DELTA PLUS range.



HEAD PROTECTION

	RISKS TO THE EYE FROM HARMFUL RADIATION											
Zone	Wave Length	Environment	Eyesight damage									
UV-A	315-380 nm	Outdoor work.	Eye fatigue, partial blindness, cataract. Sunshine.									
UV-B	280-315 nm	Sunlight. Industrial environment. Black light tests.	Cataract. Welder flash. Arc flash.									
UV-C	100-280 nm	Industrial environment. Arc welding.	Cornea or crystalline lesions. Loss of eyesight.									
Blue light	400-480 nm	Industrial environment. Computer work (fatigue, VDU). Electrical installations. Outdoor work.	Retinal lesions. Loss of eyesight. Blurring degeneration (age). Retinitis pigmentosis.									
Infra-red	780-1400 nm (near IR) 1400-2000 nm (IR mid)	Electric welding. Molten work (glassmaking, steel production). Micro-wave processes. Sunlight.	Retinal lesions. Blurring degeneration (age). Retinitis pigmentosis (near-IR). Crystalline and cornea lesions (mid-IR).									

THE ELECTRO-MAGNETIC SPECTRUM



▶ ARC WELDING

RECOMMENDED USE OF DIFFERENT GRADE NUMBERS FOR ARC WELDING ACCORDING TO STANDARDS EN169/EN175																								
A Current amperage																								
Process	1.5	6	10	15	30	40	60	70) 10	00	125	150	175	200	225	250	30	0 ;	350	400	450	500	600	
MMA	8 9 10 11 12							13 14					4											
MAG					9				10		1	11			12			13			14			
TIG			8			(9		1	0		1	11		12	2	10	3						
MIG (heavy metals)	7.				9							10			11 1			12		13				
MIG (light metals)						10							11 12				13			14				
Arc air gouging						10									11 12		13			14		15		
Plasma cutting 9 10 11 12 13																								
Micro plasma welding	elding 4 5 6 7 8 9 10 11 12																							

This table is valid under normal conditions of use, in which the distance between the eye of the user and the mass of molten metal is approx. 50 cm and average light is approx. 100 lux.

SKULL PROTECTION

▶ HOW TO PROTECT YOURSELF?

To choose the correct safety helmet

To identify the risk: falling bumps or combined risks (hearing protection and face protection).

The safety helmet has three functions:

Antipenetration for an effective skull protection.

Shock absorber because the cap and the harness absorb shocks.


Deflector thanks to a suitable design which makes it possible to deflect the fall of an object from the top of the head.

There is in addition a selection of accessories which offers a face and hearing protection.

▶ STANDARDS

EN397	Protective helmets for industry	MANDATORY	Impact*: force transmitted to the headform must not exceed 5 kN at the fall of an object of 5 kg from a 1m height. The impact energy of the helmet at the end of the test is 49 J. Penetration*: the tip of the mass used in the test (3 kg over 1m) must not come into contact with the skull Flammability: the helmet should not burn with flame emission more than 5 seconds after removal of the flame. * The impact and penetration tests are performed at room temperature, at 50°C and at -10°C
EN	Protective helm	OPTIONAL	In extreme temperatures: impact and penetration tests are conducted at room temperature at 150°C, at -20°C or -30°C Protects against lateral compression. The maximum deformation of the helmet should be ≤ 40 mm Protects against accidental short-term contact with a live electrical conductor up to 440 VAC Resistance to molten metal splashes
EN50365	Electrical insulation helmets for use in low voltage environment	MANDATORY	Electrically insulating helmets for use near energized equipment not exceeding 1000 VAC or 1500 VDC (appliance class 0). Used simultaneously with other electrically insulating protective equipment, these helmets prevent dangerous currents passing through to the person's head. These optional electrical insulation tests are more stringent than the EN397 and they complement them. (2 triangle marking, Class 0).
68Z I	(American National Standards Institute) American standard for industrial head protection	MANDATORY	Depending on the type and class of the helmet:
ANSI	(America Standard American industrial he	OPTIONAL	Protection against mechanical risk (impact, penetration, crushing), flammability, electrical insulation.
EN812	Bump caps for industry	MANDATORY	Impact*: This PPE protects against impacts from knocks against structures or objects. It does not protect from the impact of a falling object at all. The impact energy of the cap at the end of the test reached 12.25 J. Penetration*: the tip of the mass used in the test (0.5 kg over 0.5 m) must not come into contact with the skull * The impact and penetration tests are performed at room temperature, at 50°C and at -10°C Should in no way be a substitute for an industry type helmet (EN397).
EN Bump caps		OPTIONAL	In extreme temperatures: impact and penetration tests are conducted at room temperatur at -20°C or -30°C Protects against accidental short-term contact with a live electrical conductor up to 440 VAC Flammability: the helmet must not burn with flame emission more than 5 seconds after removal of the flame (F marking)

> HELMET MARKING ILLUSTRATION



HEAD PROTECTION

HEARING PROTECTION

▶ HOW TO PROTECT YOURSELF?

To choose the correct product for hearing protection.

- Identify the nature of the noise: stable, fluctuating, intermittent, pulse.
- Measure the noise at the working station: intensity (dB) and volume (Hz).
- Determine the exposure time
- Calculate the reduction necessary to return to an acceptable ambient level (cf Directive 2003/10/CE).

Requirements Directive 2003/10/EC: Minimum requirements for the protection of workers against the risks related to noise exposure						
8 hours exposure time at \geq 85 dB(A)	8 hours exposure time at ≥ 80 dB(A) and < 85 dB(A)	8 hours exposure time at > 75 dB(A) and < 80 dB(A)				

Hearing protectors available

to the worker

Hearing protection

recommended

The performance of the hearing protector (its attenuation level) must be adapted to the risk assessment of the workplace. It should bring the noise level to a level that is not harmful to health, while avoiding overprotection would cut the operator from his environment (warnings, communication...)

STANDARDS

- EN352: Exigences of safety and tests
- EN352-1: the ear-muff
- EN352-2: the earplugs
- **EN352-3:** the adjustable head defenders for the safety helmets.
- EN352-6: Earmuffs with electrical audio input.
- **EN352-8:** Audio enabled earmuffs.

These standards establish requirements with regards to the manufacture, the design, performances and test methods.

They stipulate the putting at disposal relative to the characteristics.


• **EN458:** Hearing protection

Recommendations for selection, use and maintenance.

• ANSI (US American **National Standards** institute) S3.19 - 1974

This standard specifies the test method for determining the level of noise attenuation (NRR Noise Reduction Rating) of the hearing protection, as recommended by the EPA (U.S. Environmental Protection Agency).

ATTENUATION VALUES FOR NOISE



▶ HOW DO YOU USE THE ATTENUATION VALUES?

3 indicators, from the simplest to the most precise are made available to the user:

- **SNR (Single Number Rating) :** Single average value of attenuation.
- HML: Attenuation values expressed in terms of average levels of frequency:
 - **H**: Attenuation of PPE at high frequencies (pitched noises)
 - M: Attenuation of PPE at medium frequencies
 - **L**: Attenuation of PPE at low frequencies (bass sounds))
- APV (Assumed Protection Value): Attenuation values expressed on 8 specific frequency levels (see the data sheet of the hearing protector).

WEARING RATE



2 mn of non-use (during 8h) => reduce the

2 h of non-use (during 8h) => loss of protective effectiveness of 75%

> OTH:



Over the head

UTC :



Under the chin

BTH:



Behind the head



RESPIRATORY PROTECTION

European Directives: End user's obligations

89/391: Identify and assess the risk, take preventive and protective measures, inform and train the workers

2004/37: Risks related to exposure to carcinogens or mutagens at work: hazard identification, «limit values», respiratory protection

89/656; Select and use the appropriate and compliant PPE, inform and train people, check and replace the PPE when necessary

STANDARDS

The main standards concerning the respiratory apparatuses.

• EN136: overall masks

It contains laboratory tests and practical performance tests to check the conformity with resistance to temperature, to impacts, to flame, to thermal radiation, to traction, resistance to cleansers and disinfectants. Furthermore, the visual inspection must concern the marking and the manufacturers' information guide.

• EN140 : half-masks and quarter-masks

It contains laboratory tests and practical performance tests to check the conformity with resistance to impacts, to cleaners and disinfectants, to temperature, to flame and respiratory resistance.

• EN14387 : gas filters and compound filters

It contains laboratory tests to check the conformity with resistance to impacts, to temperature, to humidity and corrosive atmospheres, and with mechanical and respiratory resistance.

• EN143 : filters against particles

It contains laboratory tests to check the conformity with resistance to impacts, to temperature, to humidity and corrosive atmospheres and with mechanical and respiratory resistance.

• EN149 : filtering half-masks

It contains laboratory tests to check the conformity with resistance to impacts, to cleansers and disinfectants, to temperature, to flame and with respiratory resistance.

• EN405 : half-masks fitted with valves and gas filters or compound filters

It contains laboratory tests to check the conformity with resistance to handling and wear, to impacts, to flame and with respiratory resistance.

• EN148-1 : standard threaded joint

This standard is specific to the standard connection system of the cartridge for full face masks.

NIOSH (US National Institute for Occupational Safety) 42 CFR Part84

Filtering facial parts, multiple levels of protection (non exhaustive list):

- **NIOSH 95**: Filter at least 95% of the particles (non-oily) suspended in the air.
- **NIOSH 99 :** Filter at least 99% of the particles (non-oily) suspended in the air.

PRODUCTS	STANDARDS	TOTAL INWARD LEAKAGE** (%)	NOMINAL Protection Factor*					
FFP1	EN149	22	4					
FFP2	EN149	8	12					
FFP3	EN149	2	50					
½ mask P1 ½ mask gazXP1	EN140 EN14387 EN 143/A1	22	4					
½ mask P2 ½ mask gazXP2	EN140 EN14387 EN 143/A1	8	12					
½ mask P3 ½ mask gazXP3	EN140 EN14387 EN 143/A1	2	48					
½ mask gazX	EN140 EN14387	2	50					
Full Face Mask P3	EN136 EN143/A1	0,1	1000					
Full Face Mask gazXP3	EN136 EN14387 EN143/A1	0,1	1000					
Full Face Mask gazX	EN136	0,05	2000					
gazX "NPF : Nominal Protection Factor means the level of protection tested in								

NPF : Nominal Protection Factor means the level of protection tested in laboratory

^{**}TIL: Leakage of the ambient atmosphere into the respiratory interface measured in laboratory






The Level of APF, Assigned Protection Factor, might be different according local regulations

HEAD PROTECTION

RESPIRATORY PROTECTION

► MARKING



GAS AND VAPOUR FILTER

Each filter or cartridge is identified with a colour code.

TYPE	PROTECTION	GAS AND VAPOURS
A	Protects from organic gases and vapours whose boiling point is > 65°C	Alcohol, Acetic Acid, Ether, Hexane, Toluene, Xylene, White Spirit, Thiophenol*
AX	Protects from organic vapours whose boiling point is $\leq 65^{\circ}\text{C}$	Acetone, Acetaldehyde, Ethyl ether, Butane, Methanol, Methan trichloride*
В	Protects from inorganic gases and vapour	Chlorine, Chlorine dioxide, Fluorine, Formaldehyde, Hydrogen Phosphide*
E	Protects from sulphur dioxide and some acid vapours & gases	Sulphur dioxide*
K	Protects from ammoniac and some amine derivatives	Ammonia, Ethylamine, Methylamine*

	FILTER ABSORPTION CLASS FOR GASES AND VAPOURS
Class 1	Low capacity filter (pollutant concentration < 0.1% or 1000 ppm).
Class 2	Average capacity filter (pollutant concentration < 0.5% or 5000 ppm).
Class 3	High capacity filter (pollutant concentration < 0.1% or 10 000 ppm).
ppm	Concentration in parts per million.

▶ PARTICLES/AEROSOLS FILTER

TYPE	PROTECTION	PARTICLES
P1	Protects from non-toxic dust and/or water-based aerosols	Cement dust, flour, calcium carbonate, (chalk), graphite, cotton, concrete*
P2	Protects from slightly toxic or irritating solid aerosols and/or liquids	Untreated softwood, grinding, cutting, welding, milling, coal, glass fibre,mineral fibre, graphite, powdered pesticide*
P3	Protects from solid aerosols and/or liquids listed as toxic	Asbestos (without manipulation), powdered pesticide, biological agents, pharmaceutical powder, treated wood, hard wood (exotic), chromium, lime, lead, graphite*
		Manganese, Kaolin, Sodium hydroxide (Caustic soda), Quartz, Silica*

^{*}This type of usage is indicative and cannot engage Delta Plus Responsibility

USER GUIDE FOR BREATHING APPARATUS FILTER FOR POLLUTING **SUBSTANCES**

Substances	Chemical formula	n° cas	olynov filtry	artick	MC/DM*	0EL	Unit of easur
1- chloro- 2,3- epoxy- propane	C3H5OCI	106-89-8	А	P3	MC	VLE=2	ppm
1,1,1-Trifluoro-2-bromo-2-chloroethane	CF3CHBrCl	151-67-7			ARI or A AIR	2,000	ppm
1,1,2,2- tetrabromoethane	CHBr2CHBr2	79-27-6	Α	P3	MC	1	ppm
1,1'-Ethylene-2,2'-bipyridyllium dibromide	C12H12N2Br2	85-00-7	A	P3	MC MC	0,50	mg/n
1,2,3,4,5,6,7,8-octachloronaphthalene 1,2,4- Trichlorobenzene	C10Cl8 C6H3Cl3	2234-13-1 120-82-1	A	P3	MC	5,00	mg/m ppm
1,2,4-Benzenetricarboxylic anhydride	C9H4O5	552-30-7	A	P3	MC	0,04	mg/n
1,2-Benzenedicarboxylic anhydride	C6H4(C0)20	85-44-9		P3	MC	1,00	ppn
1,2-Dibromo-2,2-dichloroethyl dimethyl phosphate	(CH30)2P(0)OCHBrCBrCl2	300-76-5	Α	Р3	MC	3,00	mg/n
,2-dichloroethane	CICH2CH2CI	107-06-2	Α		MC	10,00	ppn
,2-Dihydroxybenzene	C6H4(OH)2	120-80-9	Α	P3	MC	5	mg/r
,2-Ethanediamine	NH2CH2CH2NH2	107-15-3	K		MC	10,00	ppn
I,2-ethanediol	HOCH2CH2OH	107-21-1	A	P3	MC	50,00	ppr
1,3- butadiene 1,4- dichlorobenzene	CH2=CHCH=CH2 C6 H4 Cl2	106-99-0 106-46-7	AX A		MC MC	VLE= 1 75,00	ppr
1,4-benzenediamine	C6H4(NH2)2	106-40-7	A	P3	MC	75,00	ppr mg/r
,4-dihydroxybenzene	C6H4(OH)2	123-31-9	A	P3	MC	2	mg/r
,4-dinitrobenzene	C6H4(NO2)2	100-25-4	Α	P3	DM or MC	1,000	mg/i
,5-diisocyanatonaphthalene	C10H6(NC0)2	3173-72-6	A2B2	Р3	MC	0,10	mg/i
1,5-pentanedial	OCH(CH2)3CHO	111-30-8	A2	Р3	MC	0,20	ppi
,6- hexanolactam	C6H11NO	105-60-2	Α	Р3	MC	0,22	ppi
-Chloro-2-methylbenzene	CIC6H4CH3	95-49-8	Α		MC	50,00	pp
-Chloro-2-propene	CH2=CHCH2CI	107-05-1	AX		MC	1,00	pp
-Hydroxybutane	CH3CH2CH2CH2OH	71-36-3	Α		MC	50,00	pp
-Methoxy-2-propanol	CH30CH2CHCH3	107-98-2	A	DO:	MC	100	pp
-Methylpropyl acetate	CH3COOCH(CH3)CH2CH3	105-46-4	A	P3	DM or MC	200	pp
-Propen-3-ol -Propyn-3-ol	CH2=CHCH2OH C3H3OH	107-18-6 107-19-7	A		MC MC	2	pp
- hutoxyethanol	C4H9OCH2CH2OH	111-76-2	A	P3	MC	25,00	pp
- Diethylaminoethanol	(C2H5)2NCH2CH2OH	100-37-8	K	10	MC	10,00	pp
2- ethoxyethyl acetate	CH3COOCH2CH2OCH2CH3	111-15-9	Α		MC	1	pp
2- ethylhexyl chloroformate	CI1 C7 02 H12	24468-13-1	Α	P3	DM or MC	1	pp
2- furaldehyde	C5H4O2	98-01-1	Α		MC	2,00	pp
2- Methoxyethyl acetate	CH3COOCH2CH2OCH3	110-49-6	Α		MC	0	pp
2- Methylaziridine	C3H7N	75-55-8	K	P3	MC	2,00	pp
2- methylpentane- 2,4- diol	(CH3)2COHCH2CHOHCH3	107-41-5	Α		DM or MC	25	pp
2- nitronaphthalene	C10H7N02	581-89-5	A	Р	DM or MC		
2- Pyridylamine	NH2C5H4N	504-29-0 111-40-0	A ABEK	P3	DM or MC	2	mg/
2,2'-Diaminodiethylamine 2,2'-dihydroxydiethyamine	NH2CH2CH2)2NH (HOCH2CH2)2NH	111-40-0	K	P3	MC	1,00	pp
2,2-Dichlorovinyl dimethyl phosphate	(CH30)2P(0)0CH=CCI2	62-73-7	A	P3	MC	0,10	pp
2,3- epoxypropyl isopropyl ether	C6H12O2	4016-14-2	A	10	MC	50	pp
2,3,4,5,6-pentachlorophenol	C6CI5OH	87-86-5	А	P3	MC	1	mg
2,3-Dihydro-2,2-dimethyl-7-benzofuranyl							
2,4- dichlorophenoxyacetic acid	CI2C6H30CH2C00H	94-75-7		Р3	MC	10	mg/
2,4,5-Trichlorophenoxyacetic acid	CI3C6H2OCH2COOH	93-76-5		P3	DM or MC	10	mg
2,4,6- trinitrophenol	(NO2)3C6H2OH	88-89-1		P3	MC	0	mg
,4,6-tetryl	(NO2)3C6H2N(NO2)CH3	479-45-8	Α	P3	MC	2	mg
,5-Furanedione	C4 H2 O3	108-31-6	A	P3	MC	0,25	pp
2-Aminotoluene	CH3C6H4NH2	95-53-4	A	P3	MC	2,00	pp
-butanol	CH3CH(0H)CH2CH3 C7H13P06	78-92-2 7786-34-7	A	P3	MC MC	100,00	pp
-Carbomethoxy-1-methylvinyl dimethyl phosphate -Chloro-1,1,2-Trifluoroethyl difluoromethyl ether	CHF20CF2CHCIF	13838-16-9	А	PS	ARI or A AIR	2,000	pp
2-Chloro-1,3-butadiene	CH2=CCICH=CH2	126-99-8	AX	P3	MC	VLE = 1	pp
2-chloroacetaldehyde	CICH2CH0	107-20-0	А		MC	1,00	pp
-Chloroethanol	CH2CICH2OH	107-07-3	Α		MC	1,00	pp
-hydroxymethylfuran	C5H6O2	98-00-0	Α		MC	10,00	pp
-Isopropoxy propane	(CH3)2CHOCH(CH3)2	108-20-3	Α		MC	500,00	pp
-Mercaptoacetic acid	HSCH2COOH	68-11-1	A2B2	Р3	MC	1	pp
-methoxyethanol	CH30CH2CH2OH	109-86-4	Α		MC	5,00	pp
-Methylacrylic acid	CH2=C(CH3)COOH	79-41-4	A AB	P3	MC	20	pp
-methylpropenenitrile	CH2=C(CH3)CN	126-98-7	450	P3	MC	1	pp
-Methylpropyl acetate	CH3COOCH2CH(CH3)2	110-19-0	Α		MC	150.00	pp
-Oxetanone	C3H4O2	57-57-8			ARI or A AIR	400	
-Pentanol acetate	CH3COOCH(CH3)C3H7	626-38-0	A		MC MC	125 50,00	pp
-Phenyl propylene -propenamide	C6H5C(CH3)=CH2 CH2=CHC0NH2	98-83-9 79-06-1	A	P3	MC MC	0,30	pp mg/
-propenantice -propenenitrile	CH2=CHCN CH2=CHCN	107-13-1	A	P3	MC	2,00	mg.
-Propenoic acid	CH2=CHC00H	79-10-7	A		DM or MC	2,000	pp
-Propyl acetate	CH3C00CH(CH3)2	108-21-4	A		MC	250.00 (ST	_
2-Propynyl alcohol	C3H3OH	107-19-7	A		MC	1	pp
3,3'- dichlorobenzidine salts	NH2ClC6H3C6H3ClNH2	91-94-1	А	P3	MC		Ü
3,3'-dimethylbenzidine	C14H16N2	119-93-7	Α	P3	MC	0,02	mg
,5,5- trimethylcyclohex- 2- enone	C9H14O	78-59-1	Α		MC	4,00	pp
a,4,7,7a-Tetrahydro-4,7-methanoindene	C10 H12	77-73-6	Α	Р3	MC	5,00	pp
8-Heptanone	CH3CH2CO[CH2]3CH3	106-35-4	Α		MC	50	pp
s-Methyl-1-butanol acetate	CH3COOCH2CH2CH(CH3)2	123-92-2	Α		DM or MC	100	pp
8-Methyl-5-heptanone	C2H5COCH2CH(CH3)CH2CH3	541-85-5	Α		MC	25	pp
1- Methylpentan- 2- One	CH3COCH2CH(CH3)2	108-10-1	Α		MC	50	pp

OEL OCCUPATIONAL EXPOSURE LIMIT

TWA

TIME WEIGHTED AVERAGE Average Exposure limit over an 8 hour time period



STEL

SHORT TERM EXPOSURE LIMIT Should not be longer than **15 minutes**Should not occur more than 4 times per day with at least 60 minutes between exposures



Substances	Chemical formula	n° cas	Plynové filtry	Particle filter	MC/DM*	0EL	Unit of measure- ment
4,4'- Methylenedianiline (mda)	CH2(C6H4NH2)2	101-77-9	А	P3	MC	0,01	ppm
4-Hydroxy-4-Methyl-2-Pentanone	CH3COCH2C(CH3)2OH	123-42-2	Α		MC	50	ppm
4-Nitroaniline 4-nitrochlorobenzene	C6 H6 N2 02 CIC6H4NO2	100-01-6 100-00-5	A	P3	MC MC	1,00	mg/m3 mg/m3
5-Methyl-2-hexanone	CH3COCH2CH2CH(CH3)2	110-00-3	A	ro	MC	50	ppm
6,9-methano- 2,4,3-benzo-dioxathiepin-3-oxide	C9H6Cl6O3S	115-29-7	A	P3	MC	0	mg/m3
Acetaldehyde	CH3CH0	75-07-0	AX		MC	100	ppm
Acetic acid	CH3COOH	64-19-7	Α	Р3	MC	10.00	ppm
Acetic ester	CH3C00C2H5	141-78-6	Α		MC	400.00	ppm
Acetic oxide	(CH3C0)20	108-24-7 74-86-2	Α		MC	5	ppm
Acetylene	C2H2	107-02-8	AX		ARI or A AIR	2500	ppm
Acraldehyde Age	CH2=CHCH0 C6H1002	106-92-3	450 A		MC	5	ppm
Aldrin	C12H8Cl6	309-00-2	AB	P3	DM or MC	0.25	mg/m3
Alpha- chlorotoluene	C6H5CH2CI	100-44-7	A		MC	1	ppm
Alpha-chloroacetophenone	C6H5C0CH2Cl	532-27-4	ABEK	P3	MC	0,30	ppm
Alpha-starch	(C6H10O5)n	9005-25-8		P3	MC	5,00	mg/m3
Aluminium metal (respirable dust)	Al	7429-90-5		P2/P3	DM or MC	5,000	mg/m3
Aluminum trioxide	Al203	1344-28-1		P3	DM or MC	4	mg/m3
Amidocyanogen Aminocyclohexane	NH2CN C6H11NH2	420-04-2 108-91-8	A	P3	DM or MC DM or MC	2,000	mg/m3 ppm
Aminodimethylbenzene	(CH3)2C6H3NH2	1300-73-8	K		DM or MC	2	ppm
Aminomethane	CH3NH2	74-89-5	K		MC	10	ppm
Ammonia	NH3	7664-41-7	К		MC	25	ppm
Ammonium amidosulfonate	NH4OSO2NH2	7773-06-0		P3	MC	5,00	mg/m3
Ammonium chloride	NH4CI	12125-02-9	K	Р	MC	10	mg/m3
Amyl acetic ether Anhydrous hydrogen bromide;	CH3COO[CH2]4CH3 H Br	628-63-7 10035-10-6	A B	P3	MC MC	100	ppm
Anne Anne	C6H100	108-94-1	A	ro	DM or MC	25,000	ppm
Antimony and compounds (as sb)	Sb	7440-36-0	_ ^	P3	MC	MEL	mg/m3
Antimony hydride	SbH3	7803-52-3			ARI or A AIR	0	ppm
Antimony trioxide	03 Sb2	1309-64-4		Р3	DM or MC	0,500	mg/m3
Argon	Ar	7440-37-1			ARI or A AIR		ppm
Arsenic & compounds except arsine	As	7440-38-2		P3	MC	0,15	mg/m3
Arsenic trihydride Arsenic trioxide	AsH3 As2O3	7784-42-1 1327-53-3			ARI or A AIR ARI or A AIR	0,020	ppm mg/m3
Artificial barite	BaSO4	7727-43-7		P3	MC MC	0,200	mg/m3
ASBESTOS, amiante	Hydrated mineral silicates	1332-21-4	PAPR	P3	MC	MEL	fibres/m
Asphalt, petroleum fumes	n/ a	8052-42-4			ARI or A AIR	5	mg/m3
Atrazine (iso)	C8H14CIN5	1912-24-9		Р3	DM or MC	5,000	mg/m3
Azimethylene	CH2N2	334-88-3	ABEK	P3	MC	0,20	ppm
Azirane	C2H5N	151-56-4	K 450	00	MC	^	ppm
Azium Azodicarbonamide	NaN3 C2H4N4O2/NH2CON=NCONH2	26628-22-8 123-77-3	A	P3 P3	DM or MC MC	0 MEL	mg/m3 mg/m3
Barium compounds soluble (as ba)	Ba	7440-39-3	A	P2/P3	DM or MC	1	mg/m3
Basudin®	C12H21N2O3PS	333-41-5	BE	P3	MC	0,10	mg/m3
BCME [Bis (chloromethyl) ETHER]	(CH2CI)20	542-88-1	A2	P3	MC	0,05	mg/m3
Benomyl (iso)	C14H18N4O3	17804-35-2	Α	Р3	DM or MC	5,000	mg/m3
Benzenamine	C6H5NH2	62-53-3	Α	P3	MC	2,00	ppm
Benzene	C6H6 C6H5CI	71-43-2	A 450		MC	1,00	ppm
Benzene chloride Benzene hexahydride	C6 H12	108-90-7 110-82-7	A		DM or MC DM or MC	75,000 300.000	ppm
Benzyl butyl phthalate	C19 H20 O4	85-68-7	A	Р	DM or MC	5,000	mg/m3
Beryllium and compounds	Be	7440-41-7		Р3	MC	VLE	mg/m3
Beta-Aminoethyl alcohol	NH2CH2CH2OH	141-43-5	А		MC	3	ppm
Beta-Hydroxypropyl acrylate	CH2=CHCOOCH2CHOHCH3	999-61-1	Α		MC	- 1	ppm
BGE	C7 H14 O2	2426-08-6	Α		MC	5,60	ppm
Biotite Biotopium abromate	H2KAl3(SiO4)3	12001-26-2 7789-00-6		P3	DM or MC	3,000	mg/m3 mg/m3
Bipotassium chromate Bis(2- ethylhexyl) phthalate	K2 Cr O4 C24H38O4	117-81-7	A	P3	ARI or A AIR DM or MC	5,000	mg/m3 mg/m3
Bis(2,3- epoxypropyl) ether	C6H1003	2238-07-5	A	P3	MC	0,10	ppm
Bismuth telluride	Bi2Te3	1304-82-1		P3	MC	5,00	mg/m3
Borates, (tetra) sodium salts	Na2B407	1330-43-4		P3	DM or MC	1,000	mg/m3
Borax decahydrate	Na2B407 • 10H20	1303-96-4		Р3	MC	5,00	mg/m3
Boric anhydride	B203	1303-86-2		P3	DM or MC	10,000	mg/m3
Bornan- 2- one	C10H160	76-22-2	Α	P3	DM or MC	2,000	mg/m3
					ARI or A AIR	1,000	ppm
Boron fluoride	BF3	7637 07 02					ppm
Boron fluoride Boron hydride	B2H6	19287-45-7	B	P3	MC DM or MC	0,10	
Boron fluoride Boron hydride Bromacil (iso)	B2H6 C9H13BrN2O2	19287-45-7 314-40-9	B AB B	P3	DM or MC	1,000	ppm
Boron fluoride Boron hydride	B2H6	19287-45-7	AB	_	DM or MC		
Boron fluoride Boron hydride Bromacil (iso) Bromine	B2H6 C9H13BrN2O2 Br2	19287-45-7 314-40-9 7726-95-6	AB B	P3	DM or MC MC	1,000 0,10	ppm ppm
Boron fluoride Boron flydride Bromacil (iso) Bromine Bromine fluoride	B2H6 C9H13BrN2O2 Br2 BrF5	19287-45-7 314-40-9 7726-95-6 7789-30-2	AB B AX	P3	DM or MC MC MC	1,000 0,10 0,10	ppm ppm
Boron fluoride Boron hydride Boronacil (seo) Bromine Bromine fluoride Bromoethane Bromoethylene Bromoform	B2H6 C9H13BrN2O2 Br2 BrF5 CH3CH2Br CH2=CHBr CHBr3	19287-45-7 314-40-9 7726-95-6 7789-30-2 74-96-4 593-60-2 75-25-2	AB B AX AX AX	P3	DM or MC MC MC MC MC MC MC MC DM or MC	1,000 0,10 0,10 200,00 5,000 0,50	ppm ppm ppm
Boron fluoride Boron hydride Bromacil (iso) Bromine Bromine fluoride Bromoethane Bromoethylene Bromoothylene Bromoethane	B2H6 C9H13BrN2O2 Br2 Br5 CH3CH2Br CH2=CHBr CH3R3 CH3Br	19287-45-7 314-40-9 7726-95-6 7789-30-2 74-96-4 593-60-2 75-25-2 74-83-9	AB B AX AX AX AX	P3	DM or MC MC MC MC MC MC MC MC MC MC MC	1,000 0,10 0,10 200,00 5,000 0,50 5	ppm ppm ppm ppm ppm ppm
Boron fluoride Boron hydride Bromacil (so) Bromine Bromine fluoride Bromoethane Bromoethyiene Bromoform Bromomethane Butane	B2H6 C9H13BrN2O2 Br2 BrF5 CH3CH2Br CH2-GHBr CHBr3 CH3Br CH3CH2CH2CH3	19287-45-7 314-40-9 7726-95-6 7789-30-2 74-96-4 593-60-2 75-25-2 74-83-9 106-97-8	AB B AX AX AX AX AX AX	P3	DM or MC MC MC MC MC DM or MC MC MC MC MC MC MC MC DM or MC	1,000 0,10 0,10 200,00 5,000 0,50 5 600,000	ppm ppm ppm ppm ppm ppm ppm
Boron fluoride Boron hydride Bromacil (iso) Bromine Bromine fluoride Bromoethane Bromoethylene Bromoothylene Bromoethane	B2H6 C9H13BrN2O2 Br2 Br5 CH3CH2Br CH2=CHBr CH3R3 CH3Br	19287-45-7 314-40-9 7726-95-6 7789-30-2 74-96-4 593-60-2 75-25-2 74-83-9	AB B AX AX AX AX	Р3	DM or MC MC MC MC MC MC MC MC MC MC MC	1,000 0,10 0,10 200,00 5,000 0,50 5	ppm ppm ppm ppm ppm ppm

This list is not contractual. It is an indicative list and in no way incurs the liability of DELTA PLUS.



HEAD PROTECTION

utyl methyl ketone /MBK utylamine admium adesium hydroxide alcium carbimide alcium narbonate alcium sulfate henilydrate arbonyl cholic acid arbon hexachloride arbonyl chioride arbonyl chi	CH3CO[CH2]3CH3 CH3CH2CH2CH2NH2 Cd S Cs0H CaCN2 CaC02 Ca(CH2)2 Casio3 Ca(CH2)2 Casio3 CaSO4 • 0.5H2O C10HsG014NO2S CH3NHCOOCTOH7 C12H15N03 CGH5OH C CO2 CS2 C13CCC3 OO CCI4 COCI2 CH3CH2COOH CH2BrCl Cd9/Cd C2H5OGH2CH2CHOH (CGH1005)n as Portland Cement C12CCC CI2 CI2 CI3CCCC CI2 CI3CCCCC CI3CCCC CH3CCCC H3CCCC CH3CCC H3CC CH3CCC CH3CC CH3CC CH3CC CH3CC CH3CC CH3CC CH3CC CH3CC	591-78-6 109-73-9 7440-43-9 21351-79-1 156-62-7 1317-65-3 1305-62-0 1344-95-2 26499-65-0 2425-06-1 63-25-2 163-25-2 163-25-2 75-15-0 67-72-1 63-08-9 75-15-0 67-72-1 63-08-9 75-14-5 79-94-1 108-95 1306-19-0 110-80-5 1904-34-6 65997-15-1	A BK B A A A A A A A A A A A A A A A A A	P3 P3 P3 P3 P3 P3 P3 P3 P3 P3 P3 P3 P3 P	MC MG DM or MC DM or MC ARI or A AIR DM or MC DM or MC DM or MC DM or MC MC DM or MC MC MC MC ARI or A AIR MC MC ARI or A AIR MC MC ARI or A AIR MC MC MC MC MC ARI Or A AIR MC MC MC MC MC MC MC MC MC MC MC MC MC	5,00 5,00 VLE=0,05 2,000 0,500 5,000 5,000 5,000 0,100 5,000 0,100 5 3,50 5000,000 1,00 30,000 2,00 0,110	ppm mg/n mg/n mg/n mg/n mg/n mg/n mg/n mg/
acadmium ydroxide acadium carbinide alcium carbinide alcium carbonate alcium hydrate alcium hydrate alcium hydrate alcium hydrate alcium suffate hemitydrate aptafol (so) arbany (so) arba	Cd S	7440-43-9 21351-79-1 156-62-7 1317-65-3 1305-62-0 1344-95-2 26499-65-0 2425-06-1 63-25-2 1563-66-2 108-95-2 1333-86-4 124-38-9 75-15-0 67-72-1 630-08-0 56-22-5 75-94-5 79-09-4 74-97-5 1306-19-0 110-80-5 9004-34-6	A A A A A A A A A A A A A A A A A A A	P3 P3 P3 P3 P3 P3 P3 P3 P3 P3 P3 P3 P3 P	DM or MC DM or MC ARI or A AIR DM or MC DM or MC DM or MC DM or MC DM or MC DM or MC MC DM or MC ARI or A AIR MC ARI or A AIR MC ARI or A AIR MC MC MC MC MC MC MC MC MC MC MC MC MC	VLE=0,05 2,000 0,500 5,000 5,000 5,000 5,000 5,000 0,10 5,000 0,100 5 3,50 5000,000 10,00 1,00 30,000 2,00 0,10	mg/n mg/n mg/n mg/n mg/n mg/n mg/n mg/n
aesium hydroxide alcium carbinide alcium carbinide alcium hydrate alcium monosilicate alcium monosilicate alcium hydrate alcium monosilicate alcium monosilicate alcium suffate hemihydrate aptafol (so) arbolic acid arbonidack arboni	CSOH CaCN2 CaCO23 CaCO23 CaCOH2 CaSO33 CASO4 + 0.5H2O C10H69114N02S CH3NHCOOC10H7 C12H15N03 C6H5OH C C C02 CS2 CS2 C3CCC3 CO CCI4 C0C12 C13CH2C0CH CH2B1C C40/C6 C42B1C C40/C6 C42B1C C40/C6 C42B1C C40/C6 C41B1C C41B1C C61B1C C6	21351-79-1 156-62-7 1317-65-3 1305-62-0 1344-95-2 26499-65-0 2425-06-1 63-25-2 1563-66-2 108-95-2 1333-86-4 124-38-9 75-15-0 67-72-1 630-08-0 56-23-5 75-44-5 79-99-4 74-97-5 1306-19-0 110-80-5 9004-34-6	A A A A A A A A A A A A A A A A A A A	P3 P3 P3 P3 P3 P3 P3 P3 P3 P3 P3 P3 P3 P	DM or MC ARI or A AIR DM or MC DM or MC DM or MC DM or MC DM or MC MC DM or MC MC MC ARI or A AIR MC ARI or A AIR MC MC MC MC MC MC MC MC MC MC MC MC MC	2,000 0,500 5,000 5,000 5,000 5,000 0,10 5,000 0,100 5 3,50 5000,000 1,00 1,00 30,000 2,00 0,10	mg/n mg/n mg/n mg/n mg/n mg/n mg/n mg/n
alcium carbimide alcium carbimide alcium carbonate alcium suffate arbonistaria (so) arbolic acid arbonistaria arbon black arbon dioxide arbon dioxide arbon dioxide arbon dioxide arbon tetrachloride arbon tetrachloride arbon tetrachloride arbon tetrachloride arbonyethane alci arbonyethane alci dic Cadmium elebosowes letelluloce ement thiorida hiborine thiorine dioxide alcium did lethorine fluoride thiorine codde thioroacide alcium did lethorouganide thiorodimethyl ether hiboroethane	Ca(ON2 Ca(OH2) Ca(OH3) Ca(OH3) Ca(OH4	156-62-7 1317-65-3 1305-62-3 1304-95-2 26499-65-0 2425-06-1 63-25-2 108-95-2 1333-86-4 124-38-9 67-72-1 630-08-0 56-23-5 75-44-5 79-09-4 74-97-5 1306-19-0 110-80-5 9004-34-6	A A A A A A A A A A A A A A A A A A A	P3 P2/P3 P3 P3 P3 P3 P3 P3 P3 P3 P3	ARI or A AIR DM or MC DM or MC DM or MC DM or MC DM or MC MC DM or MC MC MC MC MC ARI or A AIR MC MC ARI or A AIR MC MC MC MC MC MC MC MC MC MC MC MC MC	0,500 5,000 5,000 5,000 5,000 0,10 5,000 0,100 5 3,50 5000,000 1,00 1,00 30,000 2,00 0,10	mg/n mg/n mg/n mg/n mg/r mg/r mg/r mg/r ppn mg/r ppn ppn ppn
alcium carbonate alcium hydrate alcium monsilicate alcium monsilicate alcium monsilicate alcium monsilicate alcium monsilicate alcium suffat hemihydrate arbonicaci arbonicaci arbonicaci arbon disulphide arbon hexachloride arbon hexachloride arbonyl chloride arbonyl c	Cacors Calons Calons Casors Casors Casors Casors Casors Chanicoccider Cathonic Cathonic Cathonic Cathonic Cathonic Casors	1317-65-3 1305-62-0 1344-95-2 26499-65-0 2425-06-1 63-25-2 1563-66-2 108-95-2 1333-86-4 124-38-9 75-15-0 67-72-1 630-08-0 56-23-5 75-44-5 79-09-4 74-97-5 1306-19-0 110-80-5 9004-34-6	A A A A B A A	P3 P2/P3 P3 P3 P3 P3 P3 P3 P3 P3 P3	DM or MC DM or MC DM or MC DM or MC MC MC DM or MC MC MC MC ARI or A AIR MC MC ARI or A AIR MC MC MC MC MC MC MC MC MC MC MC MC MC	5,000 5,000 5,000 5,000 0,10 5,000 0,100 5 3,50 5000,000 10,00 1,00 30,000 2,00 0,10	mg/n mg/n mg/n mg/n mg/n mg/n mg/n ppn mg/n ppn ppn ppn ppn ppn
alcium hydrate alcium sunfate monosilicate alcium sunfate hemihydrate asplatol (so) arbouran (so) ar	Ca(0H)2 Ca50(3) Ca504 • 0.5H20 C10H96/14N025 CH3NHC00C10H7 C12H15N03 C6H50H C C C02 C S2 C3CCC3 C0 CC14 C0C2 CH3CH2C00H CH2BrCl Cd0/Cd C2H50CH2C00H CH2BrCl Cd0/Cd C2H50CH2C0OH C(SH1005)n as Portland Cement C10H5CI8 C12 CI2 CI53	1305-62-0 1344-95-2 26499-65-0 2425-06-1 63-25-2 1563-66-2 108-95-2 1333-86-4 124-38-9 75-15-0 67-72-1 630-80-0 56-22-5 75-44-5 79-09-4 74-97-5 1306-19-0 1101-19-0	A A A A B A A	P2/P3 P3 P3 P3 P3 P3 P3 P3	DM or MC DM or MC DM or MC MC DM or MC DM or MC MC MC MC ARI or A AIR MC ARI or A AIR MC MC MC ARI or MC MC MC MC MC MC MC MC MC MC MC MC MC M	5,000 5,000 5,000 0,10 5,000 0,100 5 3,50 5000,000 10,00 1,00 30,000 2,00 0,10	mg/r mg/r mg/r mg/r mg/r mg/r ppr mg/r ppr ppr ppr
alcium sulfate hemitydrate saptafol (so) arbaryl (so) arbotle acid arbon black arbon black arbon disulphide arbon monadde arbon netrachoride arbon netrachoride arbon monadde arbon tetrachoride arbonyt chloride thloride	CaSO4 • 0.5H2O C10H9CI14INO2S CH3NHCOOC10H7 C12H15NO3 C6H50H C C02 C52 C32 C00 CCI4 C0CI2 CH3CH2C0OH CH2BrCl C40/Cd C2H50GH2CH2CHOH (C6H1005)n as Portland Cement C10H6CI8 C12 C12 C12 C12 C12 C12 C12 C13	26499-65-0 2425-06-1 63-25-2 1563-66-2 108-95-2 1333-86-4 124-38-9 75-15-0 67-72-1 630-08-0 56-23-5 75-44-5 79-90-4 74-97-5 1306-19-0 110-80-5 9004-34-6	A A A A B A A	P3 P3 P3 P3 P3 P3 P3 P3	DM or MC MC DM or MC DM or MC MC MC MC ARI or A AIR MC MC ARI or A AIR MC MC MC MC MC MC MC MC MC MC MC MC	5,000 0,10 5,000 0,100 5 3,50 5000,000 10,00 1,00 30,000 2,00 0,10	mg/v mg/v mg/v mg/v ppr mg/v ppr ppr ppr ppr
aptafol (eo) arbany (eo) arbany (eo) arbofuran (eo)	C10H9C114N02S CH3NHC00C10H7 C12H15N03 C6H50H C C02 C52 C3CCC3 C0 CCI4 C00C2 CH3CH2C00H CH2BrC1 C40CC4 C40CC4 C40CC4 C40CC4 C40CC4 C40CC4 C40CC4 C40CC4 C40CC4 C40CC4 C40CC4 C40CC4 C40CC4 C40CC4 C40CC4 C40CC4 C40CC4 C40CC6 C40CC4 C40CC6 C40C6 C40C6	2425-06-1 63-25-2 1563-66-2 108-95-2 1333-86-4 124-38-9 75-15-0 67-72-1 630-08-5 75-44-5 79-90-4 74-95-1306-19-0 110-80-5 9004-34-6	A A A A B A A	P3 P3 P3 P3	MC DM or MC MC MC ARI or A AIR MC ARI or A AIR MC MC ARI or A AIR MC MC MC MC MC	0,10 5,000 0,100 5 3,50 5000,000 10,00 1,00 30,000 2,00 0,10	mg/i mg/i mg/i ppri ppri ppri ppri ppri ppri
carbaryt (iso) carbofuran (iso) carbofuran (iso) carbofuran (iso) carbofuran (iso) carbon black carbon olioide carbon olioide carbon dioxide carbon hexachioride carbon retrachioride carbon retrachioride carbonyethane carbonyet	CH3NHC00C10H7 C12H15N03 C6H50H C C C02 C52 C52 C3CCC3 C0 CCI4 C0CI2 C3CCC3 C0 CCI4 C0CI2 C4CH2C0CH C42BrC1 C40/C6 C40/C6 C4H50C12C4C20H (C6H1005)n as Puttand Cement C10H5CI8 C12 C12 C12 C12 C12 C12 C12 C12 C12 C12	63-25-2 1563-66-2 108-95-2 1333-86-4 124-38-0 67-72-1 630-08-0 56-23-5 75-44-5 79-09-4 74-97-5 1306-19-0 110-80-5 9004-34-6	A A A A B A A	P3 P3 P3 P3 P3 P3	DM or MC DM or MC MC MC ARI or A AIR MC ARI or A AIR MC MC ARI or A AIR MC MC MC MC MC	5,000 0,100 5 3,50 5000,000 10,00 1,00 30,000 2,00 0,10	mg/ pp mg/ pp pp pp pp
arbofuran (so) arbofuran (so) arbofuran (so) arbofuran (so) arbofuran (so) arbofuran disude arbon disude arbon disulphide arbon monoide arbon tetrachioride arbon monoide arbon tetrachioride arbonyethane B dd: Cadmium ellosolve® letiluloee ement hioridan hiborine hiborine fluoride hiboroganide hiboroganide hiboroganide hiboroganide hiborodinethyl ether hiboroethane	C12H15N03 C8H5OH C C02 C S2 C3CCC3 C0 CCI4 C0CI2 CH3CH2C0OH CH2BrC1 C40O/Cd C2H5OOH2CH2OHD (C8H1005)n as Portland Cement C10H6CI8 CI2 CI2 CI2 CI2 CI2 CI2 CI2 CI2 CI2 CI2	1563-66-2 108-95-2 1333-86-4 124-38-9 75-15-0 67-72-1 630-08-0 56-23-5 75-44-5 79-09-4 74-97-5 1306-19-0 110-80-5 9004-34-6	A A A B A A	P3 P3 P3 P3 P3 P3	DM or MC MC MC ARI or A AIR MC ARI or A AIR MC ARI or A AIR MC MC MC	0,100 5 3,50 5000,000 10,00 1,00 30,000 2,00 0,10	mg/l ppl ppl ppl ppl ppl ppl
arbolic acid arbon black arbon disulphide arbon disulphide arbon moscide arbon moscide arbon moscide arbon tetrahoride arbonyl chloride hloridan hlorine hloride hlorine dide hlorine dide hlorine acide hlorocyanide hlorocyanide hlorocyanide hlorocyanide hlorocethane	C6H50H C C02 C52 C52 C13CC03 C0 CC14 C0C12 CH3CH2C00H CH2BrCl C40/Cd C2H509K12CH2OH (C6H1005)n as Portland Cement C10H6Cl8 C12 C12 C12 C153	108-95-2 1333-86-4 124-38-9 75-15-0 67-72-1 630-08-0 56-23-5 75-44-5 79-09-4 74-97-5 1306-19-0 110-80-5 9004-34-6	A A A A A	P3 P3 P3 P3 P3 P3	MC MC ARI or A AIR MC MC ARI or A AIR MC MC ARI or A AIR MC MC MC	5 3,50 5000,000 10,00 1,00 30,000 2,00 0,10	ppi mg/ ppi ppi ppi ppi
arbon black arbon dioxide arbon disulphide arbon monoxide arbon monoxide arbon petrachloride arbon petrachloride arbonyethane B dt: Cadmium tellosove® eluliose tement hiboride hiborine fluoride hiborine dioxide thioroganide hiboroganide hiboroganide hiboroganide hiborodimethyl ether	C CO2 C S2 CISCCG3 CO CCI4 CO02 CH3CH2CO0H CH2BrCI C49C04 C49C9C14CH005)n as Portland Cement C10H5CI8 CI2 CIFS	1333-86-4 124-38-9 75-15-0 67-72-1 630-08-0 56-23-5 75-44-5 79-09-4 74-97-5 1306-19-0 110-80-5 9004-34-6	AX A B A A	P3 P3 P3	MC ARI or A AIR MC MC ARI or A AIR MC MC ARI or A AIR MC MC MC	3,50 5000,000 10,00 1,00 30,000 2,00 0,10	mg/ pp pp pp pp
arbon dioxide arbon dioxide arbon hexachloride arbon monoxide arbon tetrachloride arbony tetrachloride arbonyt dioxide arbonyt	CO2 C S2 C S2 C S2 C S2 C C S2 C C C C C C C C C C C C C C C C C C C	124-38-9 75-15-0 67-72-1 630-08-0 56-23-5 75-44-5 79-09-4 74-97-5 1306-19-0 110-80-5 9004-34-6	A A B A A	P3	MC MC ARI or A AIR MC MC	5000,000 10,00 1,00 30,000 2,00 0,10	pp pp pp pp
arbon hexachloride arbon monoide arbon tetrachloride arbonyt chloride arbonyt chloride arbonyt chloride arbonyt chloride arbonyethane B dd: Cadmium elellosove® elellulose ement hiborida hiboride hiborine fluoride hiborine oxide hiboroeyanide hiboroujanide hiboroujanide hiboroudmethyt ether hiboroudmethyt ether	C13CCC13 C0 CC14 C0C12 CH3CH2C0OH CH2BrC1 C40/Cd C2H500F4CP4CH0H (C6H1005)n as Portland Cement C10H6Cl8 C12 C12 C15	67-72-1 630-08-0 56-23-5 75-44-5 79-09-4 74-97-5 1306-19-0 110-80-5 9004-34-6	A A B A A	P3 P3	MC ARI or A AIR MC MC MC	1,00 30,000 2,00 0,10	pp pp
arbon monooide arbon etachloride arbonyl chloride arbonyethane B dt: Cadmium etlosoke® etlusose ement hlordan hlorine hlorine fluoride hlorine oxide hloroacitic acid chloride hlorooyanide hlorooyanide hloroodimethyl ether	CO CCI4 COCI2 CH3CH2CO0H CH2BrCI Cd0/Cd Cd0/Cd C2H50C42Cd2OH (CH1005)n as Portland Cement C10H5Cl8 CI2 CI2 CI2 CI2 CI3	630-08-0 56-23-5 75-44-5 79-09-4 74-97-5 1306-19-0 110-80-5 9004-34-6	A B A	P3 P3	ARI or A AIR MC MC MC	30,000 2,00 0,10	pp
arbon tetrachloride arbonyd folioride arbonyd folioride B d: Cadmium ellosolwe® elluloce ement hloridan hlorine hlorine fluoride hlorine de ellosolwe ellosolwe elluloce ement hloridan hlorine bloride hlorine fluoride hlorine oxide hlorocyanide blorocyanide blorocodinethyl ether hlorocithane	CCI4 COCI2 CH2CH2COOH CH2BrCI C46/Cd C2H50CH2CH2OH (CSH1005)n as Portland Cement C10H6GB CI2 CI2 CI2	56-23-5 75-44-5 79-09-4 74-97-5 1306-19-0 110-80-5 9004-34-6	B A A	P3	MC MC	2,00 0,10	pp
arbonyl chloride arbonyethane B d: Cadmium ellosolve® ellulose ement hlordan hlorine hlorine fluoride hlorine oxide hloriose aide hlorosantie ellosolve® ellulose	COCIZ CH3CH2COOH CH2BrCI C400/Cd C2H5004R2CH2OH (C6H1005)n as Portland Cement C10H6CI8 CI2 CI2 CIF3	75-44-5 79-09-4 74-97-5 1306-19-0 110-80-5 9004-34-6	B A A	P3	MC MC	0,10	pp
arboyethane B d: Cadmium ellosolve@ ellulose ement hloridan hlorine hlorine fluoride hlorine oxide hlorocavaride hlorocyaride hlorocyaride hlorodimethyl ether	CH3CH2COOH CH2BrCl Cd0/Cd C2H50GH2CH2OH (CGH1005)n as Portland Gement C10H6Cl8 C12 C1F3	79-09-4 74-97-5 1306-19-0 110-80-5 9004-34-6	A	P3	MC	_	
B d: Cadmium elidisorive® elidisore ement hlordan hlorine hlorine fluoride hlorine oxide hloroacetic acid chloride hlorooyanide hloroodimethyl ether hloroodithane	CH2BrCl Cd0/Cd C2H50CH2CH2OH (C6H1005)n as Portland Cement C10H6Cl8 Cl2 ClF3	74-97-5 1306-19-0 110-80-5 9004-34-6	A				bb
d: Cadmium ellosolve® ellolose ement hlordan hlorine hlorine elloride hlorine duode hloroacetia acid chloride hloroyanide hloroyanide hlorodimethyl ether	Cd0/Cd C2H50CH2CH20H (C6H1005)n as Portland Cement C10H6Cl8 Cl2 ClF3	1306-19-0 110-80-5 9004-34-6		P3		200,00	pp
ellosolve® ellulose ement hlorian hlorine hlorine fluoride hlorineovide hloroseatia eaid chloride hlorooyanide hlorooyanide hloroofmethyl ether	C2H50CH2CH2OH (C6H1005)n as Portland Cement C10H6Cl8 Cl2 ClF3	110-80-5 9004-34-6	Α		MC	VLE=0,05	ma.
ellulose ement hlordan hlorine hlorine fluoride hlorine adde hlorine adde hlorine adde hlorocyanide hlorocyanide hlorocyanide hlorocimethyl ether	(C6H1005)n as Portland Cement C10H6Cl8 Cl2 CIF3	9004-34-6			MC	0,50	pp
hlordan Notrine Moriae Notrine fluoride Notrine oxide Notroaeste acid chloride Notroayanide Notrodimethyl ether Notroethane	as Portland Cement C10H6Cl8 Cl2 ClF3			P3	DM or MC	5,000	ma
hlordan Notrine Moriae Notrine fluoride Notrine oxide Notroaeste acid chloride Notroayanide Notrodimethyl ether Notroethane	C10H6Cl8 Cl2 ClF3			P2/P3	DM or MC	10,000	mg
hlorine fluoride hlorine oxide hloroacetic acid chloride hloroocyanide hlorodimethyl ether hlorodithate	CIF3	57-74-9	А	P3	DM or MC	0,500	mg
nlorine oxide hloroacetic acid chloride hlorocyanide hlorodimethyl ether hloroethane		7782-50-5	В		MC	0,50	pp
hloroacetic acid chloride hlorocyanide hlorodimethyl ether hloroethane		7790-91-2	В		MC	0,10	pp
hlorocyanide hlorodimethyl ether hloroethane	CI 02	10049-04-4	В		DM or MC	0,100	pp
hlorodimethyl ether hloroethane	CICH2COCI	79-04-9	Α	P3	MC	0,05	pp
hloroethane	CICN	506-77-4	B 450		MC ADLex A AID	0,30	pp
	CH30CH2CI	107-30-2	PV.		ARI or A AIR	1000.000	
morocalation acid	CH3CH2CI CICH2COOH	75-00-3 79-11-8	AX A	P3	DM or MC MC	1000,000	pp
hloroethene	CH2=CHCI	75-01-4	AX	ro	MC	1,00	pp
hloroform	CHCI3	67-66-3	AX		MC	2,00	Di
hloromethane	CH3CI	74-87-3	- A		ARI or A AIR	100,000	pr
hloropicrin	CCI3NO2	76-06-2	А	P3	MC	0,10	pp
hlorosulfuric acid	HCLO3S	7790-94-5	Е	P3	MC	1,00	mg
hlorothene	CH3CCI3	71-55-6	Α		MC	300,00	pp
hlorpyrifos	C9H11Cl3NO3PS	2921-88-2	А	Р3	DM or MC	0,200	mg
hromic acid (cro3)	CrO3	1333-82-0	BE	Р3	MC	0,05	mg
hromium	Cr	7440-47-3		P3	MC	0,50	mg
obalt and compounds (as co)	Co	7440-48-4		P2/P3	DM or MC	VLE	mg
opper, dusts and mists	Cu	7440-50-8		P3	MC	1,00	mg
rag® herbicide No. 1	C6H3Cl2OCH2CH2OSO3Na	136-78-7		P3	MC	5,00	mg.
resols (all isomers)	C7 H8 0 C6H5CH(CH3)2	1319-77-2	A	P3	MC MC	5,00 50.00	pp
vanogen chloride, (as -cn)	C- N	57-12-5	В	P3	MC	5,00	mg
yclohexene	C6 H10	110-83-8	A	13	DM or MC	300.000	pp
yclohexylmethane	CH3C6H11	108-87-2	A		DM or MC	400,000	pp
BP	C6H4(C00C4H9)2	84-74-2	Α	P3	MC	5,00	mg
ca	C2Cl2	7572-29-4			ARI or A AIR	0,100	pp
DH	C5H6Cl2N2O2	118-52-5	ABEK	P3	MC	0,20	mg
DT	(C6H4CI)2CHCCI3	50-29-3		P3	MC	1	mg
i- N- Butyl Phoshate	(C4H90)2(OH)PO	107-66-4	Α	P3	MC	1,00	pp
iallyl phthalate	C14 H14 O4	131-17-9	A	P3	DM or MC	5,000	pp
iammonium peroxodisulphate	N2 H8 S2 08	7727-54-0	A	P3	MC	1,00	mg
ianiline (mboca)	CH2(C6H4CINH2)2	101-14-4	Α	P3	MC	0,00	mg
iatomaceous earth, natural, respirable dust IBENZ(a, h) ANTHRACENE	SiO2 C22 H14	68855-54-9 65996-93-2	A	P3	MC MC	1,20 0,10	mg mg
ibenz(a, ri) ani hnacene ibenzoyl peroxide	(C6H5C0)202	94-36-0	A	P3	DM or MC	5,000	mg
ibromochloropropane	CH2BrCHBrCH2CI	96-12-8	Ĺ	13	ARI or A AIR	0,001	pp
ibutyl phosphate	(C4H90)2(OH)PO	107-66-4	А	P3	MC	1,00	pp
ibutylated hydroxytoluene	[C(CH3)3]2CH3C6H2OH	128-37-0		Р	MC	10,00	mg
ichloromethane	CH2Cl2	75-09-2	AX		MC	50,00	pp
ichloromethyl ether	(CH2CI)20	542-88-1	A2	P3	MC	0,05	mg
icyanogen	NCCN	460-19-5	BK		DM or MC	10,000	pp
icyclohexyl phthalate	C20 H26 O4	84-61-7	Α	P3	DM or MC	5,000	pp
ieldrin (iso)	C12H8Cl60	60-57-1	A	P3	DM or MC	0,250	mg
ethyl ether	C2H50C2H5	60-29-7	AX	DC	MC DM or MC	400,00	pp
iethyl phthalate iethyl sulphate	C6H4(C00C2H5)2	84-66-2	A	P3	DM or MC	5,000	mg
iethyl sulphate iethylene imidoxide	C4 H10 O4 S C4H9ON	64-67-5 110-91-8	A	P3	MC MC	VLE 20	pp
ietnylene imidoxide ifluorodibromomethane	CHH9UN CBr2F2	75-61-6	A		ARI or A AIR	100,000	pp
iisodecyl phthalate	C28 H46 O4	26761-40-0	A	P3	DM or MC	5,000	mg
iisononyl phthalate	C26 H42 O4	28553-12-0	A	P3	DM or MC	5,000	mg
iisooctyl phthalate	C24 H38 O2	27554-26-3	А	P3	DM or MC	5,000	mg
iisopropylamine	[(CH3)2CH]2NH	108-18-9	K		MC	5	pp
imethyl carbinol	(CH3)2CH0H	67-63-0	А		MC	400	pp
imethyl ester of 1,2-benzenedicarboxylic acid	C6H4(C00CH3)2	131-11-3	А	P3	MC	5,00	mg
imethyl ether	H6 C2 O	115-10-6			ARI or A AIR	400,000	pp
imethyl methane	CH3CH2CH3	74-98-6			ARI or A AIR	1000,000	pp
imethyl sulphate	(CH3)2SO4	77-78-1	А	P3	MC	0,10	pp
imethylacetone	CH3CH2COCH2CH3	96-22-0	A		DM or MC	200,000	pp
imethylaminoethanol	C4H11NO/(CH3)2NCH2CH2OH	108-01-0	A	D.C.	MC	?2	pp
imethylnitromethane	(CH3)2CH(NO2)	79-46-9	A NO	P3	MC	10,00	pp
initrogen tetroxide (N2O4),	N 02	10102-44-0	NO A	DO:	MC	3,00	pp
iphenyl	C6H5C6H5	92-52-4	A	P3	MC MC	0,20	pp
iphenyl ether (vapor) ipotassium peroxodispulphate (measured as s2o8)*	C6H5OC6H5 H2 K2 O8 S2	101-84-8 7727-21-1	A	P3	MC MC	1,00	pp
ipotassium peroxodispuipnate (measured as szos): firex®	C6H3Cl2NHCON(CH3)2	330-54-1	mD	P3	DM or MC	10,000	mg.
isodium peroxodisulphate (measured as s2o8)	Na2 08 S2	7775-27-1	A	P3	MC	1,00	mg.

Substances	Chemical formula	n° cas	Plynové filtry	Particle filter	MC/DM*	0EL	Unit of measure- ment
Disodium tetraborate, pentahydrate	B4 07 2Na 10H 20	11130-12-4	А	P3	DM or MC	1,000	mg/m3
Disulfoton (iso)	C8H19O2PS3	298-04-4	ABE	P3	MC	0,10	mg/m3
Disulphur dichloride	S2 CI2	10025-67-9	В	P3	MC	1,00	ppm
Divanadium pentaoxide (as v) DMAC	V205 CH3CON(CH3)2	1314-62-1 127-19-5	A	P3	MC DM or MC	VLE=0,005 10,000	ppm
DMF	HCON(CH3)2	68-12-2	A		MC	10,000	ppm
DMH	(CH3)2NNH2	57-14-7	K 450		MC	0,06	ppm
Eca	C6H7NO2	7085-85-0	AXB	Р3	MC	2	mg/m3
Elemental selenium	Se	7782-49-2		P3	MC	0	mg/m3
Endrine Ethane	C12H8Cl60	72-20-8		P3	MC	0,10	mg/m3
Ethanedioic acid	C2 H6 H00CC00H • 2H20	74-84-0 144-62-7		P3	ARI or A AIR MC	1	ppm mg/m3
Ethanethiol	CH3CH2SH	75-08-1	AX	P3	MC	1	ppm
Ethyl acetone	CH3COCH2CH2CH3	107-87-9	А		MC	200	ppm
Ethyl acrylate	CH2=CHC00C2H5	140-88-5	Α		MC	5,00	ppm
Ethyl alcohol	CH3CH2OH	64-17-5	А		MC	1000	ppm
Ethyl chloroformate	C3H5ClO2 / ClCOOC2H5	541-41-3			ARI or A AIR	1	ppm
Ethyl ester of formic acid	CH3CH2OCHO	109-94-4	AX		MC	100	ppm
Ethyl methyl ketone Ethyl nitrile	CH3COCH2CH3 CH3CN	78-93-3 75-05-8	A		MC MC	200,00	ppm
Ethyl parathion	(C2H50)2P(S)0C6H4N02	56-38-2	A2	P3	MC	0	ppm mg/m3
Ethylamine	CH3CH2NH2	75-04-7	K	10	MC	10,00	ppm
Ethylbenzene	CH3CH2C6H5	100-41-4	A		MC	100	ppm
Ethylene	C2 H4	74-85-1			ARI or A AIR		ppm
Ethylene bromide	BrCH2CH2Br	106-93-4	Α		MC	0,05	ppm
Ethylene oxide	C2H40	75-21-8	AX		MC	5,00	ppm
Ferbam (iso)	[(CH3)2NCS2]3Fe	14484-64-1		P3	MC	10	mg/m3
Ferrocene	C10 H10 Fe	102-54-5	A	P	MC	10	mg/m3
Fluoride (as f) Fluorine-19	F ₂	16984-48-8 7782-41-4	AB B	P3	DM or MC MC	1,00	mg/m3 ppm
Formal	CH30CH20CH3	109-87-5	AX		MC	1000,00	ppm
Formaldehyde	HCHO	50-00-0	ABE		MC	0,50	ppm
Formamide	HCONH2	75-12-7	A	P3	MC	10,00	ppm
Formic acid	HC00H	64-18-6	B / BE	Р3	MC	5	ppm
Formonitrile	HCN	74-90-8	В	P3	MC	2,00	ppm
Freon® 112	CCI2FCCI2F	76-12-0	Α		MC	500,00	ppm
Freon® 112a	CCI3CCIF2	76-11-9	Α		MC	500,00	ppm
Freon® 113	CCI2FCCIF2	76-13-1			ARI or A AIR	1000	ppm
Freon® 114 Freon® 12	CCIF2CCIF2 CCI2F2	76-14-2 75-71-8			ARI or A AIR ARI or A AIR	1000,000	ppm ppm
Freon® 21	CHCI2F	75-43-4			ARI of A AIR	10,000	ppm
Freon® 22	CHCIF2	75-45-6			ARI or A AIR	1000,000	ppm
Germanium tetrahydride	GeH4	7782-65-2			ARI or A AIR	0	ppm
Glycerol	HOCH2CH(OH)CH2OH	56-81-5	А	Р3	MC	5,00	mg/m3
Glycidyl phenyl ether	C9H10O2	122-60-1	Α		MC	1	ppm
Glycol dinitrate	02N0CH2CH20N02	628-96-6	Α	Р	MC	0,20	ppm
Graphite Guthion®	C C10H12O3PS2N3	7440-44-0 86-50-0	A	P2/P3 P3	DM or MC DM or MC	5,000	mg/m3
Gypsum	Ca S 06 H4	10101-41-4	A	P3	MC	4	mg/m3 mg/m3
Hafnium	Hf	7440-58-6		P3	MC	1	mg/m3
Halon® 1301	CBrF3	75-63-8			ARI or A AIR	1000,000	
Helium	He				ARI or A AIR		ppm
Heptan- 2- one	CH3CO[CH2]4CH3	110-43-0	А		MC	100	ppm
Hexachlorobenzene	C6 CI6	118-74-1	Α	Р3	MC	0,03	mg/m3
Hexahydromethylphenol	CH3C6H10OH	25639-42-3	A		MC	50	ppm
Hexalin Hexamethyl phosphoramide	C6H110H ((CH3) 2NI 3PO	108-93-0 680-31-9	A		MC ARI ou A AIR	50,00	ppm
Hexane	CH3[CH2]4CH3	110-54-3	A		DM ou MC	50	ppm
Hydrated lime	Ca(OH)2	1305-62-0	,,	P3	DM or MC	5,000	mg/m3
Hydrazine	H2NNH2	302-01-2	К	P3	MC	0,10	ppm
Hydrazinobenzene	C6H5NHNH2	100-63-0	Α	P3	DM or MC	0,140	ppm
Hydrazoic acid (as vapour)	H N3	7782-79-8	K	P3	MC	0	ppm
Hydrogen	H2	1333-74-0 ?			ARI or A AIR		ppm
Hydrogen chloride	H CI	7647-01-0	B	P3	MC	5,00	ppm
Hydrogen fluoride (as f)	HF	7664-39-3	B 450 B/BE/	P3	MC	3.00 (ST)	ppm
Hydrogen nitrate	HN03	7697-37-2	NO	P3	MC	2	ppm
Hydrogen peroxide Hydrogen phosphide	H202 PH3	7722-84-1 7803-51-2	AB B	P3	MC MC	0,10	ppm
Hydrogen sulfate	H2SO4	7664-93-9	BE	P3	MC	1	mg/m3
Hydrogen sulphide	H2 S	7783-06-4	450 B	1.3	MC	10	ppm
Hydroquinone monomethyl ether	CH30C6H40H	150-76-5		P3	MC	5	mg/m3
Hydrous magnesium silicate	Mg3Si4010(0H)2	14807-96-6		P3	MC	2,00	mg/m3
Hyponitrous acid anhydride	N2 O	10024-97-2	NO		MC	25,000	ppm
Impure corundum	Al203	1302-74-5		P3	DM or MC	5	mg/m3
Indium and compounds (as in)	In	7440-74-6		P3	MC	0	mg/m3
Indonaphthene	C9 H8	95-13-6	A		MC	10	ppm
lodine	12	7553-56-2	IPR	P3	MC	0,10	ppm
Iodomethane	CH3I	74-88-4	AX	Do.	MC DM or MC	VLE=2	ppm
Iron (III) oxide Iron oxide, fume (as fe)	Fe203 Fe203	1309-37-1 1309-37-1		P3	DM or MC DM or MC	5	mg/m3 mg/m3
Iron oxide, rume (as re)	Fe(C0)5	13463-40-6	A	P3	MC MC	0	ppm
Isobutanol	(CH3)2CHCH2OH	78-83-1	A		MC	50	ppm
Isobutenyl methyl ketone	(CH3)2C=CHCOCH3	141-79-7	A		MC	10,00	ppm
Isoflurane	C3 F5 H2 CI O	26675-46-7			ARI or A AIR	50	ppm
Isophorone diamine diisocyanate	C12H18N2O2	4098-71-9	А		MC	VLE=0,01	ppm
Isopropyl chloroformate	C4H7ClO2/(CH3)2CH0C0Cl	108-23-6	А	P3	MC	? 1.00	ppm
Isovalerone	[(CH3)2CHCH2]2CO	108-83-8	Α		MC	25,00	ppm
Jasmolin I or II	C20H2803 / C21H2805 C21H3003 / C22H3005	8003-34-7	A	P3	MC	5.00	mg/m3
	C21H28O3 / C22H28O5		-				
Kaolin Vata ethylene	(Al2Si2O5(OH)4)2	1332-58-7		P3	DM or MC	5	mg/m3
Keto-ethylene Ketone propane	CH2=C0 (CH3)2C0	463-51-4 67-64-1	AX		ARI or A AIR MC	1 500	ppm
Lead and compounds (except lead alkyls)	(GH3)2GU Pb	7439-92-1	PA .	P3	MC	150,00	ppm μg/ m3
Lepidolite	n/a	12001-26-2		P3	DM or MC	3,000	mg/m3
Lime	CaO	1305-78-8		P2/P3		2,00	mg/m3
			-				3

TECHNICAL INFORMATION

Substances	Chemical formula	n° cas	Plynov filtry	Particl filter	MC/DM*	0EL	Unit o neasur
Lithium hydroxide	LiOH	1310-65-2		P3	MC	1.00 (ST)	mg/n
Lithium monohydride*	LiH Mix : C3 H6: C3 H8: C4 H8:	7580-67-8	Α	P3	MC	0,025	mg/n
LPG (Liquefied Petroleum Gas) Magnesite	Mix : C3 H6; C3 H8; C4 H8; C4 H10	68476-85-7 546-93-0		P3	ARI or A AIR	1000.00	ppm mg/m
Magnesium oxide, fume and dust (as mg)	MgCO3 MgO	1309-48-4		P3	DM or MC	15	mg/n
Malathion (iso)	C10H19O6PS2	121-75-5	Α	P3	MC	10	mg/n
Manganese and compounds (as mn)	Mn	7439-96-5		P2/P3	DM or MC	1,000	mg/n
Manganese tetroxide Manganese tricarbonylmethylcyclopentadieny	Mn3O4 CH3C5H4Mn(CO)3	1317-35-7 12108-13-3	A	P3	DM or MC MC	0	mg/m
Margarite	n/ a	12001-26-2	_ ^	P3	DM or MC	3,000	mg/n
MD	C5H5Mn(C0)3	12079-65-1	А	P3	DM or MC	0,100	mg/n
MDI	CH2(C6H4NC0)3	101-68-8	A	P3	MC	0,01	ppn
Mecrylate Mercury & its inorganic divalent compounds	CH2=C(CN)COOCH3	137-05-3 7439-97-6	A Hg	P3	MC DM or MC	2,00 0,050	ppm mg/m
Mesitylene	C6H3(CH3)3	108-67-8	A	13	MC	25	ppn
Methacrylate monomer	CH2=C(CH3)COOCH3	80-62-6	А		MC	100	ppn
Methane	C H4	74-82-8			ARI or A AIR		ppn
Methane tetrabromide	CBr4	558-13-4	A	D0	DM or MC	1,400	mg/n
Methane tetramethylol Methanethiol	C(CH20H)4 CH3SH	115-77-5 74-93-1	A AXB	P3	MC MC	5 0,50	mg/n
Methanol	CH30H	67-56-1	AX		MC	200	ppn
Methomyl (iso)	CH3C(SCH3)NOC(0)NHCH3	16752-77-5		P3	MC	3	mg/n
Methoxy-dtt	(C6H4OCH3)2CHCCI3	72-43-5	А	P3	DM or MC	15,000	mg/n
Methyl acetate	CH3COOCH3	79-20-9	AX		MC	200.00	ppn
Methyl ester of formic acid Methyl ester of isocyanic acid	HCOOCH3 CH3NCO	107-31-3 624-83-9	AX B	P3	MC MC	100 VLE=0,02	ppn mg/n
Methyl ester of isocyanic acid Methyl ethylene oxide	CH3NCO C3H6O	75-56-9	AX	rJ	MC MC	100,00	mg/r ppr
Methyl parathion	(CH30)2P(S)0C6H4N02	298-00-0	450 A2	P3	MC	0	mg/r
Methyl phosphite	(CH30)3P	121-45-9	A	P3	MC	2	ppr
Methyl propenoate	CH2=CHC00CH3	96-33-3	А		MC	10	ppr
METHYL- t- BUTYL ETHER	C5 H12 O	1634-04-4	AX	P3	MC	25	ppr
Methylene oxide Methylstyrene	HCHO CH2=CHC6H4CH3	50-00-0 25013-15-4	ABE		MC MC	0,50	ppr
Methylstyrene Miak	CH2=UHC6H4UH3 CH3COCH2CH2CH(CH3)2	110-12-3	A		MC MC	100 50	ppr
Mibc	(CH3)2CHCH2CH(OH)CH3	108-11-2	A		MC	25	ppn
MMH	CH3NHNH2	60-34-4	AK	P3	MC	0,04	ppr
Molybdenum compounds (as mo)	Mo	7439-98-7		P3	MC	5	mg/r
Monochloropentafluoroethane	CCIF2CF3	76-15-3			ARI or A AIR	1000,000	ppr
Monofluorotrichloromethane N- Butyl chloroformate	CCI3F C5 H10 CL 02	75-69-4 592-34-7	A	P3	ARI or A AIR	1,00	ppr
N- propyl acetate	CH3COOCH2CH2CH3	109-60-4	A	P3	MC	200.00	ppr
V, n- dimethylaniline	C6H5N(CH3)2	121-69-7	A	P3	MC	5,00	ppr
N,N'-Dimethyl-4,4'-bipyridinium dichloride	CH3(C5H4N)2CH3 • 2CI	1910-42-5	А	P3	MC	0,10	mg/r
Naphthalene	C10H8	91-20-3	А	P3	MC	10,00	ppn
Navadel®	C4H602[SPS(0C2H5)2]2	78-34-2	A	P3	MC	0,20	mg/r
Neon	Ne (COLESCANI)	7440 01 9 109-89-7	K+		ARI or A AIR MC	10.00	ppr
N-Ethylethanamine N-Ethylmorpholine	(C2H5)2NH C6 H13 N O	109-89-7	450 A	P3	MC	10,00 5.00	ppr
Ng	CH2N03CHN03CH2N03	55-63-0	A	P3	DM or MC	0,100	mg/r
Nickel and inorganic compounds	Ni	7440-02-0		P3	DM or MC	1,000	mg/r
Nickel carbonyl	Ni(CO)4	13463-39-3			ARI or A AIR	0.10 (ST)	ppr
Nicotine	C5H4NC4H7NCH3	54-11-5	A	P3	DM or MC	1	mg/r
Nitrapyrin Nitric oxide	CIC5H3NCCI3 N O	1929-82-4 10102-43-9	AB	P3	MC ARI or A AIR	5,00 25	mg/r
Nitrocarbol	CH3NO2	75-52-5	A	P3	MC	100	ppn
Nitroethane	CH3CH2NO2	79-24-3	Α	P3	MC	100	ppn
Nitrogen	N2	7727-37-9			ARI or A AIR		ppn
Nitrogen trifluoride	NF3	7783-54-2			ARI or A AIR	10	ppn
Nitropropane	CH3CH2CH2NO2	108-03-2	A	P3	MC	25	ppn
N-methylmethanamine NN- Dimethylethylamine	(CH3)2NH C4 H11 N	124-40-3 598-56-1	K	P3	MC MC	10,00 5,00	ppn
N-Nitroso-N,N-dimethylamine	(CH3)2N2O	62-75-9	A	P3	MC	3,00	ppi
N-octane	CH3[CH2]6CH3	111-65-9	Α		MC	75,00	mg/n
Nonyphenols	C15H240	25154-52-3	А	P3	MC		
N-phenylmethylamine	C6H5NHCH3	100-61-8	Α		DM or MC	1	ppn
N-Trichloromethylmercapto-4-cyclohexene 1,2-dicarboximide	C9H8Cl3N02S	133-06-2	Α	Р3	DM or MC	5,000	mg/r
Nux vomica	C21H22N2O2	57-24-9		P3	MC	0	mg/r
O- acetylsalicylic acid	CH3C00C6H4C00H	50-78-2		P2/P3	DM or MC	5.00	mg/r
D-anisidine D-dianisidine	NH2C6H4OCH3 (NH2C6H3OCH3)2	90-04-0	A	P3	MC DM or MC	1	mg/r
O-diphenylbenzene	C6H5C6H4C6H5	84-15-1		P3	DM or MC	1	ppr
Dil mist, mineral	001100011100110	8012-95-1		P3	MC	5	mg/r
Oil of mirbane	C6H5N02	98-95-3	А	P3	MC	1	ppn
O-nitrotoluene	N02C6H4CH3	88-72-2	А	P3	MC	2,00	ppn
Ortho-dichlorobenzene	C6H4Cl2	95-50-1	A	200	MC	50,00	ppn
Orthophosphoric acid O-sec-Butylphenol	H3PO4 CH3CH2CH(CH3)C6H4OH	7664-38-2 89-72-5	B	P3	MC MC	1.00 (ST) 5,00	mg/n
D-sec-Butylphenol Dsmium oxide	0s04	20816-12-0	В	P3	MC	0,00	mg/r
Oxooctyl alcohol	C7H15CH2OH	26952-21-6	A		MC	50	ppr
Ozone	03	10028-15-6	AXB2	Р3	MC	0	ppr
- Aramid respirable fibres	(C14 H10 O2 N2) n	26125-61-1		P3	DM or MC	0.50	fibres
P- toluenesulphonyl chloride	C7 H7 S O2 CI	98-59-9	AB	P3	DM or MC	5.00 (ST)	mg/n
Paracetamol	C8 H9 N O2	103-90-2	,	P3	DM or MC	10 00	mg/n
P-Dioxane Pentachlorophosphorus	C4H802 PCI5	123-91-1 10026-13-8	A B	P3	MC MC	10,00	ppr mg/r
Pentane	CH3[CH2]3CH3	109-66-0	AX	13	MC	120	ppr
Peracetic acid	C2H4O3	79-21-0	AB	P3	DM or MC		ppr
Peroxide de 2-Butanone	C8H16O4	1338-23-4	А	Р3	MC	VLE=0,2	ppr
Phenyl phosphate	(C6H5O)3PO	115-86-6	А	P3	MC	3	mg/r
Phenylaniline	(C6H5)2NH	122-39-4	A	P3	MC	10,00	mg/r
Phenylethylene	C6H5CH=CH2	100-42-5 298-02-2	A	P3	MC MC	50,00	ppr ma/r
Phorate	(C2H50)2P(S)SCH2SC2H5		_				mg/r
Phosphorus oxychoride	POCI3	10025-87-3	I B	P3	MC	0	


Substances	Chemical formula	п° cas	Plynové filtry	Particle filter	MC/DM*	0EL	Unit of measure- ment
Phosphorus pentoxide		1314-56-3	А	P3	DM or MC	2.00 (ST)	mg/m3
Phosphorus trichloride	PCI3	7719- 12 2	B 450	P3	MC	0	ppm
Phosphorus, yellow Picloram (iso)	P4 C6H3Cl3O2N2	7723-14-0 1918-02-1	AR	P3	ARI or A AIR MC	5,00	mg/m3
Piperazine hydrochloride	C4H10N2 HCI	142-64-3	AD	P3	MC	5.00	mg/m3
Piperidine	CH2(CH2)4NH	110-89-4	А		DM or MC	?	ppm
Platinum metal	Pt	7440 06 4		P2/P3	DM or MC	5	mg/m3
Polychlorinated biphenyl	C6H3Cl2C6H2Cl3	11097-69-1	AB	P3	MC	0,10	mg/m3
Polychlorinated biphenyls (pcb's)	C12 H(10- x) Clx	1336-36-3			ARI or A AIR	0,500	mg/m3
Potassium bromate	K Br 03	7789-01-2		P3	DM or MC		
Potassium hydroxide	КОН	1310-58-3	١	P3	MC	2.00 (ST)	mg/m3
P-quinone Primary isoamyl alcohol	0C6H40 (CH3)2CHCH2CH2OH	106-51-4 123-51-3	A	P3	MC MC	0,10	ppm
Propranolol	C16 H21 N O2	525-66-6	A	P3	DM or MC	2	mg/m3
Propylene	C3 H6	115-07-1		10	ARI or A AIR	_	ppm
Propylene glycol	as Propane- 1,2- diol	57-55-6	А	P3	DM or MC	150	ppm
Propylene glycol-1,2-dinitrate	CH3CNO20HCHNO20H	6423-43-4	Α	P3	MC	0	ppm
Pvc (polyvinyl chloride) (resp. Dust)	(C2 H3 Cl) N	9002-86-2		Р3	MC	4	mg/m3
Pyridine	C5H5N	110-86-1	Α	P3	MC	5	ppm
Pyrophosphate	Na4P207	7722-88-5		P3	MC	5	mg/m3
Quartz RDX	SiO2	14808-60-7		P3	DM or MC	0,050	mg/m3
	C3H6N6O6 C6H4(OH)2	121-82-4 108-46-3	A	P3	DM or MC MC	1,500	mg/m3
Resorcinol Rhodium (as rh) metal fume and dust	Rh	7440-16-6	A	P2/P3	DM or MC	10	ppm mg/m3
Rotenone (iso)	C23 H22 O6	83-79-4	A	P3	MC	5	mg/m3
Saccarose	C12H22O11	57-50-1	-,	P2/P3	DM or MC	10	mg/m3
Sec-Hexyl acetate	C8 H16 O2	108-84-9	А		MC	50	ppm
Seekay wax	C10H4Cl4	1335-88-2	А	P3	DM or MC	2	mg/m3
Selenium dihydride	H2 Se	7783-07-5			ARI or A AIR	0	ppm
Silica, amorphous (resp. Dust)	SiO2	7631-86-9		P3	MC	6,00	mg/m3
Silica, fused (resp. Dust)	02 Si	60676-86-0		P3	MC	0	mg/m
Silicane	SiH4	7803-62-5		DC	ARI or A AIR	5,000	ppm
Silicon (resp. Dust) Silicon monocarbide	Si SiC	7440-21-3 409-21-2		P3	MC DM or MC	5.000	mg/m3
Silver, metallic	Ag	7440-22-4		P3	MC	0,000	mg/m
Sodium bisulphite	NaHSO3	7631-90-5		P2/P3	MC	5	mg/m
Sodium hydroxide	NaOH	1310-73-2		P3	MC	2.00 (ST)	mg/m3
Sodium metabisulphite	Na2S205	7681-57-4	В	P3	MC	5,00	mg/m3
Sodium monofluoroacetate	FCH2COONa	62-74-8		P3	DM or MC	0	mg/m3
Subtilisins	Bacillus subtilis	1395-21-7			ARI or A AIR	0	mg/m3
Sulfur fluoride	SF6	2551-62-4	BE	P3	MC	1000	ppm
Sulfurous oxychloride	SOCI2	7719-09-7	В	P3	MC	1.00 (ST)	ppm
Sulphur diaxide	S02	7446-09-5	E		MC	2	ppm
Sulphur pentafluoride	S2F10 SF4	5714-22-7 7783-60-0	В	P3	MC ARI or A AIR	0,01	ppm
Sulphur tetrafluoride	S02F2	2699-79-8	BE		MC MC		ppm
Sulphuryl difluoride Sym-dichloroethylene	CICH=CHCI	540-59-0	450 AX		MC	5 200,00	ppm
Tantalum	Ta	7440-25-7	-AA	P3	MC	5	mg/m3
TCP	(CH3C6H40)3P0	78-30-8	A	P3	DM or MC	0	mg/m3
TDI	CH3C6H3(NCO)2	584-84-9	A2B2	P3	MC	VLE=0,01	-
TEA	(C2H5)3N	121-44-8			MC	10,00	ppm
Tedp	[(CH3CH20)2PS]20	3689-24-5	ABE	P3	MC	0	mg/m3
Tellurium & compounds	Te	13494-80-9		P2/P3	DM or MC	0	mg/m3
Tellurium fluoride	TeF6	7783-80-4			ARI or A AIR	0	ppm
Tepp (iso)	[(CH3CH20)2P0]20	107-49-3	А	P3	MC	0	mg/m3
Tert-Butyl ester of acetic acid	CH3C00C(CH3)3	540-88-5	A		DM or MC	200	ppm
Tetrachloroethylene	CI2C=CCI2	127-18-4	A		MC	50,00	ppm
Tetraethyl silicate	(C2H5)4SiO4	78-10-4	A		MC	10	ppm
Tetramethyl silicate Tetramethyl succinodinitrile	(CH30)4Si (CH3)2C(CN)C(CN)(CH3)2	681-84-5 3333-52-6	A	P3	MC DM or MC	1	ppm
Thallium, soluble compounds (as tl)	TI	7440-28-0	L	P3	MC	0	mg/m
THF	C4H80	109-99-9	А		MC	200	ppm
Thio-4,4' bis (tert-butyl-6m-crésol)	[CH3(OH)C6H2C(CH3)3]2S	96-69-5		P3	DM or MC	5,000	mg/m3
Fhiophenol	C6H5SH	108-98-5	Α		MC	0	ppm
Thiram (iso)	C6H12N2S4	137-26-8	А	Р	MC	5	mg/m:
Tin compounds, inorganic, except snh4 (as sn)	Sn	7440-31-5		P3	MC	2	mg/m3
Titanium peroxide	TiO2	13463-67-7		P3	MC	4	mg/m:
FMA Follows	(CH3)3N	75-50-3	K		MC MC	100.00	ppm
Toluene Fributyl ester of phosphoric acid	C6H5CH3 (CH3[CH2]30)3P0	108-88-3 126-73-8	A	P3	MC MC	100,00 2,50	ppm mg/m:
Tributyl ester of phosphoric acid Trichloroethanoic acid	CCI3COOH	76-03-9	В	P3	MC MC	2,50	mg/m:
Trichlorohydrin	CH2CICHCICH2CI	96-18-4	A		MC	10,00	ppm
Tricyclohexyltin hydroxide	(C6H11)3SnOH	13121-70-5	A	P3	MC	5,00	mg/m
Triglycidyl isocyanurate (tgic)	C12 H15 N3 06	2451-62-9	AB	P3	DM or MC	VLE	mg/m
Triiodomethane	CHI3	75-47-8	А		MC	0,60	ppm
Trilene	CICH=CCI2	79-01-6	А		MC	75,00	ppm
Trimethyl carbinol	(CH3)3COH	75-65-0	A		MC	100	ppm
Trinitrotoluol	CH3C6H2(NO2)3	118-96-7	А	P3	MC	1	mg/m
Tungsten & compounds (as w) (soluble)	W C10 LI16 (oppose)	7440-33-7	,	P3	MC	1 100	mg/m
Turpentine	C10 H16 (approx)	8006-64-2	А	DO	MC	100	ppm
Uranium compounds, natural, soluble (as u)	U CH2=CH00CCH3	7440-61-1 108-05-4	A	P3	MC MC	0 VLE =4	mg/m:
VDC	CH2=CH0UCCH3	75-35-4	AX	P3	MC	VLE =4	ppm
Warfarin (iso)	C19H16O4	81-81-2	- ^^	P2/P3	DM or MC	0	mg/m
White spirit	n/a	8052-41-3	A	2.0	MC	350,00	mg/m
Xylene (all isomers)	C8H10	1330-20-7	A		MC	100	ppm
Y- BHC (Iso) Yttrium	C6H6Cl6 Y	58-89-9 7440-65-5	В	P3 P3	MC MC	1	mg/m3 mg/m3
Zinc chloride, fume	ZnCl2	7646-85-7		P3	MC	1	mg/m
	Zn(C18H3502)2	557-05-1	1	P3	MC	5,00	mg/m
Zinc distearate (resp. Dust) Zinc oxide fume	Zn0	1314-13-2		P3	DM or MC	5	mg/m

*MC/DM = Overall masks / Half-mask



HAND PROTECTION

HAND MEASURING



THE EUROPEAN STANDARDS

EN420

GENERAL REQUIREMENTS

- **Conform to harmlessness** (pH, chrome VI levels, etc...).
- Conform to the size charts (see chart on below).
- Pass the dexterity test
- Conform to the labelling, information and identification instructions.

SIZES AS PER STANDARD EN420							
	Hand dimer	Minimal					
Glove size	Palm circumference	Length	glove length				
6	152	160	220				
7	178	171	230				
8	203	182	240				
9	229	192	250				
10	254	204	260				
11	279	215	270				

> STANDARDIZED LABELING/IDENTIFICATION

All our products meet the requirements in directive 89/686/CEE. Each is clearly identified by a standardized label, on which you will see:

- our brand logo;
- the product reference;
- the size ;
- an information tag indicating that instructions are available for the product :
- the standardization pictogram(s) with their performance ratings.

And of course the data sheet for the product and the statement of compliance are available by simple request and on line 24 hours/day on our Web site: **www.deltaplus.eu**



EN388

MECHANICAL RISKS

The EN388 standard applies to all types of protective gloves with respect to physical and mechanical aggression from abrasion, cutting from slicing, perforation and tearing.

PERFORMANCE LEVELS

REQUIREMENTS

1 to 4 1 to 5 1 to 4 1 to 4

RESISTANCE TO PERFORATION

Force required to pierce the sample with a standardized punch.

RESISTANCE TO TEARING

Maximum force required to tear the sample.

RESISTANCE TO CUTTING WITH A BLADE Number of cycles required to cut the sample at constant speed.

ABRASION RESISTANCE

Number of cycles required to damage the sample at constant speed.

TEST	LEVEL 1	LEVEL 2	LEVEL 3	LEVEL 4	LEVEL 5
ABRASION RESISTANCE (number of cycles)	100	500	2 000	8 000	-
BLADE CUT RESISTANCE (index)	1.2	2.5	5.0	10.0	20
TEAR RESISTANCE (N)	10	25	50	75	-
PUNCTURE RESISTANCE (N)	20	60	100	150	



EN511

▶ COLD RISKS

The EN511 standard defines the requirements and test methods for cold protection gloves from cold transmitted by convection or conduction down to -30°C. This cold can be from climatic conditions or industrial activity.

PERFORMANCE LEVELS REQUIREMENTS

1 to 4 1 to 4 1 to 1

IMPERMEABILITY TO WATER

— RESISTANCE TO CONTACT COLD

RESISTANCE TO CONVECTIVE COLD



HAND PROTECTION



EN407

▶ HEAT AND FIRE RISK

The EN407 standard specifies the test methods, the general requirements, the thermal performance and the labelling of gloves to protect from heat and fire.

It applies to all gloves which must protect hands from heat and/or flames in any one or several of the following forms: fire, contact heat, convective heat, radiating heat, small spray of molten metal or large spray of melting metal.

PERFORMANCE LEVELS

REQUIREMENTS

1 to 4 1 to 4 1 to 4 1 to 4 1 to 4 1 to 4

RESISTANCE TO LARGE MELTING METAL SPRAY Amount of spray required to cause damage.

RESISTANCE TO SMALL MELTING METAL SPRAY

Amount of spray required to raise the glove to a certain temperature.

RESISTANCE TO RADIATING HEAT Time required to raise to a given temperature level.

RESISTANCE TO CONVECTIVE HEAT
Time during which the glove is able to delay the
transfer of the heat of a flame.

RESISTANCE TO CONTACT HEAT

Temperature (within the range of 100°C to 500°C) at which the person wearing the gloves will not feel any pain (for a period of at least 15 seconds).

RESISTANCE TO FLAMMABILITY

Time during which the material remains lighted and continues to be consumed after the ignition source has been eliminated.

PERFORMANCE Level	CONTACT TEMPERATURE °C	THRESHOLD TIME (second)
1	100°C	≥15 s
2	250°C	≥15 s
3	350°C	≥15 s
4	500°C	≥15 s

Requirements and test methods for gloves used for manual welding of metals, for cutting and related techniques. Welder gloves are ranked in two types: B when great dexterity is required, and A for other welding processes.

Standard EN374-1, protective gloves against chemicals and micro-organisms, specifies the performance requirements required for gloves for protecting users against chemical products and/or micro-organisms and defines the terms to be used:

- Penetration (tested as per standard EN374-2):
 Diffusion, at a non molecular scale, of a chemical product and/or micro-organism through the porosities, seams, micro-holes or other imperfections present in the material of the protective glove.
- Permeation (tested as per standard EN374-3):
 Process by which a chemical product diffuses through the material of a protective glove, at the molecular scale.

A glove is considered resistant to chemical products if it obtains a performance index to permeation at least equal to 2 for three test chemical products included in the following list of chemical products:

CODE LETTER	CHEMICAL PRODUCT	N° CAS
А	Methanol	67-56-1
В	Acetone	67-64-1
С	Acetonitrile	75-05-8
D	Dichloromethane	75-09-2
Е	Carbon disulfide	75-15-0
F	Toluene	108-88-3
G	Diethylamine	109-89-7
Н	Tetrahydrofurane	109-99-9
I	Ethyl acetate	141-78-6
J	n-Heptane	142-82-5
K	Caustic soda 40 % (NaOH or sodium hydroxide)	310-73-2
L	Sulphuric acid 96 %	7664-93-9"

PASSAGE TIME MEASURED (MN)	PERFORMANCE INDEX TO PERMEATION
> 10 mn	1
> 30 mn	2
> 60 mn	3
> 120 mn	4
> 240 mn	5
> 480 mn	6



The glove will then carry the following pictogram:

Failing compliance with this requirement.

the glove will carry the following pictogram:



Examples of application:

The field of use is decisive, as depending on the case, the glove must only be water and airtight, resistant to micro-organisms, sealed against splashes of low concentrate chemical products, resistant to low concentrate chemical products or against chemical products. It is therefore highly important to consult the recommended fields of use.

			EXAMPLES OF USES APPLICATIONS	MARKINGS	CATEGORIES AS PER 89/686/CEE
			Waterproof glove for very frequent and prolonged use (dish washing gloves)	None	CAT I For Minor Risks
EMENTS		EN374-1 EN374-2	Glove against micro-organisms (bacteria, fungi), air and water proof		CAT II For Intermediary Risks
EN374-1 GENERAL REQUIREMENTS	TEST METHODS	EN374-1 EN374-2 EN374-3	Glove offering low pro- tection against chemical products (occasional contact), air and water proof	[]	CAT III For irreversible Risks
EN374-1		EN374-1 EN374-2 EN374-3	Glove against chemical products (direct and prolonged contact), air and water proof		CAT III For irreversible Risks

ISO2859 (DISPOSABLE GLOVES)

Determine the acceptable quality level (AQL): AQL 1.5 for instance



FOOD COMPATIBILITY



> FOOD COMPATIBILITY IS GOVERNED BY:

Regulation (EC) N° 1935/2004 of the European Parliament and of the Council of 27th October 2004 on materials and articles intended to come into contact with foodstuffs.

Materials and articles must be manufactured in compliance with good manufacturing practice so that, under normal or foreseeable conditions of use, they do not transfer their constituents to food in quantities which could:

- endanger human health;
- bring about an unacceptable change in the composition of the food or a deterioration in the organoleptic characteristics thereof.

Food contact of plastic materials is governed by Regulation (EU) No 10/2011 of the Commission of 14 January 2011 repealing the directive 2002/72/EC.

PVC/Vinyl or even Latex/Nitrile gloves (unless local legislation exists) are directly subject to this directive.

It defines:

- positives lists of authorized constituents;
- the purity criteria applicable to some of these constituents;
- special migration limits in foodstuff s for certain constituents :
- maximum residual quantities of some constituents in the material;
- an overall migration limit in foods (10 mg/dm2 of material or 60 mg/kg of food).

Directive 85/572/EC provides the list of stimulants to be used for testing migration of constituents of plastic materials and articles intended to come into contact with foodstuffs:

- Aqueous foods (pH > 4.5): Stimulant A :
- Acid food (pH <= 4.5): Stimulant B;
- Alcoholic foods: Stimulant C;
- Fatty foods: Stimulant D.
- Dry foods: Stimulant E.



HAND PROTECTION

CHEMICAL RESISTANCE TABLE

					_
	St	la J	Neoprene	<u>e</u>	PVC viny
	n°CAS	Natural Iatex	Neop	Nitrile	PVC
20% nitric acid	631-61-8	***	***	***	***
30% and 5% hydrochloric acid	/ / / / / / / / / / / / / / / / / / / /		*	*	*
30% formaldehyde 30% hydrofluoric acid	123-86-4 62-54-4	***	***	***	***
50% acetic anhydride	141-78-6		*	*	*
85% lactic acid	127-08-2	***	***	***	***
85% triethanolamine 90% formic acid	67-64-1 64-19-7	***	**	**	*
Acetaldehyde	04-19-7	***	***	***	***
Acetone	10043-35-3	***	***	***	***
Alcoholic beverages	10035-10-6	***	*	*	*
Ammonium acetate Ammonium carbonate	7647-01-0 7738-94-5	***	***	***	**
Ammonium caluoride	77-92-9	***	***	***	***
Amyl acetate	7664-39-3	**	***	***	**
Amyl alcohol Aniline	64-18-6	*	**	*	***
Animal fats	7697-37-2	**	**	*	*
Asphalt	112-80-1	*	***	***	*
Beet-root	144-62-7	***	***	***	***
Benzaldehyde	7004.00.0	*	**	**	**
Benzene Benzyl alcohol	7664-38-2 57-11-4	***	***	***	***
Bichromate of potash	7664-93-9		*		**
Bleach	/	***	***	***	***
Borax Deale alle fleelsheadt	74 44 0	***	***	***	***
Brake oils (lockheed) Bromides	71-41-0 100-51-6	***	***	***	***
Butter	71-36-3	***	***	***	***
Butyl acetate	64-17-5	***	***	***	***
Butyl alcohol (or n-butanol)	78-83-1	***	***	***	***
Calcium acetate Calcium chloride	67-56-1 111-87-5	***	***	***	***
Calcium fluophosphate	75-07-0	***	***	*	_ ^
Calcium hydrate	100-52-7			*	
Calcium nitrate	50-00-0	***	***	***	***
Carbolic acid Carbon tetrachloride	1336-21-6 62-53-3	***	***	***	***
Castor oil	02-03-0	**	*	***	
Chlorinated lime	71-43-2			*	
Chlorine	/		***	***	*
Chloroacetone Chloroform	298-14-6	***	***	***	***
Chromic acid	144-55-8	***	***	***	***
Citric acid	7778-50-9	*	***	***	***
Concentrated ammonia	7631-90-5	***	***	***	***
Concentrated boric acid Concentrated laundry potash	1	***	***	***	***
Concentrated laundry soda	1	***	***	***	***
Concentrated sulphuric acid	/	***	***	***	
Creosote	10361-29-2	***	***	***	***
Cresol Crystallisable acetic acid	497-19-8 584-08-7	***	***	***	***
Cutting oils	/	***	***	***	***
Cyclohexane	1	***	***	***	***
Cyclohexanol	7782-50-5		***	***	***
Cyclohexanon Dead lime	67-66-3	***	***	**	
Diacetone alcohol	12125-02-9	***	***	***	***
Dibutyl ether	10043-52-4	***	***	***	***
Dibutyl phtalate	75-09-2	*	***	***	***
Diehanolamine Diesel oils	75-09-2 7718-54-9	***	***	***	***
Diluted sulfphuric acid (battery)	7447-40-7	***	***	***	***
Dioctylphtalate	7647-14-5	***	***	***	***
Dyes (hair dyes) Ethyl acetate	8001-58-9 1319-77-3	*	***	***	***
Ethyl alcohol (or ethanol)	151-50-8	***	***	***	***
Ethylamine	110-82-7		*	**	
Ethylaniline	108-93-0	***	***	***	***
Ethylene dichloride	108-94-1	***	***	***	***
Ethylene glycol Fertilisers	/	***	***	***	***
Fish and shellfish	,	**	***	**	**
Fixing agents	/	***	***		*
Fluorides Formaldehyde)	142-96-1 84-74-2	**	*	***	
Fuel oil	107-06-2	××	*	***	
Fuels	78-87-5			*	
Furol (furfural or furaldehyde)	111-42-2	***	***	***	***
Gas-oil Gasoline	117-81-7	**	***	***	***
Glycerin	/	*	***	***	
Glyceropthalic paint	/		**	*	*
Glycols Usic blooching agents	/	***	***	***	***
Hair bleaching agents Hair-curling products	/		*	***	*
Hexane	/		**	***	
Household detergents	1	*	***	***	*
Hydraulic fluids (esters)	75-04-7	*	*	***	*
Hydraulic oils (petrol) Hydrobromic acid	107-21-1	***	***	***	***
Hydrogen peroxide	/	***	***	***	***

Not recommended Average * Good ** Very good ***

This table provides only general information. Be careful! Glove resistance is influenced by other factors such as temperature, chemical product concentration, thickness, immersion time, and others. For specific use conditions, we recommend testing the glove prior to

For specific use conditions, we recommend testing the glove prior to use.

	n°CAS	Natural Iatex	Neoprene	Nitrile	PVC vinyl
Isobutyl alcohol		***	***	***	*
Isobutyl ketone	1	***	***	***	***
Kerosene Lard oil	50-00-0	***	***	***	***
Linseed oil	50-00-0	***	*	***	*
Lubricating oils	98-01-1	***	**		
Magnesia Methyl gestate	56-81-5	***	***	***	***
Methyl acetate Methyl alcohol (or methanol)	107-21-1	***	***	***	***
Methyl ethyl ketone	/	*	***	***	
Methyl isobutyl ketone	/		*	***	*
Methyl salicylate Methylamine	110-54-3		*	***	*
Methylaniline	1		***	***	***
Methylcyclopentane	1		*	***	*
Methylene chloride Methylformiate	/	*	***	***	*
Milk and dairy products	/		*	***	*
Mineral greases	/		***	***	*
Mono ethanol amine	1		***	***	*
N-butylamine Naphta	/		***	***	*
Naphtalene	1		*	***	*
Nickel chloride	/		*	***	*
Nitrate of ammonium	1		***	***	*
Nitrate of potassium Nitrobenzene	/		***	***	*
Nitrohydrochloric acid	1305-62-0	***	***	***	***
Nitropropane	7778-54-3	***	***	***	***
Non-alcoholic beverages Octyl alcohol	7681-52-9	***	***	***	***
Octyl aconol Oleic acid	/	×××	***	***	*
Olive oil	/	*	***	***	
Oxalic acid	/	***	***	***	***
Paraffin oil Peanut oil	1309-48-4	***	***	***	***
Perfumes and essences	79-20-9	*	***	*	*
Petroleum ether	74-89-5	***	**	***	***
Petroleum products	100-61-8	*	*	***	***
Petroleum spirit Phenyl chloride	96-37-7	***	*	***	*
Phosphates of calcium	1	*	***	*	*
Phosphoric acid	/	**	*		
Polyester resins Potash flakes	119-36-8 141-43-5	***	***	***	***
Potassium acetate	108-90-7	***	*	*	***
Potassium bicarbonate	1		*	***	*
Potassium carbonate	91-20-3		*	**	*
Potassium chloride Potassium cyanide	109-73-9 6484-52-2	***	***	***	***
Potassium manganate	10124-37-5	***	***	***	***
Potassium phosphates	7757-79-1	***	***	***	***
Potassium sulphate Poultry	7631-99-4 98-95-3	***	***	***	***
Propylene dichloride	50-50-5	***	**	*	
Quick lime	1	***	***	***	***
Shampoos	/		*	***	*
Silicates Soda flakes	127-18-4	***	***	***	***
Sodium bicarbonate	7722-64-7	***	***	***	***
Sodium bisulphite	10103-46-5	***	***	***	***
Sodium carbonate Sodium chloride	/	***	***	***	***
Sodium chlorite	1	*	***	***	*
Sodium nitrate	1	***	***	**	***
Sodium phosphates	/	***	***	**	***
Sodium sulphate Soybean oil	1	***	***	***	***
Stannic chloride	1		*	**	*
Stearic acid	/	***	***	***	***
Styrene Sulphites, bisulphites, hyposulphites	/	***	***	***	***
Sulphines, disdiplines, hyposulphines Sulphuric ether (pharmacy)	1	***	***	*	*
Fartaric acid	100-42-5		*	*	*
Tetrachloroethylene	7778-80-5	***	***	***	***
THF = tetrahydrofurane Toluen	7757-82-6 7733-02-0	***	***	***	***
Tributyl phosphate	// /	***	***	***	***
Trichlorethylene	1	***	***	***	***
Tricresyl phosphate	56-23-5		*	**	*
Trinitrobenzene Trinitrotoluol	109-99-9 108-88-3	**	*	**	*
Triphenyl phosphate	126-73-8	*	**	**	*
Turbine oils	79-01-6		*	*	
Tumipseed oil	1330-78-5	***	**	***	**
Turpentine Vinegar and condiments	102-71-6	***	***	***	***
Washing powders	1		*	**	*
Water paint	115-86-6	*	***	***	*
Weed killers	/	***	***	***	**
Wood turpentine Xylene	/	*	***	***	*
Xylophene	1		*	**	

BODY PROTECTION

INTERNATIONAL MAINTENANCE CODE FOR ARTICLES

	TEXTILE
\times	No treatment.
	Moderate treatment.
-	Very light treatment.
	WASHING
40	Maximum temperature 40°C. Normal mechanical treatment. Normal temperature rinsing. Normal spinning.
40	Maximum temperature 40°C. Reduced mechanical treatment. Rinse at gradually decreasing temperature. Reduced spinning.
Kunt	Wash by hand. No machine washing. Maximum temperature 40°C. Treat with care.
×	Do not wash. Treat with care when wet.
	DRYING
\odot	Can be dried in rotating drum dryer. Normal program.
\odot	Can be dried in rotating drum dryer. Moderate, low temperature program
X	Do not dry in rotating drum dryer.
	CHLORINATION
	Chlorination (chlorine bleach).
CI	Chlorination possible solely in cold, diluted solution.
×	No chlorination.
	IRONING
<u></u>	Iron at the maximum iron sole plate temperature of 200°C.
•••	Iron at the maximum iron sole plate temperature of 150°C.
<u></u>	Iron at maximum iron sole plate temperature of 110°C. Steam treatment presents risks.
X	Do not iron. Steam treatment is forbidden.
	DRY-CLEANING
0	Dry cleaning. The circle stands for dry-cleaning for textile articles (Leather and fur articles are excluded). It contains information on the various dry cleaning treatments.
YOY	Day algoring prohibited

Dry-cleaning prohibited.





BODY PROTECTION

CHEMICAL PROTECTIVE CLOTHING



EN14126 ▶ **PROTECTIVE CLOTHING AGAINST INFECTIVE AGENTS**

This standard specifies the requirements and test methods concerning reusable protective clothing for limited use providing protection against infective agents.

Associated with standards for protective clothing against chemical products, the letter B is added after the garment type.

Examples: TYPE 6-B / TYPE 5-B / TYPE 4-B / TYPE 3-B



TYPE 6

EN13034 ▶ **PROTECTIVE CLOTHING AGAINST LIQUID CHEMICALS**

Requirements for chemical protection clothing offering limited performance against liquid chemical products (type 6 equipment), including clothing for partial body protection (Type PB [6]).

This standard sets out the minimum requirements for limited use and reusable limited performance chemical protective clothing. Limited use chemical protective clothing is intended for use in cases of a potential exposure to light sprays, liquid aerosols or low-pressure, low-volume splashes, against which a complete liquid permeation barrier (at the molecular level) is not required.



TYPE 5

EN13982-1 ▶ **PROTECTIVE CLOTHING FOR USE AGAINST SOLID PARTICLES**

Performance requirements for protective clothing against chemical products offering full body protection against air-borne solid particulates (type 5 clothing).

This standard sets out the minimum requirements for chemical protection clothing resisting penetration of solid particulates suspended in air (type 5). This clothing offers full body protection, including the torso, arms and legs, such as one or two-piece coveralls, with or without hood or face-shield, with or without foot protection.



EN14605 TYPE 4 TYPE 3

▶ PROTECTIVE CLOTHING AGAINST LIQUID CHEMICALS

Requirements for chemical protection clothing with liquid-tight (type 3) or spray-tight (type 4) connections, including items providing only partial body protection (types PB [3] and PB [4]).

This standard sets out the minimum requirements for the following types of limited use and re-useable chemical protective clothing:

- Clothing protecting the full body with liquid-tight connections between the various clothing parts (Type 3: liquid-tight clothing);

- Clothing protecting the full body with spray-tight connections between the various clothing parts (Type 4: spray-tight clothing);

Note: These standards were formerly entitled EN1512 (Type 4) and EN1511 (Type 3).

STANDARD	TYPE CHEMICAL	PROTECTION
EN13034	6	Against splashes
EN13982-1	5	Against dust (asbestos)
EN14605	4	Against mists
EN14605	3	Against sprays

EXAMPLES OF APPLICATIONS					
Applications	Risks	Level of protection			
Work Maintenance	Fouling	Category I / Non PPE			
Industrial cleaning	Exposure to hazardous chemical substances and particles	Type 6 Type 5			
Asbestos abatement / removal (dust > 1 micron)	Contact with particles or fibres	Type 5			
Agriculture and horticulture (Handling of herbicides / pesticides / fungicides / fertilizers)	Contact with harmful elements	Type 4			
Paint spraying (Solvents)	Contact with low-concentrate aerosols	Type 4			
Paint spraying (Preparation / Mixing)	Contact with high concentrate aerosols	Type 3			
Laboratories / Chemical Industries	Projection of chemical products	Type 3			
Emergency / Rescue Personnel	Bacteriological contamination	Type 4-B Type 3-B			

	TESTS								
General	Tests &	Level of protection							
performance	Specific performance	1a	1b	1c	2	3ª	4 ^a	5	6 ª
	Internal pressure	Χ	Χ	Χ	-	-	-	-	-
Performance	Leak to interior	-	Xp	Х	Χ	-	-	-	-
requirements for the whole	Penetration by a jet of liquid	-	-	-	-	Х	-	1	-
garment	Penetration by a spray	-	-	-	-	Х	Х	-	-
	Against solid particles	-	-	-	-	-	-	Х	-
	Penetration by a spray	-	-	-	-	-	-	-	Х
5 (Abrasion / Tearing / Perforation / Seams	Х	Χ	Χ	Χ	Х	Х	Х	Х
Performance	Resistance to tensile strength	Х	Χ	Χ	Χ	Χ	Χ	-	Χ
requirements for	Resistance to flame	Χ	Χ	Χ	Χ	Χ	Χ	Χ	Χ
the constituent materials of the	Resistance to cracking by bending	Х	Х	Х	Х	Х	Х	Х	-
garment	Resistance to cracking by bending at -30°C	Х	Х	Χ	Х	Х	Х	1	-
	Resistance to permeation according to:	Х	Х	Х	Х	Х	Х	-	-
	Resistance to penetration by liquids	-	-	-	-	-	-	1	Х
	Impermeability to liquids (repulsion)	-	-	-	-	-	-	-	Х

- a When the protection equipment only protects certain parts of the body (torso, arms, legs), only the performance requirements for the constituent materials of the garment are required (type 6, 4 and 3).
- b Applicable for suits whose respiratory mask is separate and removable.

HEAT PROTECTIVE CLOTHING

TASOUB



EN11611

A1 Class 2

ROTECTION USED IN WELDING AND ALLIED **PROCESSES**

This standard sets out the performance requirements for protective clothing for use by operators in welding and allied processes with comparable risks.

This type of protective clothing is intended to protect the wearer against molten metal splash, short contact with flame and UV radiation. It is intended to be worn at ambient temperature, continuously for up to 8 hours.

protection against low risks during welding techniques and situations producing Class 1 fewer projections and low radiant heat protection against higher risks during welding techniques and situations producing Class 2 more projections and a higher radiant heat.

MAICO EN14116



Indice: 1 / 2 or 3 Nh : Number of washes TO: Service temperature I: Industrial wash

▶ PROTECTION AGAINST HEAT AND FLAME

This standard sets out the performance requirements for limited flame spread materials and material assemblies used in protective clothing. Limited flame spread materials and material assemblies are used to make protective clothing in order to reduce the risks of flammability of the garment and the dangers it may cause. They are suitable for protection against accidental contact with small igniting flames, in conditions

with no significant heat danger.

MATERIALS	MATERIALS WHICH DO NOT SPREAD FLAME
index 1	but which may form a hole on contact with a flame
index 2	and do not form a hole on contact with a flame
index 3	…and do not form a hole on contact with a flame. They also give only limited after-flame (≤ 2s)

TONC3 EN11612



A1 B1 C1 D1 E1 X

MAICO EN531



AB1 C1 XX

▶ PROTECTION FOR WORKERS EXPOSED TO HEAT

Protection against heat and flame.

These standards specify the performance requirements of materials and protective clothing against heat and flames. They apply to clothing made of soft material, designed to protect the human body except the hands against heat and/ or flame. Tested are:

TESTS	CODES	PERFORMANCES
Limited flame spread	А	A1 and/ or A2
Convective heat	В	B1 to B3
Radiant heat	С	C1 to C4
Molten aluminium splash	D	D1 to D3
Molten metal splash	E	E1 to E3
Contact heat	F	F1 to F3



BODY PROTECTION

TECHNICAL PROTECTIVE CLOTHING

EN340 - EN ISO 13688 ▶ GENERAL REQUIREMENTS

Reference standard, not for use alone, but only in association with another standard containing the protection performance requirements.

This standard specifies general performance requirements for ergonomics, innocuousness, size designation, durability, ageing, compatibility and marking of protective clothing and the information to be supplied by the manufacturer with the protective clothing.



EN1149-5 ► PROTECTIVE CLOTHING TO DISSIPATE STATIC ELECTRICITY

This European Standard specifies requirements for materials and the design of protective electrostatic dissipation clothing used in conjunction with a grounded system in order to prevent incendiary discharges. WARNING: These requirements may be insufficient in oxygen enriched flammable environments. This standard is not applicable for protection against mains voltages.

The control of undesirable static electricity on the person is often necessary.

The electrostatic potential may, indeed, have serious consequences on the charged individual, because it can be high enough to cause dangerous sparks.

After a risk assessment, the wearing of protective electrical dissipation clothing may be necessary. The use of clothing certified according to EN1149-5 is then adapted.

The ATEX Directive 1999/92/EC, in its Annex II-A-2.3, requests that workers be equipped with work clothes made of materials that do not produce electrostatic discharges that can ignite explosive environments.

The electrostatic potential can also affect equipment sensitive to electric discharge. And antistatic clothing are often used on electronic manufacturing sites, assembling semiconductors for example. Finally, they are used on sites with controlled atmospheres such as automotive paint workshops, to avoid the emission of particles that may be deposited on the body paint.

The antistatic charge dissipation can be provided by a process limiting the build up of charge, or by adding carbon or metal wires. People wearing protective electrostatic charge dissipation clothing must always be grounded with a resistance of less than $10^8\Omega,$ for example, by wearing appropriate footwear such as the safety shoes stated in EN ISO 20345, or by other suitable means.

EN13356 ► VISUAL ACCESSORIES FOR NON PROFESSIONAL USE

This standard specifies optical performance requirements for accessories that are worn, attached to, or carried by individuals and designed for non-professional use. The visualization accessories conforming to this standard are intended to visually indicate the presence of the user when illuminated by vehicle headlights on unlit roads. This standard does not apply to clothing.



EN381

► PROTECTION FOR HAND-HELD CHAINSAWS

This standard specifies the requirements to be used to assess the resistance of protective clothing to cutting by hand-held chainsaws. It is divided into several parts:

EN381-5 Specifies the requirements for leg protectors.

EN381-7 Specifies the requirements for protective gloves.

EN381-9 Specifies the requirements for protective gaiters.

EN381-11 Specifies the requirements for upper body protectors.

The cut tests are conducted using 4 chain speeds:

16 m/s	Class 0
20 m/s	Class 1
24 m/s	Class 2
 28 m/s	Class 3

The protective zone on leg protectors is coded using three letters A, B or C, corresponding to the coverage surface of the cut-proof material (Type A, Type B or Type C).

Marking:





EN1073-2

PROTECTIVE CLOTHING AGAINST RADIOACTIVE CONTAMINATION

This standard specifies the requirements and test methods for non ventilated protective clothing against radioactive contamination in the form of particles. Clothing of this type is designed only to protect the body, the arms and the legs of the wearer, but it may be used with accessories that protect other parts of the wearer's body (for example, boots, gloves, respiratory protective device - APR).

The garments are classified according to their nominal protection factor (ratio between the concentration of test particles in the ambient atmosphere and the concentration of test particles inside the garment), determined in relation to the total inward leakage (ratio between the concentrations of test particles insider the garment and inside the test chamber).

The classes are as follows:

CLASS	NOMINAL PROTECTION FACTOR
3	500
2	50
1	5



EN471 EN ISO 20471

► HIGH VISIBILITY CLOTHING

This standard specifies the requirements for protective clothing aiming to signal the presence of the wearer visually, so that he may be detected and seen in hazardous situations, in all conditions of daylight, and night under illumination of car headlights.

There are three classes of high-visibility clothing. Each class must have minimum surfaces of visible material constituting the garment; the higher the class, the more visible the garment:

	CLASS 3	CLASS 2	CLASS 1
Background material (Fluorescent)	0.80 m ²	0.50 m ²	0.14 m ²
Retroreflective material (Bands)	0.20 m ²	0.13 m ²	0.10 m ²

Background material:

Yellow, orange/red or red fluorescent material intended to be highly conspicuous.

Retroreflective material:

Classified into 2 levels. The highest level of retroreflection gives the best contrast and visibility of high-visibility clothing seen in darkness, under headlamps.

Marking:

X: Class of high visibility surface (from 1 to 3)

X: Performance level of the retro-reflective material (1 to 2)

STRADA EN471



3.2

EN471

- 3 : Class of high visibility surface (from 1 to 3)
- 2 : Performance level of the retro-reflective material (1 to 2)

GILP2 EN ISO 20471



Max. 25x

EN ISO 20471

2 : Class of the visibility surface (1 to 3) Max. 25x: Optional marking, number of maximum washes authorized for the model. On this example: 25 washes maximum (see indication of service temperature on the garment tag).

FOUL WEATHER PROTECTIVE CLOTHING



EN342

► PROTECTIVE CLOTHING AGAINST COLD

This standard specifies the requirements and performance test methods for protective clothing against cold **at temperatures lower than -5°C** (cold store / extreme cold workers).

There are two types of garment:

Garments: covering part of the body, e.g. parka, jacket, coat.

Suits: covering the whole body (trunk + legs), e.g. coveralls, parka & dungarees.



EN14058 ▶ PROTECTIVE CLOTHING AGAINST COOL ENVIRONMENTS

This standard specifies the requirements and performance test methods for protective garments (vests, jackets, coats, trousers) against cool environments.

These garments are for use in moderate low temperatures (-5°C and over) to protect against local body cooling and are not only for outdoor use such as in the construction industry, but may also be used for indoor activities, such as in the food processing industry.

These garments are not always necessarily made of air impermeable or watertight materials. Therefore, in this European standard, these requirements are optional.



EN343

▶ PROTECTIVE CLOTHINGAGAINST RAIN

This standard specifies the requirements and test methods applicable to the materials and seams of protective clothing against foul weather (for example precipitation in the form of rain or snow), fog and ground humidity.

TESTS								
	Code	EN343	EN342	EN14058				
Class of thermal resistance (in m².K/W)	R _{ct}	1	-	X				
Class of water vapour resistance (in (m².Pa)/W)	R _{et}	X	-	-				
Class of air permeability (in mm/s)	AP		X	X (optional)				
Resistance to water penetratio (in Pa)	WP	X	X (optional)	X (optional)				
Resultant effective thermal insulation (in m².K/W) Measured on a moving manikin	cler	_	X	X (optional)				
Effective thermal insulation (in m².K/W) Measured on a stationary manikin	/ _{cle}	-	X (optional)	X (optional)				



BODY PROTECTION

• THERMAL RESISTANCE (Rct) IN M2.K/W:

Measurement of the thermal insulation provided. Divided into 3 classes (from 1 to 3) from the least insulating to the most insulating. The higher the value, the greater the thermal insu-

• WATER VAPOUR RESISTANCE (Ret) IN (M2.PA)/W:

Measures the evaporative resistance, i.e. the product's obstacle to the passage of water vapour, or the barrier it offers to evaporation of transpiration on the surface of the skin. The higher a product's water vapour resistance, the greater this product's barrier to the passage of water vapour: A breathing product has a low water vapour resistance. Divided into 3 classes (from 1 to 3) from the least breathable to the most breathable.

• AIR PERMEABILITY (AP) IN mm/s:

Determines the complex's permeability to air.
Divided into 3 classes (from 1 to 3) from the least airtight to the most airtight.

• RESISTANCE TO WATER PENETRATION (WP) IN PASCAL:

Measurement of the outer material and seams' resistance to water penetration under a water pressure of (980+/-50) Pa/min. Divided into 3 levels (1 to 3) from the least impermeable to the most impermeable.

• RESULTANT EFFECTIVE THERMAL INSULATION:

Measured on moving dummy ($\prime_{\rm cler}$) or on non moving dummy ($\prime_{\rm cle}$). The thermal insulation coefficient, expressed in m².K/W, is used to determine the optimum usage temperature of the garment in relation to the individual's activity and his exposure time.

Thermal insulation is measured with undergarments of type:

- **(B) for ensembles** (Undershirt with long sleeves, long underpants, socks, bootee + thermojacket, thermopants, knitted gloves, balaclava)
- **(R) for garments** (Undershirt with long sleeves, long underpants, socks, bootees, jacket, trousers, shirt, knitted gloves, balaclava)
- ((C) provided by the manufacturer

AMBIENT TEMPERATURE CONDITIONS FOR HEAT BALANCE FOR DIFFERENT LEVELS OF ACTIVITY AND EXPOSURE DURATIONS

	ACTIVITY									
Standard applicable	Insulation m ² .K/W	Very light Stationary standing 75 W/m²		ligh	moving htly W/m²	Wearer m mediu 170 W	ım			
	/ _{cle} -/ _{cler}	8h	1h	8h	1h	8h	1h			
EN14058	0.170	19°C	11°C	11°C	2°C	0°C	-9°C			
EN14058	0.230	15°C	5°C	5°C	-5°C	-8°C	-19°C			
EN342	0.310	11°C	-2°C	-1°C	-15°C	-19°C	-32°C			
EN342	0.390	7°C	-10°C	-8°C	-25°C	-28°C	-45°C			
EN342	0.470	3°C	-17°C	-15°C	-35°C	-38°C	-58°C			
EN342	0.540	-3°C	-25°C	-22°C	-44°C	-49°C	-70°C			
EN342	0.620	-7°C	-32°C	-29°C	-54°C	-60°C	-83°C			

Marking:



EN14058

X : Class of heat resistance, R_{ct}


X : Class of air permeability. AP (Optional)

X: Class of resistance to water penetration

WP (Optional)

 $\boldsymbol{X}:/_{_{\text{cler}}}$ of the garment (Optional)

X: / dof the garment (Optional)



NORDLAND

EN342 0,705 m².K/W (B)


3

Χ

**

EN342

X (undergarment B/C/R) : / cler of the garment X (undergarment B/C/R) : / cle of the garment (Optional)




X : Class of resistance to water penetration WP (Optional)



EN343

 \boldsymbol{X} : Resistance to water penetration, $\boldsymbol{W}\boldsymbol{p}$

X: Water vapour resistance, R_{et}



EN14404 ► KNEE PROTECTION

This European Standard provides the requirements and test methods for protective knee devices used by people that have kneel to carry out their work. This standard does not apply to the knee protection that are medical devices and are designed for sport.

	KNEE PROTECTION
Type 1	Knee protection independent of other product and attached around the leg
Type 2	Plastic foam or other padding inserted in the pockets of trousers or permanently attached to the trousers
Type 3	Devices that are not attached to the body but implemented during the movement of the user. They can be provided for each knee or both knees together
Type 4	Protection of one or both knees, part of devices with additional functions, such as helping to stand or kneel. The knees protection can be worn on the body or independently

FOOT PROTECTION

SAFETY SHOES-BOOTS

STANDARDS

EN ISO 20344

This standard defines the test methods for safety footwear, protective footwear, and occupational shoes.

It may be used only in conjunction with standards EN ISO 20345 and EN ISO 20347, which specify the requirements for the shoes as a function of specific levels of risk involved.

EN ISO 20345 ► SPECIFICATION FOR SAFETY FOOTWEAR FOR THE WORKPLACE

In reference to standard EN ISO 20344, this European standard defines the basic and the additional (optional) requirements for safety footwear for the workplace, marked «S».

The safety shoe is equipped with safety toe caps designed to withstand a maximum impact of 200 joules and crushing up to 15 kN.

EN ISO 20347 ▶ SPECIFICATION FOR OCCUPATIONAL SHOES MARKED «O»

These shoes are different from safety/protective footwear in that they have no protective toe cap for impact and crushing.

EN ISO 61340-4-3

This standard specifies the requirements and tests for electrostatic shoes with specific applications. It describes the test methods used to determine the electrical resistance of shoes used to control the electrostatic potential of the user's workstation.

EN ISO 20349

This standard specifies the requirements and tests for protective shoes against heat risks and molten metal splashes as in foundries or welding.

THE PARTS OF A SHOE





FOOT PROTECTION

	SIZE CORRESPONDANCE TABLE													
Europe	35	36	37	38	39	40	41	42	43	44	45	46	47	48
UK	2	3	4	5	6	6 1/2	7	8	9	10	10 1/2	11	12	13
Cm	23.1	23.7	24,4	25.1	25.7	26.4	27.1	27.8	28.4	29.1	29.7	30.3	31.0	31.6

• SB OR S1 TO S5 OR SBH (SAFETY FOOTWEAR) • OB OR O1 TO O5 OR OBH (OCCUPATIONAL SHOES)				
CLASS 1 or 2	EN ISO 20345	EN ISO 20347		
ALL MATERIALS	SB: basic properties	OB: basic properties		
CLASS 1 Leather shoes and other materials, except rubber or polymer shoes	\$1 : basic properties plus: - closed back - anti-static - energy absorbing heel - outsole resistance against hydrocarbons	01 : basic properties plus: - closed back - hydrocarbon-resistant sole - anti-static - energy absorbing heel		
	S2: the same as S1 plus: - waterproof	02 : the same as 01 plus: - waterproof		
	S3 : the same as S2 plus: - puncture resistant sole - studded sole	03 : the same as 02 plus: - puncture resistant sole - studded sole		
CLASS 2 All rubber shoes (fully cured) or all polymer (fully moulded)	S4: basic properties plus: - closed back - anti-static - energy absorbing heel - outsole resistance against hydrocarbons	04 : basic properties plus: - anti-static - energy absorbing heel		
	S5 : the same as S4 plus: - puncture resistant sole - studded sole	05 : the same as 04 plus: - puncture resistant sole - studded sole		
HYBRID SHOES Rubber foot (fully cured) or all polymer (fully moulded) / Top leather upper and other materials	SBH: properties specific to hybrid safety shoess	OBH : properties specific to hybrid work shoes		

SYMBOLS FOR INDIVIDUAL SPECIFICATIONS En ISO 20345					
	Puncture resistant sole	Р			
	Electrical properties :				
	Conductive shoe	С			
	Antistatic shoe	А			
	Insulating shoe	See EN50321			
	Resistance to aggressive environments :				
Whole shoe	Heat-insulated sole	HI			
	Sole insulated against cold	CI			
	Energy absorbing heel	Е			
	Water-resistant of the whole shoe (waterproof shoes in leather and other materials, class 1)	WR			
	Metatarsal impact protection	M			
	Ankle protection	AN			
	Cut-resistant upper	CR			
Upper	Resistance of the rod penetration and water absorption (shoes in leather and other materials, class 1)	WRU			
Outoolo	Contact-heat resistant outsole	HR0			
Outsole	Oil-resistant outsole	FO			

SYMBOLS FOR INDIVIDUAL SPECIFICATIONS En ISO 20349						
Floor types	Symbols					
Resistance to molten metal splashes, with use of aluminum as molten metal during the test.	AL					
Resistance to molten metal splashes, with use of cast-iron as molten metal during the test.	FE					
Insulation of the sole against the heat. 150°C sandbox test, 30 minutes of exposure (HI-1).	HI-1					
250°C sandbox test, 40 minutes of exposure (HI-3).	HI-3					
WG indicates that the footwear complies with the requirements defined for welding footwear.	WG					

RESISTANCE TO SLIPPING				
Floor types	Symbols			
Hard industrial floors, for indoor use (such as food industry tiled flooring)	SRA			
Hard industrial type floors for indoor or outdoor uses (paint or resin type flooring in industry)	SRB			
All types of hard floors for multiple uses indoors or outdoors	SRC			

THE CORRECT SELECTION OF FALL ARREST PRODUCTS GIVES PERFECT SAFETY

Fall arrest equipment includes different products which have to be adapted for each risk to ensure the necessary protection. These products (full body harness, fall arrester on anchorage line, work positioning systems, energy absorbers, self-retractable fall arrester, accessories) are governed by the Directive 89/686/EEC and the European standards on Personal Protective Equipment (PPE).

THE HARMONIZED EUROPEAN STANDARDS

All protective equipment against falls from a height are submit to European standards. You will find, below, a summed up presentation of every standard.

GENERAL STANDARDS

EN363 ► FALL ARREST EQUIPMENT

Set of personal protective equipment against falls from height, linked to one another and intended to stop a fall. A fall arrest equipment must contain at least a full body harness and a fall arrest equipment.

EN364 ► TEST METHOD

Describes the different test methods of the various PPE against falls from height, as well as the test equipment.

EN365 ► GENERAL REQUIREMENTS FOR THE INSTRUCTIONS FOR USE AND THE MARKING

Description of the marking that must figure on the PPE against falls from height and of the information which must appear on the instructions for use.

SPECIFIC STANDARDS

EN361 ▶ **FULL BODY HARNESS**

Body securing device intended to stop falls. The full body harness can be made of straps, buckles and other elements; set and adjusted in a right way on the body of an individual to secure him during a fall and afterwards.

EN353-1 + CNB VG11.073 ► MOBILE FALL ARRESTER ON RIGID ANCHORAGE LINE

Equipment consisting of a mobile fall arrester with self-locking, integral with its rigid anchorage line (rail, cable...). An energy reducer can be built-in on the equipment.

EN353-2 ► MOBILE FALL ARRESTER ON FLEXIBLE ANCHORAGE LINE

Equipment consisting of a mobile fall arrester with self-locking, integral with its flexible anchorage line (rope, cable...). An energy reducer (absorber) can be built-in in the equipment.

EN355 ► ENERGY ABSORBER

Component of a fall arrest equipment, which guarantees the stop of a fall from a height in safety by reducing the impact of the shock. **WARNING:** If we associate a lanyard energy absorber, the total length of the entire device must not exceed 2 m.

EN360 ► SELF-RETRACTABLE FALL

Fall arrester with self- locking device and a self-retractable system for the lanyard. An energy reducer (absorber) can be built-in in the equipment.

EN362 ► CONNECTOR

Connection element or equipment component. A connector can be karabiner or a snap hook.

EN354 ► LANYARDS

Connection elements or equipment component. A lanyard can be in rope made of synthetic fibres, in metallic rope, in strap or in chain. Maximum length: 2m. **CAUTION:** A lanyard without energy absorber must not be used as a fall arrest equipment.

EN358 ▶ WORK POSITIONING SYSTEM

A work positioning system consists of components (work positioning belt and lanyard) linked to one another to form a complete equipment.

EN813 SEAT HARNESSES

EN1891 SHEATHED BRAIDED ROPE WITH A LOW COEFFICIENT OF ELONGATION (STATIC ROPES)

EN12841 ▶ ROPE ACCESS SYSTEM

A rope device for work positioning.

EN1496 ▶ **RESCUE EQUIPMENT**

Rescue lifting devices.

EN567 ► EQUIPMENT FOR MOUNTAINEERING AND CLIMBING

Safety requirements and test methods for blockers.

EN12275 ► MOUNTAINEERING AND CLIMBING EQUIPMENT

Safety requirements and test methods for connectors.



FALL PROTECTION

EN12278 ► MOUNTAINEERING AND CLIMBING EQUIPMENT

Safety requirements and test methods for pulleys.

EN341 ▶ **PPE AGAINST FALLS FROM HEIGHT** Descending devices.

EN795 2012 ► **ANCHORAGE DEVICES**

Element to which a personal protective equipment can be fastened. (Standard under development).

- TYPE A Anchor device with one or more stationary anchor points with the need of a structural anchor.
- **TYPE B** Anchor device with one or more stationary anchor points without the need of a structural anchor.
- TYPE C Anchor device employing an flexible anchor line with maximum deviation of 15°.
- **TYPE D** Anchor device employing an rigid anchor line with maximum deviation of 15°.
- **TYPE E** Anchor device for use on surfaces with a maximum slope of 5°.



OTHER STANDARDS

EN1498 ► RESCUE STRAP

Directive 2006/42/CE for the machines or equipments with mobile function.

Directive 94/9/EC for equipment intended for use in potentially explosive environments.

EN13463-1 ► NON-ELECTRICAL EQUIPMENT FOR POTENTIALLY EXPLOSIVE ATMOSPHERES

basic method and requirements (risk analysis).

EN13463-5 ► NON-ELECTRICAL EQUIPMENT FOR POTENTIALLY EXPLOSIVE ATMOSPHERES

protection constructional safety "c" regarding the main mechanical devices: joints, bearings, gears, belts, clutch chains, brakes, coupling devices, conveyor belts

It sets out the requirements to be respected for the design and maintenance instructions.

It sets out the requirements and tests to be conducted according to the type of component.

Directive 93/42/CEE for the medical devices or accessories.





Α

ABRASION

Abrasion means wear through the action of friction. For the mechanical standard EN388 for gloves, EN343 for clothing and EN ISO20344 for shoes, the test consists of knowing when the product will deteriorate. The level is thus used to provide an indication of resistance and longevity.

ABS

Acrylonitrile Butadiene Styrene (ABS) is a thermoplastic used in industry to make rigid, light and moulded products. Material used to make the shells of safety helmets.

ACCOMMODATIVE (REFLEX)

The cristallin acts as a lens enabling focusing in distance thanks to a muscle. Presbyopia (near-sightedness) is caused when it does not work properly. The accomodative reflex ensures clear vision.

ACETATE

A fibre obtained by the action of artificial resins on cellulose and with: low weight, excellent optical properties, heat stability, good resistance to most chemical products. It does have some disadvantages however: low resistance to abrasion and scratching, risk of ignition near a heat source greater than 100°C.

ACRYLIC

Synthetic fibre often resembling wool: Very high elasticity (so does not crease) - Very lightweight - Heat insulation equal to wool - Very high resistance to abrasion and traction. It is thermoplastic, has low absorbent power and dries very quickly.

ACTIVATED CARBON

Activated carbon, or absorbent carbon or medicinal carbon, is carbon which has been treated by pyrolysis to increase its absorbency. The basic material used is often coconut, but it can be wood, bone or some other carbon.

A grain of activated carbon has a network of pores and channels similar in dimension to molecules. Activated carbon creates a chemical principle enabling toxic gas / vapour molecules to be captured.

AEROFRESH CONTROL

System developed by Delta Plus, used to ventilate the shoe at the instep and ankle by means of an air vent.

AEROSOLS

In chemistry, an aerosol is a set of solid or liquid particles, in suspension in a gaseous medium. An aerosol is a suspension of very fine particle (colloidal size) in a gas (risk of contamination of the air ways).

A cloud is an example of an aerosol. Other examples are mist, smoke or the cloud of dust given off when you shake out a rug.

AEROSOLS AND AQUEOUS FOGS

Small droplets produced during pulverization.

ALUMINISED (LINING)

The DELTALU aluminised lining combines heat insulation performance with lightness; polyester wad on aluminium foil batting (perforated). It is a real barrier inside garments protecting against the cold and the wind.

ANCHOR LINE

Element on which a sliding fall arrester moves. The anchor line can be a rope, a cable or a rail.

ANCHORAGE POINT

Element to which a fall arrest system can be connected.

ANTI-MIST (AB)

Surface treatment for lenses realized by dip coating the lens to prevent the formation of mist. This treatment is incompatible with mirror treatment of the lens itself.

ANTI-SCRATCH (AR)

Surface treatment of lenses to prevent superficial scratches. This treatment is obtained by dipping the lens in a «silicone» based solvent. It is colourless on the lense and does not alter vision.

ANTISTATIC

Property of a product, which prevents or limit the formation of static electricity. it is often requested in industrial environments for the risks of electrical discharge.

Antistatic protective clothing are mainly used in explosive risk environments such as: chemical plants, refineries, weapons factories, mines. They are also widely used to protect materials sensitive to electrical discharge such as on electronics manufacturing or semi-conductor assembly sites. Finally, they are used in controlled-atmosphere sites such as automobile paint workshops, the aim being to prevent the emission of particles which may be deposited on bodywork paint.

APV

Assumed Protection Value: complete and precise method for mesuring the hearing protector attenuation

- Attenuation per frequency (63Hz, 125Hz, 250Hz, 500Hz, 1000Hz, 2000Hz, 4000Hz & 8000Hz).
- Mean Attentuation: mean attentuation every 16 people tested.
- Standard Deviation: statistical presentation of the results.
- Assumed Protection: minimum attentuation at each Frequency level. It is computed by subtracting the standard deviation from the mean attenuation for each considered frequency.

APV

Assigned Protection Value.

Formula used to define the level of protection achieved in the workplace by 95% of operators trained in the wearing of respiratory protective devices or RPD and properly using after control a well maintained and adjusted device.

Maximal concentration allowed corresponds to: NPF x OEL.

AQL

Initials which mean «Average Quality Level». The standard ISO N° ISO2859 determines sampling for controls batch by batch, the AQL thus gives the maximum number of gloves with defects on 100.

ARAMIDES

Thermostable fibres used mainly in heat-proof applications . There are two types: para-aramides such as Kevlar® (anti-cut & resistant to flame and heat) and meta-aramides such as Nomex® (antistatic & resistant to flame and heat).



GLOSSARY

Δ

ABRASION

Abrasion means wear through the action of friction. For the mechanical standard EN388 for gloves, EN343 for clothing and EN ISO20344 for shoes, the test consists of knowing when the product will deteriorate. The level is thus used to provide an indication of resistance and longevity.

ABS

Acrylonitrile Butadiene Styrene (ABS) is a thermoplastic used in industry to make rigid, light and moulded products. Material used to make the shells of safety helmets.

ACCOMMODATIVE (REFLEX)

The cristallin acts as a lens enabling focusing in distance thanks to a muscle. Presbyopia (near-sightedness) is caused when it does not work properly. The accomodative reflex ensures clear vision.

ACETATE

A fibre obtained by the action of artificial resins on cellulose and with: low weight, excellent optical properties, heat stability, good resistance to most chemical products. It does have some disadvantages however: low resistance to abrasion and scratching, risk of ignition near a heat source greater than 100°C.

ACRYLIC

Synthetic fibre often resembling wool: Very high elasticity (so does not crease) - Very lightweight - Heat insulation equal to wool - Very high resistance to abrasion and traction. It is thermoplastic, has low absorbent power and dries very quickly.

ACTIVATED CARBON

Activated carbon, or absorbent carbon or medicinal carbon, is carbon which has been treated by pyrolysis to increase its absorbency. The basic material used is often coconut, but it can be wood, bone or some other carbon.

A grain of activated carbon has a network of pores and channels similar in dimension to molecules. Activated carbon creates a chemical principle enabling toxic gas / vapour molecules to be captured.

AEROFRESH CONTROL

System developed by Delta Plus, used to ventilate the shoe at the instep and ankle by means of an air vent.

AEROSOLS

In chemistry, an aerosol is a set of solid or liquid particles, in suspension in a gaseous medium. An aerosol is a suspension of very fine particle (colloidal size) in a gas (risk of contamination of the air ways).

A cloud is an example of an aerosol. Other examples are mist, smoke or the cloud of dust given off when you shake out a rug.

AEROSOLS AND AQUEOUS FOGS

Small droplets produced during pulverization.

ALUMINISED (LINING)

The DELTALU aluminised lining combines heat insulation performance with lightness; polyester wad on aluminium foil batting (perforated). It is a real barrier inside garments protecting against the cold and the wind.

ANCHOR LINE

Element on which a sliding fall arrester moves. The anchor line can be a rope, a cable or a rail.

ANCHORAGE POINT

Element to which a fall arrest system can be connected.

ANTI-MIST (AB)

Surface treatment for lenses realized by dip coating the lens to prevent the formation of mist. This treatment is incompatible with mirror treatment of the lens itself.

ANTI-SCRATCH (AR)

Surface treatment of lenses to prevent superficial scratches. This treatment is obtained by dipping the lens in a «silicone» based solvent. It is colourless on the lense and does not alter vision.

ANTISTATIC

Property of a product, which prevents or limit the formation of static electricity. it is often requested in industrial environments for the risks of electrical discharge.

Antistatic protective clothing are mainly used in explosive risk environments such as: chemical plants, refineries, weapons factories, mines. They are also widely used to protect materials sensitive to electrical discharge such as on electronics manufacturing or semi-conductor assembly sites. Finally, they are used in controlled-atmosphere sites such as automobile paint workshops, the aim being to prevent the emission of particles which may be deposited on bodywork paint.

APV

Assumed Protection Value: complete and precise method for mesuring the hearing protector attenuation

- Attenuation per frequency (63Hz, 125Hz, 250Hz, 500Hz, 1000Hz, 2000Hz, 4000Hz & 8000Hz).
- Mean Attentuation: mean attentuation every 16 people tested.
- Standard Deviation: statistical presentation of the results.
- Assumed Protection: minimum attentuation at each Frequency level. It is computed by subtracting the standard deviation from the mean attenuation for each considered frequency.

APV

Assigned Protection Value.

Formula used to define the level of protection achieved in the workplace by 95% of operators trained in the wearing of respiratory protective devices or RPD and properly using after control a well maintained and adjusted devices.

Maximal concentration allowed corresponds to: NPF x OEL.

AQL

Initials which mean «Average Quality Level». The standard ISO N° ISO2859 determines sampling for controls batch by batch, the AQL thus gives the maximum number of gloves with defects on 100.

ARAMIDES

Thermostable fibres used mainly in heat-proof applications . There are two types: para-aramides such as Kevlar® (anti-cut & resistant to flame and heat) and meta-aramides such as Nomex® (antistatic & resistant to flame and heat).

ARCH SUPPORT SYSTEM

This is an anatomical piece which provides rigidity to the instep and gives greater stability to the foot.

ARMBAND

Armbands are pieces of fabric worn around the arm. Fluorescent armbands are accessories, used for greater visibility. Attention these are not PPE.

ASSEMBLY

Assembly is the stage which consists of assembling the shoe upper on the form with the insole. Manufacturing occurs when this is assembled to the various midsoles and outsoles.

ATEX

This European regulation, which aims to improve the health and safety of workers at risk from explosive environments, is the result of the application of 2 directives:

- Directive 1999/92/EC for the protection of workers potentially at risk from explosive environments.
- Directive 94/9/EC for machines intended for use in explosive environments.

PPE are not governed by these two directives, they are even explicitly excluded from the Directive 94/9/EC (Chapter I, Section 4). They may be used in ATEX regulated zones as part of an overall explosion risk prevention system.

Directive 89/686/EEC for PPE takes into account the risks of explosion in Annex II, paragraph 2.6.: "PPE for use in explosive environments.

PPE for use in explosive environments must be designed and manufactured in such a way that it cannot be the seat of an electric or electrostatic arc or result from an impact, capable of igniting an explosive mixture."

ATTACHMENT

(DORSAL) Connection point of a fall arrester on a harness. (STERNAL) Connection point of a fall arrester on a harness. (LATERAL) Connection point of a work restraint system or work

(LATERAL) Connection point of a work restraint system or work positionning. (VENTRAL) Connection point of a work restraint system or work positionning.

E

BACK PAD

Element of a harness used to cross the straps at the back and position the D-ring at the correct height.

BIAS (FABRIC ON THE)

It is the use of a fabric part in its transversality (angle 45°) in order to obtain a flexible and deformable part. Examples of applications: strips or ribbons to be adapted to rounded forms (edge of a cuff, inside belt of trousers, etc.).

BLOUSON

A blouson is a short garment which only covers the torso and hugs the waist. A long jacket is an alternative between a blouson and a parka.

BLUE (LIGHT)

Harmful light emitted between 380 and more than 500 nanometres. Examples: intense sunlight, light used for the sedimentation of ceramics in dentistry, etc.

BRUSHED

Fabric on which one or both sides have a furry aspect obtained by the brushing operation.

The operation consists of passing the fabric over a rotating drum fitted with metal teasels. This treatment gives the article a soft, thick feel, making it warmer and bulkier, but removes toughness.

BUMP CAP

Bump cap and anti-scalp (EN812 standard). It is a PPE widely used in industry, especially for indoor use to protect the skull against shock contact with hard surfaces that could cause minor injuries.

It can not replace the helmet, in case it is required to wear a helmet with EN397 standard.

BUMPER CAP

Protective toecap designed to protect against premature wear on the front of the sole.

BURSITIS

Bursitis is an occupational illness of the knee, often occuring in tile layers, welders, floor covering layers, etc...

It comes in form of a gradual and slow increase in the volume of a bursa due to repeated microtraumas.

BUTT (LEATHER)

Part corresponding to the croup of the animal at the bottom of the skin (grain).

n

CANVAS (WEAVE)

The plain weave, is the basic fabric weave, and is characterised by inversed and alternating arrangement of the warp yarns on the weft yarns. There is no difference between the right and wrong sides of the fabric. This weave is particularly resistant to abrasion and very easy to water-proof.

CARBON (FIBRE)

The carbon fibre is used in materials for its anti-static properties.

CARROUSEL (INJECTION)

It's a machine with several injection stations (12 18 24 30 36) used to make soles.

CEMENTED (ASSEMBLY)

The most widely used manufacturing process for shoes in general: it consists of gluing the sole to the insole.



GLOSSARY

CEMENTED (SEAM)

Assembly procedure for seams by hot gluing to guarantee the sealing of seams for coated materials.

CHEST STRAP

Strap used in the design of a harness with the role of maintaining the position of the harness straps on the shoulders in order to prevent any risk of losing the harness in the event of a fall. The chest strap is not obligatory on a harness.

CHIN STRAP

Element used to prevent a safety helmet from falling. It may be simple or with a chin-cup, with two or four fastening points used for work at height.

CHLORINATED (GLOVE)

A washing process for the latex glove, washed in chlorinated water to produce unpowdered gloves. The advantages of unpowdered glove is: it is easier to put the glove on (a velvety contact), improves comfort and reduces the allergenic effect of the natural latex proteins carried by the powder.

CLEARANCE

The clearance is the height between the foot of a person equiped with a fall arrest system and the nearest obstacle.

CLOGGING

Phenomenon of dust filtre saturation. As respiratory protection is provided by a mechanical barrier (interlacing of fibres and electromagnetic reaction), when the filter is saturated, clogging occurs; the user feels difficulty in breathing.

CLOSING

This is the step during which the various parts of the upper, collar, vamp, quarters, gussets are assembled..

COATING

Coating is the operation by which the surface of a textile or leather is coated with a layer of chemical product with the aim of giving it properties of chemical resistance, or to enhance its mechanical resistance. They are mainly found in the form of polyvinyl chloride (PVC), polyurethane (PU), and natural (Latex) or synthetic (Nitrile, Neopren) elastomer. There are many applications, from tarpaulins to imitation leather including proofing of protective clothing.

CONCENTRATION

Quantities of chemical products in the air breathed by a worker at his workstation, and which may adversely affect his health. Hence the need to have concentration limits below which the risks of intoxication are low or non-existant (TLV/OEL).

CONFINED SPACE

A confined space is characterized by a volume/ dimension ratio such as the natural exchange of indoor air with outdoor air being reduced and able to cause asphyxiation, intoxication, fire or explosion. In these areas, the risks are increased by various gas or smoke fumes. Examples: wells, tanks, sewers, ditches, accessible collectors, valve chambers, tanks...

CONNECTOR

Connecting element. A connector can be a carabiner or a hook.

COTTON

Natural textile fibre made of silky filaments surrounding the cotton seed: it is comprised of about 94% cellulose. Comfort, easy cleaning and good absorbency are its main properties.

CUFF

15 cm gauntlet found on welding gloves to protect wrist and forearm against molten metal splash.

П

DECIBELS

Acoustic pressure, in other words the intensity or amplitude of sounds and noises, expressed in decibels (dB), and determines the danger to humans. The safety level has been fixed at 85 dB: above this, pain occurs, and injuries appear.

Decibels are usually measured using a sound meter which converts the sound signal into an electric current.

DEFLECTOR

This is the role played by the helmet because of its rounded shape, it deflects the trajectory of a moving object, without stopping it suddenly, preventing a violent impact.

DERMIS

The skin of the animal, comprised of two layers: the grain (external part of the dermis) and the flesh split (internal part of the dermis). Using the tanning process, the dermis is transformed into leather.

DESIGNER

Person in charge of creating the shoe design integrating all the technical design elements.

DIOPTER

Unit of power of optical systems used to determine the measurement of refraction, i.e. the ability of a medium or an object to deflect light rays. Unit of power equal to the inverse of the focal distance, expressed in metres. The focal distance is the distance between the lens or the refracting medium, and the point at which these rays converge (where they meet). The human visual system is 60 diopters (40 for the cornea and 20 for the cristallin).

DIPPED (GLOVE)

Glove manufacturing process by dipping the form of a ceramic hand in baths of various compositions depending on the material used. The next step is firing in ovens (vulcanisation).

DMF

Dimethylformamide N or N-dimethylformamide is a common solvent used in organic chemistry. DMF may be a carcinogenic substance, although the EPA (Environmental Protection Agency) does not consider it a cancer risk. The new innovative manufacturing process, also called PU Water, is 100% based on water. No solvents, such as DMF, are used, strengthening innocuousness.

DOLOMIA

Dolomia is a sedimentary carbonate rock comprised of at least 50% dolomite. It is a double calcium and magnesium carbonate, which crystallizes into lozenge-shaped prisms (rhombohedrons). Dolomia is a sedimentary rock comprised mainly of the mineral dolomite (between 90 and 100%) and calcite, which do not have the same density (dolomite: 2.87; calcite: 2.71), playing a fundamental role in rock erosion.

The Dolomia test, conducted using Dolomia dust, is an optional test for filtering face pieces (EN149 :2001 A1:2009) guaranteeing longer lasting performances of resistance to penetration.

DRILEX®

Drilex® is a technical lining found in top of the range sports shoes. This lining is comprised of 2 fibres and enables absorption of perspiration and evacuation of humidity to the outside (antibacterial and anti-odour).

DUAL GRIP

Name of an outsole offering a grip system suited to smooth or friable surfaces, with a large contact tread pattern, and central channels to evacuate liquids.

DUAL-DENSITY (SOLE)

Dual-density means the sole is made of 2 superimposed parts; the underpart in contact with the ground is more rigid whereas the upper part is more flexible and shock absorbent.

DUNGAREE

Dungaree are work garments comprised of trousers and a bib on the chest with shoulder straps. More commonly known as dungarees.

DUSTS

Solid particles suspended in the air.

E

EAR DEFENDER

Element of ear defenders (with the headband and the foam) which provides the sound attenuating effect.

EARPLUGS

Disposable or reusable ear defenders (EN352-2): inserted in the ear canal to plug the conduit. Usually made of polyurethane or PVC, they can also come with a cord, a headband and a detectable metal insert (for use in the food processing industry).

ECO-DESIGNED

Delta Plus develops eco-designed products whose environmental impacts are reduced to a minimum. Thus, throughout the lifespan of the product, the use of energy is minimized, the use of raw materials such as organic cotton and reduced packaging are given priority.

EDGED (SEAM)

Seam consisting of covering another seam with a band of fabric compatible with that of the garment to provide better sealing.

ELASTANE

Extensible fibre made of synthetic elastomer yarns. Elastane is always mixed with other fibres to give the fabric its properties: suppleness, elasticity and crease-proofing.

ELECTRIC ARC

An electric arc is a visible electric current in a nonconductive media (gas, air, vacuum...).

The arc is created when the non-conductive material ionizes, which occurs more easily when conducting surfaces are nearby. The position of an electric arc is stable: once it has found the shortest path, it remains there (minimum energy principle). The whole difficulty for arc welding is therefore to master the arc using a continuous movement so that it keeps the desired form despite the fact that the emitting surface (or more rarely the receiving surface) is sometimes an acute angle.

Electrical arc welding produces a huge quantity of localized heat generating the fusion of materials, making strong joins that remain after cooling.

ELECTRIC FLASHOVER

Electric flashovers are electrical burns without the current passing through the body. In low voltage, following an electric arc, the skin injuries are superficial and mainly affect the hands and face.

Protection is provided by the polycarbonate of a thickness >1.4mm. The best protection is provided by a face shield.

ENERGY ABSORBER

Fall arrester composed of a lanyard with an energy dissipating device, which guarantees to stop a fall from height safely under normal conditions of use.

ENERGY DISSIPATOR

Component of a fall arrester designed to dissipate the kinetic energy accumulated during the fall.

ERGONOMICS

Studies and research into the methodical organisation of work and the arrangement of protective equipment according to the anatomical possibilities of people.

ESD

ELECTROSTATIC DISCHARGE, electrostatic discharge.

Any contact and any physical separation of solid materials may generate electrostatic charge. A person, or a garment worn by the person, may be electrically charged. Where appropriate, the ESD can cause damage, if the charged person or object comes into contact with an ESD sensitive device (microchips, semiconductors, printed circuit boards...).

EN 61340-5-1 (Protection of electronic devices against electrostatic phenomena) defines the general requirements of the areas protected against ESD, EPA (ESD Protected Areas).

To be admitted into an EPA area, depending on the configuration of the workstation, clothing and footwear must be subjected to specific electrical charge dissipation tests determined by European and American standards. Based on the results of these tests, the product will have the special ESD marking. Other PPE (gloves, head protection and fall arrest system) are not mentioned in this standard.

EUROPEAN DIRECTIVE

The directive is a community legal act taken by the Council of the European Union, alone or with the Parliament depending on the case. Member



GLOSSARY

states are bound by the directive in the objective to be reached, but are free to choose the means and way of reaching this objective within the time limits fixed by it.

l

FABRIC

Any material obtained by interlacing of the warp and weft yarns, and made on a loom or weaving machine. Fabric with a plain weave structure is usually called plain weave.

FALL ARREST HARNESS

Body harness system designed to stop falls, a harness is one element in a fall arrest system. It should be designed to hold the individual during and after the fall with an angle of 50° from the vertical.

FALL ARREST SYSTEM

Protective equipment against falls from height or fall-arrest systems are comprised of 3 elements:

- a body holding system designed to stop falls (fall arrest harness).
- a linking sub-system designed to stop a fall from height (self-retracting fall-arrester, sliding fall-arrester or energy absorbing lanyard).
- a safe anchorage point.

FALL INDICATOR

Mechanical and visual device that allow to identify if a fall arrester suffered a drop impact.

FILTERING MEDIA

Type of respiratory protection device used either in positive pressure (assisted ventilation) or in negative pressure (free ventilation).

FINISH

Finishes are treatments used on some fabrics or yarns, to give them special properties, such as flame proofing, antistatic, water repellent, etc.

FLAME PROOFING

Treatment of textile materials with non flammable substances to reduce the risks of fire or slow flame spread.

FLANNEL

Lightly brushed fabric, soft and fluffy to the touch, originally made of wool.

FLAP

See valve.

FLASH

Surface treatment of a lens giving it a mirrorer aspect. The mirror effect on lens reflects the intensity of the light and heat to reduce eye strain during exposure to bright light, and to limit headaches resulting from this exposure.

This treatment is not acompatible with anti-fog treatment. The colour of the treatment can be gold or other.

FLEECE

Thick, soft fabric, brushed on both sides.

FLOCK (GLOVE)

Cotton fibers deposited as a finishing process. Flocking provides a pleasant and soft contact and reduces perspiration.

FLUCTUATING

Noise whose fluctuations are greater than 5dB during the period of measurement.

FOAM

Element of ear defenders (with the headband and the ear cups) which attenuates the noise and provides comfort. It's inside the ear cups.

FOOD (COMPATIBILITY)

The products must not pass on to foodstuffs components of a quantity which may pose a danger to human health, or lead to an unacceptable modification to their composition or a change in their organoleptic qualities. Directive 85/572/CEE provides a list of simulants to be used to check the migration of material components and plastic objects designed to be in contact with foodstuffs:

- Aqueous foodstuffs (pH > 4.5): Simulant A.
- Acid foodstuffs (pH <= 4.5): Simulant B.
- Alcoholic foodstuffs: Simulant C.
- Fatty foodstuffs: Simulant D.
- Dry foodstuffs: Simulant E.

FOOD (SOLE)

White or light-coloured sole to prevent marks on the floor; anti-slip sole as it is used on very slippery surfaces.

FREQUENCY

Frequency is expressed in hertz. Only sounds with frequencies of between 20 and 20 000 Hz are audible.

At a frequency of between 20 and 200 Hz, the audible sound is low-pitched. Below that, they are infrasounds.

At a frequency of between 2000 and 20 000 Hz, the audible sound is high-pitched. Above that, they are ultasounds.

FUMES

Small particles suspended in the air (aerosols).

C

GAUGE

This is the width of the stitch. It corresponds to the number of needles used in 1 English inch (2.54 cm). Example: gauge 7 corresponds to 7 needles in 1 inch. The higher the gauge, the finer the stitch. Gauges are 7, 10, 13, 14.

GLASS FIBRE

Glass fibre is a very fine filament of glass. By extension, composite materials strengthened with this fibre (usually associated with polymers) are also called glass fibre.

Monolithic glass is a very fragile material but when spun to a diameter less than one tenth of a millimetre, it loses its fragility and becomes a highly mechanically resistant material.

GRAIN LEATHER

External part of the dermis, with no mechanical modifications. This is the most supple and resistant part of leather.

GUSSET

It is the part of the shoe on either side of the tongue. It protects and seals the closure.

R

HACCP

Hazard Analysis Critical Control Point. This a method of quality control in the food industry, used to:

- identify and analyse the risks associated with various stages in the production process of a foodstuff.
- define the means required to control them.
- ensure that these means are implemented effectively and efficiently. It is a systematic and rational approach to controlling microbiological, physical and chemical hazards in food.

HARNESS

An element of the harness. The most of arm webbing are starshape with 4 or 6 arms. Webbing with 6 fixing points or more, ensure better distribution of the force exerted on the helmet. Webbing can be made of polyethylene, or textile for better absorption of perspiration.

HARNESS (SAFETY HELMET)

It can be made of textile material or polyethylene. Its role is to absorb the impact of a falling object. It is comprised of two elements: the headband and the webbing.

HEADBAND

Element of ear defenders (with the muffs and the foam), it maintains the pressure of the protection on the ears.

HEADGEAR

It is one of the elements of the harness of safety helmet. It is often made of low density polyethylene (LDPE). It is adjusted by a tightening system with rack (ratchet), or by a sliding system (tightening straps with notches).

HEAT SEALED (SEAM)

Seams covered on one side with a band of fabric compatible with that of the garment and hot-welded for increased protection and sealing.

HML

High Medium Low: 3 levels of frequency measurement.

HYDROPHILIC

A hydrophilic fabric is comprised of water-absorbent materials (e.g. cotton, wool, etc.).

HYDROPHOBIC

A hydrophobic fabric is comprised of materials that do not absorb water. (e.g. polyamide, acrylic, polyester...).

IMPACT FORCE

This is the force subjected to the body at the moment of the fall, expressed in daN (decaNewton).

IMPERMEABLE

An impermeable fabric is used to make products which is completely water and air tight.

Water proofing is usually done by the application of a coating. The coating is a deposit of a plastic film (PVC, polyurethane or acrylic) on the surface of a textile. For example, rain suits with their polyurethane or PVC coatings, boots in PVC or dipped glove.

IMPULSE

Noise the sound level of which increases considerably almost instantaneously.

IMPUTRESCIBLE (LEATHER)

After the tanning process, the leather becomes imputrescible, meaning it cannot rot.

INFRARED

Infrared (IR) radiation is electromagnetic radiation of a wavelength longer than that of visible light, but shorter than that of microwaves. Infrared radiation has wavelengths between about 750 nm and 1 mm, spanning five orders of magnitude.

INFRASOUNDS

Sounds of a frequency to low to be heard by humans (< 20 Hz). The average human ear only hears sounds within a certain range of frequencies between about 30 Hz (below that the sounds are called infrasounds) and 15 kHz (above which the sounds are called ultrasounds). Some physiologists even extend the limits of this range from 20 Hz to 20 kHz.

INJECTION (SOLE)

Sole or zip manufacturing system, liquid material is injected into a mould, this material then solidifies and takes the form of the mould.

INJECTION POINT

Point through which the press injects polyethylene into the mould and which is cut on removal from the mould.

INNOCUOUSNESS

The innocuousness of a product guarantees the fact that it contains no materials which may cause allergies to sensitive people. Innocuousness is an integral part of the basic requirements of protective clothing in EN340 or gloves in EN420. Usually, the pH of materials, the chromium VI content of leathers, the nickel emission of metallic materials, azoic dyes and the solidity of the dyes are tested.

INSOLE

This is the sole inside the shoe, in contact with the sole of the foot.

INTERLOCK

Basic knitting weave, each side are the same.

Interlock has good dimensional stability which doesn't ladder too much. Widely used to make sports clothing.

INTERMITTENT

Noise whose fluctuations fall to the ambient level several times.



GLOSSARY

JACKET

A jacket is a garment with sleeves, closed in the front, covering the torso to the waist or hips.

JERSEY

Light and supple knits with a different right and reverse side. Widely used to make t-shirts and undergarments. The advantages of jersey are suppleness and comfort.

K

KEVLAR®

Para-aramide fibre manufactured by DuPont de Nemours. It combines lightness and resistance. For equal weight, Kevlar® is five times tougher than steel. Its properties: very resistant to cutting, carbonises between 425°C and 475°C; does not melt; self-extinguishing; dimensional stability; chemical stability; alteration of colour under UV.

KINETIC ENERGY

Energy that a body has as a result of its motion.

KNIT

All fabrics made of stitches or interlaced loops, made using needles or hooks. Knits are extensible. The basic fabrics are: rib, interlock, jersey.

KNITTED CUFF

Flexible, elastic knitted band finishing a collar, sleeves, legs, bottom of some garments.

Used to tighten wrists, collars, etc.

- Integrated cuff (knitted at the same time as the main piece).
- Pieced-cuff (knitted separately and stitched).

L

LAMINATED (FABRIC)

A laminated fabric is a complex of several layers of woven, knit or non-wovens assembled to enhance their performances.

2-layer laminate is used to describe a fabric laminated on 2 layers with a waterproof fibre usually on the outer layer. The inner layer is usually thicker and softer for greater comfort against the skin.

3-layer laminate is a fabric laminated in 3 layers, usually with waterproofing on the outer layer, comfortable fabric on the inner layer and sandwiched between the two, a waterproof- breathable membrane.

LANYARD

Generic term, a lanyard can be made of synthetic fibre rope, metal cable, webbing or a chain. A lanyard may not exceed 2 m in length.

LAST

The last is the basis for any study of the shoe which determines the general look, the volume and fit. It is made of wood for the study and then in plastic for production. The length of the foot, perimeter at the joint, foot width, and instep height are used to determine the size of a shoe and make the basic last.

LIFFLINE

This is an anchor line to which a fall arrest system is connected to safeguard the horizontal movements of a person working at height. The anchor line can be a rope, a strap, a cable or a rail.

LINING

This is the part in contact with the foot. Often made of leather or textile, it improves the solidity of the shoe and acts like a second skin for comfort.

LOOSE SOIL

Irregular, uneven surface.

N

MANUAL ADJUSTMENT

Tightening system for safety helmets, using a sliding plastic strap. This system differs from the rack and ratchet system.

MECHANICAL INSPECTION

For PPE of 3rd Category III, it is obligatory to review at least once a year the PPE to ensure its proper functioning. This mechanical inspection is also required after any fall.

MEMBRANE

This is a thin polymer film (PU or polyester) applied to the inner surface of a fabric to enhance waterproofing and breathability..

MESH

An alveolar fibre, used to enable air circulation and evacuate perspiration.

MICROFIBRE

Light, very fine and soft synthetic textile fibre with soft touch, skin of peach aspect.

MIDSOLE

The midsole is also called the comfort sole, whereas the outsole is in contact with the ground; together they make up the two parts of a shoe sole.

MIG/MAG (WELDING)

MIG (Metal-arc Inert Gas) or MAG (Metal-arc Active Gas) welding (the only difference between the two is the gas used to protect the welding bath), both indicated in AWS terminology as GMAW (Gas Metal Arc Welding), is a semi-automatic welding process.

The metals are melted by the heat energy released by an electric arc which erupts in a protected atmosphere between a fuse electrode wire and the parts to be assembled.

MIRRORED

See flash.

MOULDED

Moulding is a technique which consists of shaping an object using a mould which is hollow to hug the form of the desired object.

The moulded material must be able to change from the liquid to the solid state or be thick but sufficiently consistent to be able to be removed from the mould without deforming.

A wide range of materials can be moulded:

- metals
- plastics. The manufacturing process for frames is injection moulding. A part production technique for large or very large production runs, this moulding can be in disk or in form.

N

NANOMETRES

Unit of measurement (1 millionth of a mm) used to calculate the wavelength of light. Maxwell in 1865 succeeded in demonstrating that light is an electromagentic wave whose field is measured in nanometres, with a visible and invisible spectrum. The wavelength determines the colour of the light. The human eye is only sensitive to wavelengths between 400 and 700 nm.

NATURAL LATEX

This is a natural polyisoprene from the Hevea braziliensis. It is part of the elastomer family, and is therefore elastic, supple and robust. It also has the properties of being impermeable to water, and resistant to detergents and some alcohols.

NBR (NITRILE)

This is a type of Nitrile: Nitrile Butadiene Rubber (NBR).**NEOPRENE** It is a synthetic latex. It is obtained by polymerization of a chlorinated compound: polychloroprene.

The neoprene has the same advantages as latex, namely impermeability, elasticity and resistances against alcohols and detergents. It is also an excellent protection against the chemicals, greases and hydrocarbons and has a good resistance against heat.

NITRILE

It is a synthetic latex. Its vulcanisation gives it properties similar to natural latex and many advantages (resistance to abrasion; excellent performance in oily and greasy environments; good resistance to chemical products).

NON WOVEN

Non-wovens are used to make numerous products: single-use garments, quilt padding, sleeping bags, cleaning cloths, baby's nappies, floor and wall coverings, reinforcements, garment padding, etc...

The three production processes for the lap of non-wovens are:

- dry spinning the fibres are used directly off the cards to make mattresses of fibres.
- by wet spinning a process similar to paper manufacture is used.
- by melt spinning the synthetic filaments are extruded in a current of hot air then lapped.

NON-INVERTING DEVICE

Element added to a sliding fall arrester to prevent installing it upside don on the anchor line.

NOSE CLIP

A flexible piece located at the top of single-use half-masks (on the nose), to adjust the face piece to the user's morphology.

NOTIFIED BODY NOTIFIED ORGANIZATION

Element added to a sliding fall arrester to prevent installing it upside don on the anchor line.

NPF

Nominal Protective Factor.

Formula used to define the level of protection provided by wearing a respiratory protective mask, and in standard test conditions: NPF = 100 / TIL (%). The maximum exposure concentration corresponds to: NPF x MEV.

NUBUCK (LEATHER)

Grain leather the surface of which has been buffed, giving it a fine velvety and silky aspect.

NYLON

Registered trade name of DuPont de Nemours. It is a polyamide.

0

0EL

Occupational Exposure Limit;

Concentration measured in mg/m3 or in ppm, for an exposure time equal to the work day (workday of 8 hours), corresponding to the toxic risk.

OIL-WATER REPELLENT

Leather treatment using mineral or synthetic oils or fluorinated resins, to make it resistant to water and/or oil penetration. This treatment gives the leather better mechanical performance for abrasion and increases the comfort (flexibility) of the glove, hence increased dexterity and lifespan.

OPTICAL BASE

This is the radius of curvature of the lens.

The most curved optical base is 9; the least curved is 4; the most common is 6.

OPTICAL CLASS

Parameter which measures the optical quality of the lens. There are 3 classes of optical quality. The 1st corresponds to the best quality and is recommended for permanent wearing of glasses. The 2nd class is used for intermittent wearing and the 3rd only for very brief wearing.

OUTSOLE

The sole, also called the outsole, is the part of the shoe in contact with the ground. As a result, it must be as tough as possible. With the midsole, it comprises the two parts of the sole of a shoe.

OUTSOLE

The sole is the under part of the shoe. It is in contact with the ground. Several soles can be used to make up protective footwear. The materials used to make them, their sculpture and the manufacturing process will ensure the ergonomic performance required, i.e.: Grip, Anti-slip, Safety & Wearer comfort.



GLOSSARY

OVERALL

Single-piece garment covering the whole body.

OVERCAST (SEAM)

Seams made using overcast stitch consisting of interlacing three threads around two edges of the fabric to be assembled.

OVERGLASSES

Protective glasses designed to be worn over spectacles.

OXFORD

Thick-yarned plain weave with a lustred finish similar to the Oxford weave of cotton shirts.

D

PANOFLEX®

Flexion zones integrated into the sole to enhance flexibility.

PANOSHOCK®

Delta Plus innovation: piece of expanded rubber which absorbs and reduces shock waves to the spinal column.

PARKA

A parka is by definition shorter than a coat, longer than a jacket or a blouson, and is impermeable.

PATTERN CUTTER

Person who makes the templates or patterns for garments: uppers for shoes, patterns for clothing, before cutting and assembly.

PERMEATION

Although the glove shows no porosity or imperfection, the chemical product may gradually pass through the glove, and come into contact with the skin. The standard EN374 assesses this performance: the time (in minutes) taken by the chemical substance to integrate and pass through the protective material is measured (1 mg/m²).

PHYLON®

PHYLON® is a synthetic materials, supple, ultra light, shock absorbent, used in running shoes by all the major sports brands; It is an EVA insert (Ethylene Vinyl Acetate) moulded, expanded.

PIGMENTED (SPLIT LEATHER)

Split leather coated with a layer of pigment. This is an economical, quality and resistant shoe leather.

PIQUE EFFECT (STITCH)

Knitted fabric with a raised waffle texture.

PLATING

Knitting process consisting of obtained two different fabric sides, each with a different type of yarn. Also used to combine two advantages: comfort and resistance for example.

POLAR FLEECE

Stitch brushed on one or both sides to obtain an aspect as soft as velvet. Polar fleece provides unrivalled comfort thanks to its lightness, its

softness, its breathability and its extensibility. As this stitch is not wind breaking, polar fleece complexes with microporous membranes have been developed.

P₀L₀

Polos are originally sports shirts with a turned-down collar, more specifically of Jersey.

POLYAMIDE

Synthetic fibre resistant to traction and abrasion. This is an elastic fibre that recovers its original shape after deformation. It dries rapidly as it absorbs little water. It is insect-resistant (especially against mites).

POLYCARBONATE (PC)

Polycarbonate is a polymer (plastic) which has excellent mechanical properties and thermal resistance enabling it to be used at temperatures of up to 120°C. It has optimal shock resistance, hence its use in many sectors. It filters 99.9% of UV between 0 and 380 nm, UV 400 treatment extends this protection to 400 nm and absorbs part of the blue light in the light spectrum. Its sensitivity to chemical agents and to ultraviolet rays limits its use, however.

POLYESTER

Synthetic fibre with several advantages similar to those of polyamides: resistance to traction and friction; good elasticity; uncreasable; solidity of dyes; easy care; high resistance to abrasion, resistance to acids, bases and solvents, and to heat. It can be mixed with wool and cotton, which makes up for its inability to absorb transpiration, its rough texture and its tendency to pilling.

POLYETHYLENE

Polymer obtained by polymerisation of ethylene molecules. This is a material, with good chemical resistance, high stability, and easily recycled. Polyethylenes (PE) are classified according to their density:

- LDPE (low density) is a supple plastic, used for helmet harnesses for example.
- HDPE (high density) is a hard plastic, used for the shell of helmets for example.

HSPE (high strength) provides good mechanical performances in particular against cutting, such as the fibre TAEKI for example.

POLYMER

A polymer is the name of a chain of molecules used to make synthetic filaments before being melted and transformed into yarns. The polymerization operation is a process to manufacture a polymer by connecting small molecules (monomer) into a molecular chain of multiple molecular weight (mass).

POLYMERIZATION

Chemical process by which resins or plastics are fixed to textile materials by means of heat to obtain canvas with coating.

POLYPROPYLENE (PP)

Belongs to polyolefin fibres, structurally very similar to polyethylene. Polypropylene can be used as a plastic (helmets) or as a fibre (woven or non woven). This material is easily recyclable, resistant to friction (abrasion) and to traction. It is grease-resistant. Its melting point is higher than 160°.

POLYTEXTURE

Material effect by association of weaving. Example: Ripstop with a box-effect.

POLYURETHANE (PU)

Polyurethane is a polymer transformed into synthetic resin or foam used in coatings, in some membranes and in the manufacture of elastane yarns (Lycra®). Polyurethane is frequently used for coating, making fabrics waterproof. Garments made with such coatings are often breathable and very good alternative solutions to much more expensive products made using waterproof breathable membranes. It has very good mechanical resistance (wear, abrasion, tearing and micro-cuts).

PONGEE

Fabric with a silky, shiny finish.

POPLIN

Tightly woven cotton plain weave used primarily for shirts.

POWDERED (GLOVE)

Finishing process using a powder deposit (usually corn starch). The result is pleasant to the touch and soft which limits transpiration. For disposable gloves, the powdering facilitates donning and removal.

PPE

Personal Protective Equipment.

According to the European directive 89/686/EEC, any equipment designed to be worn or held by a worker to protect him against one or more risks which may threaten his occupational health or safety, and any additional element or accessory designed for the same purpose.

PRE-FILTER

Thin filter for protection against dust (P2 or P3), to be used on full and half-masks, associated with anti-gas filters (A/B/E/K) in order to obtain a combined gas and dust filter.

PU WATER (MANUFACTURING)

Innovative manufacturing process for PU coated gloves, 100% water-based, i.e. no solvents, such as DMF, are used to ensure the bonding of the polyurethane (PU) and the support. As well as limiting the environmental impact of manufacturing, this technology minimizes the quantity of coating that penetrates inside the glove, making the support softer and more comfortable, as it limits transpiration and the accumulation of heat.

PUPILLARY (REFLEX)

The eye's adaptation to light intensity: the pupil dilates or retracts.

PVC

Polyvinyl chloride is a polymer usually known by its abbreviation PVC. PVC resists many solvents, acids and chemical products (in particular hydrocarbons). Fabrics coated with PVC are real barriers against bad weather. However, they should be worn for a limited time depending on the temperature in the working environment.

C

QUILTED

Insulating lining made by superimposing materials held together by decorative stitching (fleece + lining).

R

RAGLAN (SLEEVE)

Sleeve assembled on the bias, from the neck to the underarm. There are no shoulder or underarm seams, making for greater ease of movement.

RATCHET

Tightening system of the headband for safety helmet, for easier adjustment, using a ratchet.

REINFORCEMENT

Insert (often made of leather) stitched to the glove in the zones most exposed to the risks of abrasion and cutting (Palm reinforcement, Web reinforcement between the thumb and index finger) or lateral or in front of the shoes.

RESTRAINT (SYSTEM)

System designed to attach a person to an anchorage point so as to prevent any fall from height.

RETRO REFLECTIVE (BAND)

These are bands fixed to high-visibility garments. 3M Scotchlite™ uses 2 types of technologies, microprisms (better contrast, rigidity suited to some garments) and microbeads (resistant to washing, high flexibility), and offer several different types of bands (stitched or sealed). Retro reflective materials are used to reflect light by day and by night.

REVERSE GRAIN

Use of the inner part of the grain enabling considerable suppleness to be maintained, and significantly improving resistance to abrasion. Water-repellent treatment applied to reverse grain is ten times more effective than on the grain itself.

RIB

1x1 / 2x1 / 2x2 type knits (the first and the second figure respectively indicate the number of column in relief and column in hollow seen on the face place) used to make very elastic and reversible knits. Used mainly to make sweaters, cuffs and hose and undergarments.

RIPSTOP

This is a box-effect fabric weave (thicker yarn) that prevents tears from spreading while reducing the weight of the fabric.

ROLLING

Action of crushing leather on its whole surface with a roller to make it firmer and more flexible.

RUBBER

Synthetic elastomer made from oil and with elastic and resistance properties. The advantages of this material are to offer mechanical properties of good grip, good resistance to abrasion, contact heat and to oils and grease.



S

SATIN (WEAVE)

A fabric with a «satin» type weave is characterised by a shiny and smooth aspect. The yarn density gives it the advantage of not igniting as easily as «plain» weave. With special treatments, such as Proban®, flame retardants, it is a flame resistant material widely used for PPE.

SCIVING

Operation to thin the leather to prevent over-thickness during assembly.

SEAT STRAP

Strap used in the design of a harness with the dual role of seat and force distribution in the event of a fall, hence preventing too violent a force between the legs and any resulting consequences. The seat strap is not obligatory on a harness.

SELF-RELEASE (SYSTEM)

Chinstrap mechanism, ensure proper operation. According to standard EN397: the system should be triggered by a force > 150 N and < 250 N.

SELF-RETRACTABLE FALL ARRESTER

Device with automatic blocking system and an automatic lanyard tensioning system.

SHANK

Used to support the instep. Very often made of wood, then steel, it is also now made of composite material. Its role is to maintain the instep, or arch of the foot.

SHELL (SAFETY HELMET)

The shell is one of the components in a safety helmet (external part). Its role is to limit injuries by contact impacts (crushing and penetration). It is made by injection from two types of materials:

- HPDE (high density polyethylene), an efficient material, the most economical and widely used.
- ABS (acrylontrile butadiene styrene), a more rigid material.

SILICONE (FREE GLOVE)

Silicones are polymers derived from sand. They are present more or less everywhere, in the form of mastics, glues, joints, anti-foam additives for washing powders, cosmetics, medical equipment, electrical cable insulation sheaths, high-performance grease, etc...

A certified silicone-free glove has a considerable advantage in industries requiring the total absence of silicone in their manufacturing or assembly process, for example in the automobile industry to guarantee paint without marks.

SIZE

Half pelt cut from head to tail along the line of the backbone.

Set of measurements of the shoe volume, usually determined by the length and width of the foot, measured around the joint of the toes (toe width). Additional measurement tables, such as the height of the instep, determine the various sizes.

There are three main measurement systems in use in the world:

- french sizes (from 17 to 48).
- english sizes (1 to 13 feet).
- american sizes (equivalent to the English sizes + 0.5).

SLIDING FALL ARRESTER

Fall arrester with an automatic blocking function and a guidance system. The fall arrester moves along an anchor line. It accompanies the user in his movements with no manual intervention needed by him. In the event of a fall, the fall arrester automatically blocks on the anchor line.

SNR

Single Number Rating: a simple and widely used method to mesure the attenuantion noise, even if not really precise (measurement of decibels without taking account of frequencies).

SOFTSHELL

Soft shell materials are hybrid materials. Between the polar fleece and the windbreaker, «softshells» combine several advantages: keep in body heat, evacuate humidity and act as a barrier to external aggressions, mainly wind and fine rain. It may be laminated to enhance performances (breathable, water repellant).

SOLVENT (FREE COATING)

A solvent is a liquid that has the property of dissolving and diluting other substances without changing them chemically and without changing itself. The new innovative manufacturing process, also called PU Water, is 100% based on water. No solvent, such as DMF, is used to ensure the bond between the polyurethane (PU) and the support.

SOUND

A sound is an acoustic vibration, a movement of particles in an elastic medium: the air.

Sound is characterised by its intensity (amplitude of variations in air pressure): high or low which is expressed in decibels (dB). Sound is also characterised by its height: high or low-pitched (number of oscillations per second) which is expressed in Hertz (Hz).

SPI ICE

The process of weaving one end of a stranded rope or cable into the other in order to create a loop.

SPLIT

Internal part of the dermis, obtained by splitting or any other operation to remove the outer layer. The resistance to abrasion and heat are split advantages (after heat treatment).

STABLE

Noise whose fluctuations do not exceed 1dB during the measurement period.

STEEL

Use for the anti-puncture sole for its resistance to a force of 1100N and use for safety shoe toecap for its resistance to 100 or 200 joules.

STEL

Short terme exposure limit.

Concentration measured in mg/m³ or in ppm over a maximum time of 15 minutes that it is advisable not to exceed.

STIFFENER

A semi-rigid part inserted between the upper and the lining, located at the back of the shoe to prevent flattening and hold the heel in place.

STRAPS (MAIN)

The main straps are elements which are used in the design of a fall arrest harness. They should support a person's body during and after the fall. Other straps in the design of a harness are called secondary straps.

STROEBEL (STITCH)

This stitch is just the overstitch known to seamstresses; a single thread is chain-stitched to assemble the insole to the upper...

STRUCTURE

In knitting, the method of interlacing stitches is called the structure. The three basic knit structures are jersey, interlock and rib.

STYLIST

Person in charge of creating the sketch for a product (shoe, garment, glasses...) integrating technical elements and design constraints.

SUEDE (LEATHER)

Split suede leather is made from the flesh and buffed to obtain the suede aspect, like Nubuck, but which is from the grain.

SUPPORTED (GLOVE)

The dipped form is covered (or not: non supported) with a jersey or interlock cotton knit glove. A supported glove has better mechanical protections and comfort than an unsupported glove.

SWEATBAND

Sheep or lambskin prepared by vegetable tanning, finished without dye and mainly used in linings.

SWIVELLING CONNECTOR

Element often added to a connector or a fall arrester enabling separate rotation of the two parts.

SYNTHETICS

Fibres of chemical origin: in this family are the polyesters, the polyamides, acrylics, para-aramides, polyethylenes, elasthanes, etc.

TAEKI (FIBRE)

Synthetic fibre made of high-strength polyethylene (PEHT). It has exceptional mechanical properties, in particular against abrasion and cutting. 2nd generation TAEKI fibre is much softer than the 1st generation, thus providing greater comfort.

TANNING

Tanning transforms the raw hide into an unfinished tanned hide, making it rot-proof, receptive to finishing treatments and chemically stable.

There are different types of tanning:

- vegetable tanning (natural plant extract tannins).
- mineral tanning (usually with chromium salts).
- mixed tanning (vegetable tanning retanned with chromium).

TASLON

Rough textured fabric. The very tight crossing of its fibres makes it a robust fabric.

THERMOFUSING

Bonding operation using pressure and heat (high visibility strip on a garment, interlining in a collar...

THIMBLE

Element added inside an end loop to protect from wear generated by the friction.

THINSULATE™

Registered trade mark of 3M. It is a web of synthetic insulting non-woven combining heat, comfort and finesse. It is water repellent.

THT (HEAT-PROOF LEATHER)

Treatment used to make the leather more resistant to contact heat and reduce shrinkage on contact with a flame. The leather remains supple despite contact with a heat source.

TIL

Total Inward Leakage.

It corresponds to the performance of the filtering face piece, and is expressed in %. The lower the %, the greater the protection performance.

FFP1: 22% FFP2: 8% FFP3: 2%

TOECAP (SAFETY)

Steel, aluminium or composite shell to protect against the risk of impact and crushing of the toes. Performance is measured at 100 or 200 joules. These are the two main tests; there is also rust resistance (metal toecap), resistance to heat, to hydrocarbons, and to cold for composite toecaps.

TRIPOD

Temporary and carrying anchorage device to be used for vertical movements in confiined space.

T-SHIRT

T-shirts are cotton garments covering the torso, without a collar, most often short-sleeved, the shape of which is reminiscent of a T.

TWILL

A fabric with a «twill» weave is characterised by ribbing (diagonal relief) on the rightside of the fabric, the underside is different. «Twill» weave is a weave that resists wear and traction.

TYVEK®

The basic material in Tyvek® is polyethylene. Under the effects of pressure and heat (Flash spinning), a multitude of continuous filaments are obtained which are melt bonded to give a non-woven that is lightweight, flexible and resistant.

U

ULTRASOUNDS

Sounds of a frequency too high to be heard by humans (> 20 000Hz).

ULTRAVIOLET

Ultraviolet (UV) light is electromagnetic radiation with an intermediate wavelength between that of visible light and that of X-rays. Ultraviolet can be subdivided into near UV (380-200 nm wavelength) and extreme UV (200-10 nm). Sunburns are primarily due to UV-B. UV-A cause of sunburns during very long exposures. High intensity of UV-B (315-280 nm) are dangerous for eyes and can cause "welder's flash" or photokeratitis.



GLOSSARY

UNITS OF MEASUREMENT (YARNS)

The Tex, Decitex (Dtex), Denier (D) or Metric count (Nm) are units of measurement for yarns used to qualify their size also known as «Thread count».

UPPER

Top part of the shoe located above the sole, comprising the tongue, the collar and the guarters.

V

VALVE

Also called a flap, it provides additional comfort to the mask, by rapidly lowering its temperature at the moment of expiration and rejection of ${\rm CO}_2$. It is on disposable masks (product code V), half masks or full face masks.

VAMP

Front part at the level of the instep and on the sides.

VENTILATION

Holes located at the top of the shell to enable better evacuation of heat and perspiration.

Ventilated helmets therefore do not pass the electric test (440 VAC), except for ventilations located at the bottom of the shell, as the test is conducted by immersing the shell to half-height.

VEST

A vest is a short garment without sleeve, which covers top of the body.

VINYL

Synthetic thermoplastic polymer. It is used for disposable gloves. It is impermeable to water, alcohol and detergents, but it is not elastic.

VISIBLE (LIGHT)

Visible lightvisible spectrum or optical spectrum is the part of the electromagnetic spectrum which is visible to the human eye. There is no definite limit to the visible spectrum: the human eye adapting to light usually has maximum sensitivity at light of wavelength about 550 nm, which corresponds to a yellow-green colour.

VISUAL INSPECTION

Visual inspection of PPE of 3rd Category

VULCANISATION

Vulcanisation is a process invented by Goodyear, which consists of heating the rubber at high temperature to obtain its transformation. This process is used for dipped gloves, placed in an oven after dipping in materials.

W

WADDED (LINING)

Lining associated with a thickness of fleece to enhance the heat performance of the garment.

WARP

It is the vertical yarns of knitted fabric in opposite to horizontal yarns.

WATER REPELLENT (FABRIC)

Finish deposited on the fabric to give it the property of not letting droplets of water penetrate the fibre, but allowing them to slide off. It can be said that the drops of water are repelled. The fabric is not waterproof.

WATER REPELLENT (LEATHER)

Leather treatment using mineral or synthetic oils or fluorinated resins, to make it resistant to water penetration. This treatment gives the leather better mechanical performance for abrasion and increases the comfort (flexibility) of the glove, hence increased dexterity and lifespan.

WATERPROOF (SEAMS)

Seam on which a waterproof plastic film is applied to prevent water penetration by capillarity (passage of water by absorption of yarns and/or stitching holes) into an assembly. Assembly seam covered using thermofusing of a band of material compatible with that of the garment to prevent infiltration of water and waterproof the garment.

WEAVE

Method of interlacing warp and weft yarns in woven materials. Each weave has its own aesthetic and mechanical properties. The main fabric weaves are plain, serge, satin. The three basic knit weaves are jersey, interlock, rib. In knitting, the method of interlacing stitches is called the structure.

WEF1

These are the horizontal yarns in woven fabrics, as opposed to vertical warp yarns.

WELDING

Glasses or hood with various shades of filters suitable for welding work; disposable masks with charcoal filter, welding goggles and helmets with special tinted filter, to protect the eyes and face during welding.

WINCH

Lifting device for lifting things (eg equipment) or people, according to the tyope of product, in rescue procedure

WORK POSITIONING (SYSTEM)

A system used to maintain a user at the workstation in a given position. **WRIST CUFF**

Knitted finish of the glove wrist, to hold the glove on the wrist and prevent any penetration of dust and waste inside the glove.

7

ZIP (REVERSE STITCH)

Zip whose stitch is placed on the reverse so that only the ribbon can be seen. It is used for an aesthetic effect and to prevent friction.

ZIP (WATERTIGHT)

Reverse stitch zip covered with a PU membrane to ensure watertightness. It is used on waterproof and technical products.

INDEX

			EAD PRO	OTEOTION .			
AIR COLTAN	36	FORESTIER 2	33	M6000 A1B1E1K1	53	QUARTZ UP IV	3:
ASO CLEAR	10	FUEG0	15	M6000 A2	53	RUIZ 1	2
ASO SMOKE	10	FUJI2 CLEAR	12	M6000 P2	53	SEPANG 2	4:
BALBI 2	25	FUJI2 GRADIENT	12	M6000 P2 CLIP	53	SILVERSTONE 2	3
BARRIER	23	GALERAS	20	M6000 P3	53	SPA 3	4
BARRIER PLATE	23	GRANITE PEAK	26	M6000 PREP3	53	SPIDER REFILL FFP2	4
BASALPHA	35	GRANITE WIND	26	M6100 JUPITER	52	SPIDER REFILL FFP2W	4
BASEBALL DIAMOND V	29	HARNESS V	29	M6200 JUPITER	52	SPIDER REFILL FFP3	4
BASEBALL DIAMOND V UP	28	HEKLA	16	M6300 JUPITER	52	SPIDERMASK P2 X5	4
BASGAMMA	35	INTERLAGOS	40	M6400 JUPITER	52	SPIDERMASK P2W X5	4
BRAVA2 CLEAR	18	JUGALPHA	35	M9000 A2	51	SPIDERMASK P3 X5	4
BRAVA2 SMOKE	18	JUGGAMMA	26	M9000 A2B2E2K2	51	SUPER QUARTZ	
BRAVA2 YELLOW	18	KILIMANDJARO CLEAR	19	M9000 A2P3	51	SUZUKA 2	4
CASOUD 2	23	KILIMANDJARO CLEAR AB	19	M9000 P3	51	THUNDER CLEAR	1
CASOUD2HE	23	KILIMANDJARO SMOKE	19	M9000 A2B2E2K2P3	51	THUNDER SMOKE	
COLTAN	36	KISKA CLEAR	14	M9200 - ROTOR GALAXY	50	TOBA 2 T5	2
CONIC DISPLAY	45	KISKA SMOKE	14	M9300 - STRAP GALAXY	50	VISOR HOLDER	2
CONIC200	45	KUNLUN	17	MAGNY HELMET	42	VISOR TORIC	2
CONIC500	45	LIPARI2 CLEAR	16	MAGNY-COURS	42	VISORG	2
CONICAP01	45	LIPARI2 T5	16	MEIA CLEAR	18	VISORG MINI	2
CONICAP01BR	45	M1100	49	MEIA SMOKE	18	VISOR-HOLD MINI	2
CONICCO200	45	M1100V	49	MENTALPHA	35	VISORPC	2
CONICFIR050	44	M1195B	49	MURIA 1	21	VISORPC MINI	:
CONICMOVE01	44	M1200	49	PACAYA CLEAR	14	VULCANO2 CLEAR	
CONICMOVE01BR	44	M1200V	49	PACAYA LYVIZ	14	VULCANO2 PLUS CLEAR	
YNAMIC JUGALPHA	35	M1200VB	49	PACAYA SMOKE	14	VULCANO2 SMOKE	
EGON CLEAR	15	M1200VPLUS	48	PICO 2	25	WINTER CAP	3
EGON SMOKE	15	M1200VW	49	PITON 2 CLEAR	19	YAS MARINA	3
ILM GOGGLE	20	M1300V	48	PITON CLEAR	19	ZIRCON 1	
ILTER 11	22	M1300VB	49	PIT-STOP	38		
FILTER-IN	23	M1300V2	49	QUARTZ I	34		
ILTER-KIT	22	M6000 A1	53	QUARTZ UP III	33		
		Н	AND PRO	OTECTION			
APOLLON W733	74	NI150	AND PRO	OTECTION TOUTRAVO VE511	84	VENICUT44G3	(
	74 79				84 99	VENICUT44G3 VENICUT50	
BASF PVCC400		NI150	77	TOUTRAVO VE511			(
BASF PVCC400 CA515R	79	NI150 NI155	77 77	TOUTRAVO VE511 TP169	99	VENICUT50	(
SASF PVCC400 CA515R CA615K	79 98	NI150 NI155 NI170	77 77 77	TOUTRAVO VE511 TP169 VE630	99 76	VENICUT50 VENICUT52	6
APOLLON W733 BASF PVCC400 CA515R CA615K CP149 CC103	79 98 98	NI150 NI155 NI170 NI175	77 77 77 77	TOUTRAVO VE511 TP169 VE630 VE702	99 76 64	VENICUT50 VENICUT52 VENICUT55	6 6
BASE PVCC400 CA515R CA615K CP149 CC103	79 98 98 99	NI150 NI155 NI170 NI175 NITREX VE801	77 77 77 77 77 89	TOUTRAVO VE511 TP169 VE630 VE702 VE702GR	99 76 64 64	VENICUT50 VENICUT52 VENICUT55 VENICUT58G3	6 6 6
SASE PVCC400 CA515R CA615K CP149 CC103 DR605	79 98 98 99	NI150 NI155 NI170 NI175 NITREX VE801 NITREX VE802	77 77 77 77 77 89 88	TOUTRAVO VE511 TP169 VE630 VE702 VE702GR VE702P	99 76 64 64 65	VENICUT50 VENICUT52 VENICUT55 VENICUT58G3 VENICUT5M	6 6 6 6 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5
SASE PVCC400 CA515R CA615K CP149 DC103 DR605 SS202RP	79 98 98 99 94	NI150 NI155 NI170 NI175 NITREX VE801 NITREX VE802 NITREX VE803	77 77 77 77 77 89 88 88	TOUTRAVO VE511 TP169 VE630 VE702 VE702GR VE702P VE702PG	99 76 64 64 65	VENICUT50 VENICUT52 VENICUT55 VENICUT58G3 VENICUT5M VENITACTYL V1310	6 6 6 6
SASE PVCC400 CA515R CA615K CP149 DC103 DC8605 DS202RP DU0COLOR VE330	79 98 98 99 94 94	NI150 NI155 NI170 NI175 NITREX VE801 NITREX VE802 NITREX VE803 NITREX VE840	77 77 77 77 77 89 88 87	TOUTRAVO VE511 TP169 VE630 VE702 VE702GR VE702P VE702PG VE712GR	99 76 64 64 65 65	VENICUT50 VENICUT52 VENICUT55 VENICUT58G3 VENICUT5M VENITACTYL V1310 VENITACTYL V1371	6 6 6 6 5 5
SASF PVCC400 CA515R CA615K CP149 CC103 DR605 DS202RP DUCCOLOR VE330 CS NOCUT VV910	79 98 98 99 94 94 94	NI150 NI155 NI170 NI175 NITREX VE801 NITREX VE802 NITREX VE803 NITREX VE840 NYSOS VV904	77 77 77 77 77 89 88 87 88	TOUTRAVO VE511 TP169 VE630 VE702 VE702GR VE702P VE702PG VE712GR VE713	99 76 64 64 65 65 67 66	VENICUT50 VENICUT52 VENICUT55 VENICUT58G3 VENICUT5M VENITACTYL V1310 VENITACTYL V1371 VENITACTYL V1400B100	6 6 6 9 9
SASE PVCC400 CA515R CA615K CP149 CC103 DR605 DS202RP DUCCOLOR VE330 COS NOCUT VV910 COS OBM VV911	79 98 98 99 94 94 94 89	NI150 NI155 NI170 NI175 NITREX VE801 NITREX VE802 NITREX VE803 NITREX VE840 NYSOS VV904 PETRO VE760	77 77 77 77 77 89 88 87 88 87 88	TOUTRAVO VE511 TP169 VE630 VE702 VE702GR VE702P VE702PG VE712GR VE713 VE715	99 76 64 64 65 65 67 66	VENICUT50 VENICUT52 VENICUT55 VENICUT58G3 VENICUT5M VENITACTYL V1310 VENITACTYL V1371 VENITACTYL V1400B100 VENIZETTE VE920	6 6 6 9 9
BASE PVCC400 CA515R CA615K CP149 DC103 DR605 DS202RP DUCCOLOR VE330 EOS NOCUT VV910 EOS OBM VV911 EOS VV900	79 98 98 99 94 94 94 94 89 68	NI150 NI155 NI170 NI175 NITREX VE801 NITREX VE802 NITREX VE803 NITREX VE840 NYSOS VV904 PETRO VE760 PETRO VE766	77 77 77 77 77 89 88 87 88 72 82	TOUTRAVO VE511 TP169 VE630 VE702 VE702GR VE702P VE702PG VE712GR VE715 VE715 VE722	99 76 64 64 65 65 67 66	VENICUT50 VENICUT52 VENICUT55 VENICUT58G3 VENICUT5M VENITACTYL V1310 VENITACTYL V1371 VENITACTYL V1400B100 VENIZETTE VE920	6 6 6 9 9
ASSF PVCC400 CA515R CA615K CP149 CC103 CR605 DS202RP DUCCOLOR VE330 COS OBM VV911 COS VV900 CBN49	79 98 98 99 94 94 94 94 68 70	NI150 NI155 N1170 N1175 NITREX VE801 NITREX VE802 NITREX VE803 NITREX VE840 NYSOS VY804 PETRO VE760 PETRO VE766 PETRO VE780	77 77 77 77 77 89 88 87 88 72 82 80 82	TOUTRAVO VE511 TP169 VE630 VE702 VE702GR VE702PG VE702PG VE712GR VE713 VE715 VE722 VE726	99 76 64 64 65 65 67 66 67 67	VENICUT50 VENICUT52 VENICUT55 VENICUT58G3 VENICUT5M VENITACTYL V1310 VENITACTYL V1371 VENITACTYL V1400B100 VENIZETTE VE920	6 6 6 9 9
3ASF PVCC400 CA515R CA615K CP149	79 98 98 99 94 94 94 89 68 70 69	NI150 NI155 NI170 NI175 NI175 NITREX VE801 NITREX VE802 NITREX VE803 NITREX VE840 NYS0S W9904 PETRO VE760 PETRO VE766 PETRO VE766 PETRO VE780 PVC7327	77 77 77 77 89 88 87 88 72 82 80 82 83	TOUTRAVO VE511 TP169 VE630 VE702 VE702GR VE702P VE702PG VE712GR VE713 VE715 VE722 VE726 VE726	99 76 64 64 65 65 67 66 67 66 66	VENICUT50 VENICUT52 VENICUT55 VENICUT58G3 VENICUT5M VENITACTYL V1310 VENITACTYL V1371 VENITACTYL V1400B100 VENIZETTE VE920	6 6 6 9 9
BASE PVCC400 CA515R CA615K CP149 DC103 DR605 DS202RP DU0COLOR VE330 COS NOCUT VV910 COS VV900 DBM VV911 COS VV900 DBM49 CCN29 CP159	79 98 98 99 94 94 94 89 68 70 69 92	NI150 NI155 NI170 NI175 NITREX VE801 NITREX VE802 NITREX VE803 NITREX VE840 NYSOS W904 PETRO VE760 PETRO VE766 PETRO VE766 PVC7327 PVC7335	77 77 77 77 77 89 88 87 88 72 82 80 82 83 83	TOUTRAVO VE511 TP169 VE630 VE702 VE702GR VE702P VE702PG VE712GR VE713 VE715 VE722 VE726 VE727 VE7300R	99 76 64 64 65 65 67 66 67 67 66 66 75	VENICUT50 VENICUT52 VENICUT55 VENICUT58G3 VENICUT5M VENITACTYL V1310 VENITACTYL V1371 VENITACTYL V1400B100 VENIZETTE VE920	
BASE PVCC400 CA515R CA615K CP149 DC103 DR605 DS202RP DUCCOLOR VE330 EOS NOCUT VV910 EOS OBM VV911 EOS VV900 EBN49 FCN29 FP159 HERCULE VV750	79 98 98 99 94 94 94 89 68 70 69 92 92	NI150 NI155 NI170 NI175 NITREX VE801 NITREX VE802 NITREX VE803 NITREX VE840 NYSOS W904 PETRO VE760 PETRO VE766 PETRO VE766 PCTRO VE780 PVC7327 PVC7335 TC716	77 77 77 77 77 89 88 87 88 72 82 80 82 83 83 83	TOUTRAVO VE511 TP169 VE630 VE702 VE702GR VE702P VE702PG VE712GR VE713 VE715 VE722 VE726 VE727 VE7300R VE799	99 76 64 64 65 65 67 66 67 66 66 75	VENICUT50 VENICUT52 VENICUT55 VENICUT58G3 VENICUT5M VENITACTYL V1310 VENITACTYL V1371 VENITACTYL V1400B100 VENIZETTE VE920	6 6 6 9 9
BASE PVCC400 CA515R CA615K CP149 DC103 DR605 DS202RP DU0COLOR VE330 COS NOCUT VV910 EOS OBM VV911 EOS VV900 FBN49 FCN29	79 98 98 99 94 94 94 89 68 70 69 92 92 92 73	NI150 NI155 NI170 NI175 NITREX VE801 NITREX VE802 NITREX VE803 NITREX VE803 NITREX VE840 NYSOS W904 PETRO VE760 PETRO VE766 PETRO VE766 PTRO VE780 PVC7327 PVC7335 TC716 TER250	77 77 77 77 77 89 88 87 88 72 82 80 82 83 83 83 98	TOUTRAVO VE511 TP169 VE630 VE702 VE702GR VE702P VE702P6 VE712GR VE713 VE715 VE722 VE726 VE727 VE7300R VE799 VENICUT41	99 76 64 64 65 65 67 66 67 66 66 75 76	VENICUT50 VENICUT52 VENICUT55 VENICUT58G3 VENICUT5M VENITACTYL V1310 VENITACTYL V1371 VENITACTYL V1400B100 VENIZETTE VE920	6 6 6 6 9
SASE PVCC400 CA515R CA615K CP149 CC103 CR605 CS202RP CUCCOLOR VE330 CS0 NOCUT VV910 CS0 SDM VV911 CS0 VV900 CF0CV990 CFCV29 CFCV29 CFCV29 CFCV50 CFCCUE VV750 CFCG10	79 98 98 99 94 94 94 89 68 70 69 92 92 92 73 95	NI150 NI155 NI170 NI175 NITREX VE801 NITREX VE802 NITREX VE803 NITREX VE803 NITREX VE840 NYSOS W9904 PETRO VE760 PETRO VE766 PETRO VE766 PETRO VE780 PVC7327 PVC7335 TC716 TER250 TERK400 TOUTRAVO VE509	77 77 77 77 77 89 88 87 88 72 82 80 82 83 83 83 96 96	TOUTRAVO VE511 TP169 VE630 VE702 VE702GR VE702P VE702PG VE712GR VE715 VE722 VE722 VE726 VE727 VE7300R VE799 VENICUT41 VENICUT42	99 76 64 64 65 66 67 66 67 66 66 75 76 62	VENICUT50 VENICUT52 VENICUT55 VENICUT58G3 VENICUT5M VENITACTYL V1310 VENITACTYL V1371 VENITACTYL V1400B100 VENIZETTE VE920	6 6 6 9 9
BASE PVCC400 CA515R CA615K CP149 CC103 DR605 DS202RP DUCCOLOR VE330 COS NOCUT VV910 COS OBM VV911 COS VV900 FBN49 CPCN29 FP159 HERCULE VV750 (RPG10	79 98 98 99 94 94 94 89 68 70 69 92 92 92 73 95	NI150 NI155 NI170 NI175 NITREX VE801 NITREX VE802 NITREX VE803 NITREX VE803 NITREX VE840 NYSOS W9904 PETRO VE760 PETRO VE766 PETRO VE766 PETRO VE780 PVC7327 PVC7335 TC716 TER250 TERK400 TOUTRAVO VE509	77 77 77 77 77 89 88 87 88 72 82 80 82 83 83 83 96 96	TOUTRAVO VE511 TP169 VE630 VE702 VE702GR VE702P VE702PG VE712GR VE713 VE715 VE722 VE726 VE727 VE7300R VE799 VENICUT41 VENICUT42 VENICUT4363	99 76 64 64 65 66 67 66 67 66 66 75 76 62	VENICUT50 VENICUT52 VENICUT55 VENICUT58G3 VENICUT5M VENITACTYL V1310 VENITACTYL V1371 VENITACTYL V1400B100 VENIZETTE VE920	
BASE PVCC400 CA515R CA615K CP149 CA0103 CR605 CR	79 98 98 99 94 94 94 89 68 70 69 92 92 92 73 95 77	NI150 N1155 N1170 N1175 N1175 N1TREX VE801 NITREX VE802 NITREX VE803 NITREX VE803 NITREX VE840 NYSOS VY904 PETRO VE760 PETRO VE766 PETRO VE766 PETRO VE766 PETRO VE760 TERESO TERESO TERESO TERESO TOUTRAVO VE509	77 77 77 77 77 89 88 87 88 72 82 80 82 83 83 98 96 96 86	TOUTRAVO VE511 TP169 VE630 VE702 VE702R VE702PG VE702PG VE713 VE715 VE722 VE726 VE727 VE7300R VE799 VENICUT41 VENICUT42 VENICUT43G3	99 76 64 64 65 66 67 66 67 66 66 75 76 62 62 63	VENICUT50 VENICUT52 VENICUT55 VENICUT58G3 VENICUT5M VENITACTYL V1310 VENITACTYL V1371 VENITACTYL V1400B100 VENIZETTE VE920	
ASF PVCC400 AS515R AS615K AP149 AS605 AS60	79 98 98 99 94 94 94 89 68 70 69 92 92 92 73 95 77	NI150 N1155 N1170 N1175 N1175 N1TREX VE801 N1TREX VE802 NITREX VE803 N1TREX VE803 N1TREX VE840 NYSOS W904 PETRO VE760 PETRO VE766 PETRO VE766 PETRO VE780 PVC7327 PVC7327 PVC7335 TC716 TERESO TEREAU0 TOUTRAVO VE509 DT221 DT300	77 77 77 77 77 89 88 87 88 72 82 80 82 83 83 96 96 96 86	TOUTRAVO VE511 TP169 VE630 VE702 VE702GR VE702P VE702PG VE712GR VE713 VE715 VE722 VE726 VE727 VE7300R VE799 VENICUT41 VENICUT42 VENICUT43G3 BLE WEAR	99 76 64 64 65 65 67 66 67 76 66 66 75 76 62 62 63	VENICUT50 VENICUT52 VENICUT55 VENICUT58G3 VENICUT5M VENITACTYL V1310 VENITACTYL V1371 VENITACTYL V1400B100 VENIZETTE VE920	
ASF PVCC400 AS515R AS615K AS615K AS615K AS610103 AS605 AS202RP AUCCOLOR VE330 OS NOCUT VV910 OS OSM VV911 OS OSM VV915 AS605 BN49 CN29 P159 EERCULE VV750 PG10 II015	79 98 98 99 94 94 94 94 89 68 70 69 92 92 92 73 95 77	NI150 N1155 N1170 N1175 N1175 N1TREX VE801 NITREX VE802 NITREX VE803 NITREX VE803 NITREX VE840 NYS0S W9904 PETRO VE760 PETRO VE766 PETRO VE766 PETRO VE780 PVC7327 PVC7335 TC716 TER250 TERK400 TOUTRAVO VE509	77 77 77 77 77 89 88 87 88 72 82 80 82 83 83 98 96 86	TOUTRAVO VE511 TP169 VE630 VE702 VE702P VE702PG VE702PG VE713 VE715 VE715 VE722 VE726 VE727 VE7300R VE799 VENICUT41 VENICUT41 VENICUT42 VENICUT43G3	99 76 64 64 65 65 67 66 67 76 66 66 75 76 62 62 63	VENICUT50 VENICUT52 VENICUT55 VENICUT58G3 VENICUT5M VENITACTYL V1310 VENITACTYL V1371 VENITACTYL V1400B100 VENIZETTE VE920	
ASE PVCC400 CA515R CA615K CP149 CC103 CR605 CS202RP DUCCOLOR VE330 COS NOCUT VV910 COS VV900 BN49 CCN29 P159 LERCULE VV750 CPG10 JI015 BLOUSPO DT115	79 98 98 99 94 94 94 94 89 68 70 69 92 92 92 73 95 77	NI150 NI155 NI170 NI175 NI175 NITREX VE801 NITREX VE802 NITREX VE803 NITREX VE803 NITREX VE840 NYSOS W904 PETRO VE760 PETRO VE760 PETRO VE766 PETRO VE780 PVC7327 PVC7335 TC716 TER250 TERK400 TOUTRAVO VE509 DT221 DT300 MANCHBE	77 77 77 77 77 89 88 87 88 72 82 80 82 83 83 96 96 96 96	TOUTRAVO VE511 TP169 VE630 VE702 VE702R VE702PG VE702PG VE713 VE715 VE722 VE726 VE727 VE7300R VE799 VENICUT41 VENICUT42 VENICUT43G3 BLE WEAR P0106 P0110 SURCHPE TABP002	99 76 64 64 65 65 67 66 67 66 66 75 76 62 62 63	VENICUT50 VENICUT52 VENICUT55 VENICUT58G3 VENICUT5M VENITACTYL V1310 VENITACTYL V1371 VENITACTYL V1400B100 VENIZETTE VE920	
ASE PVCC400 CA515R CA615K CP149 CO103 CP065 CO202P COS NOCUT VV910 COS OBM VV911 COS VV900 CENTED VV900 CENTE	79 98 98 99 94 94 94 94 89 68 70 69 92 92 92 73 95 77	NI150 NI155 NI170 NI175 NI175 NITREX VE801 NITREX VE802 NITREX VE803 NITREX VE803 NITREX VE840 NYSOS W904 PETRO VE760 PETRO VE760 PETRO VE766 PETRO VE780 PVC7327 PVC7335 TC716 TER250 TERK400 TOUTRAVO VE509 DT221 DT300 MANCHBE	77 77 77 77 77 77 77 89 88 87 88 87 82 82 82 83 83 98 96 96 1SPOSAE	TOUTRAVO VE511 TP169 VE630 VE702 VE702R VE702PG VE702PG VE713 VE715 VE722 VE726 VE727 VE7300R VE799 VENICUT41 VENICUT42 VENICUT43G3 BLE WEAR P0106 P0110 SURCHPE TABP002	99 76 64 64 65 65 67 66 67 66 66 75 76 62 62 63	VENICUT50 VENICUT52 VENICUT55 VENICUT58G3 VENICUT5M VENITACTYL V1310 VENITACTYL V1371 VENITACTYL V1400B100 VENIZETTE VE920	
ASE PVCC400 CA515R CA615K CP149 OC103 OR605 OS202RP OUCCOLOR VE330 OS OBM VV911 OS OBM VV911 OS V9900 BN49 CN29 P159 BERCULE W750 PC10 DIO15	79 98 98 99 94 94 94 99 68 70 69 92 92 92 73 95 77	NI150 NI155 NI170 NI175 NI176 NITREX VE801 NITREX VE802 NITREX VE803 NITREX VE803 NITREX VE840 NYSOS W904 PETRO VE760 PETRO VE766 PETRO VE766 PETRO VE780 PVC7327 PVC7335 TC716 TER250 TERK400 TOUTRAVO VE509 D DT221 DT300 MANCHBE MASQU	77 77 77 77 77 89 88 87 88 72 82 80 82 83 83 96 96 96 96 107 104 111 111	TOUTRAVO VE511 TP169 VE630 VE702 VE702GR VE702P VE702PG VE713 VE715 VE722 VE726 VE722 VE7300R VE799 VENICUT41 VENICUT42 VENICUT43G3 BLE WEAR P0106 P0110 SURCHPE TABP002	99 76 64 64 65 67 66 67 66 66 75 76 62 62 63	VENICUT50 VENICUT55 VENICUT55 VENICUT58G3 VENICUT5M VENITACTYL V1310 VENITACTYL V1371 VENITACTYL V1400B100 VENIZETTE VE920 ZEPHIR VE210	
ASF PVCC400 AS515R AG615K AP149 C1013 RR605 IS202RP RR005 9 98 98 99 94 94 94 94 99 92 92 92 73 95 77 110 108 106 108	NI150 N1155 N1170 N1175 N1175 N1175 N1TREX VE801 NITREX VE802 NITREX VE803 NITREX VE803 NITREX VE840 NYS0S W9904 PETRO VE760 PETRO VE760 PETRO VE766 PETRO VE766 PETRO VE765 TC716 TERESO TERK400 TOUTRAVO VE509 D D D D D D D D D MANCHBE MASQU	77 77 77 77 77 77 78 89 88 87 88 87 82 80 80 82 83 83 98 96 96 86 ISPOSAE 107 104 111 111 WORK	TOUTRAVO VE511 TP169 VE630 VE702 VE702P VE702PG VE702PG VE713 VE715 VE722 VE726 VE727 VE7300R VE799 VENICUT41 VENICUT42 VENICUT43G3 BLE WEAR P0106 P0110 SURCHPE TABP002 WEAR M6VES MCCHE	99 76 64 64 65 65 67 66 67 76 66 66 75 76 62 62 63	VENICUT50 VENICUT52 VENICUT55 VENICUT58G3 VENICUT5M VENITACTYL V1310 VENITACTYL V1371 VENITACTYL V1400B100 VENIZETTE VE920 ZEPHIR VE210 PALAOS PALAOS PALAOS HV		
ASF PVCC400 AS515R AS615K AP149 AS605 AS202RP AUCCOLOR VE330 OS NORUT VV910 OS OBM VV911 OS VV900 BN49 CN29 P159 JERCULE VV750 PG10 JIO15 JUOUSPO JUT15	79 98 98 98 99 94 94 94 89 68 70 69 92 92 73 95 77 110 108 106 108	NI150 N1155 N1170 N1175 N1175 N1175 N1TREX VE801 NITREX VE802 NITREX VE803 NITREX VE803 NITREX VE840 NYSOS W9904 PETRO VE760 PETRO VE766 PETRO VE766 PETRO VE766 PETRO VE765 TC716 TER250 TER400 TOUTRAVO VE509 D D D D D D D D MANCHBE MASQU M2SAL M2SAL	77 77 77 77 77 89 88 87 88 87 88 72 82 80 82 80 82 83 83 98 96 86 ISPOSAE 107 104 111 111 WORK	TOUTRAVO VE511 TP169 VE630 VE702 VE630 VE702 VE702GR VE702P VE702PG VE713 VE715 VE715 VE722 VE726 VE727 VE7300R VE799 VENICUT41 VENICUT41 VENICUT43G3 BLE WEAR P0106 P0110 SURCHPE TABP002 WEAR M6VES MCCHE MCCOM	99 76 64 64 65 65 67 66 67 76 66 66 75 76 62 62 63 110 111 111 110 111 111 110	VENICUT50 VENICUT52 VENICUT55 VENICUT58G3 VENICUT5M VENITACTYL V1310 VENITACTYL V1371 VENITACTYL V1400B100 VENIZETTE VE920 ZEPHIR VE210 PALAOS PALAOS PALAOS HV PHPAN	
ASF PVCC400 AS515R AS615K AS615K AS615K AS615K AS615K AS616S ASC020RP ASC05C ASC020RP ASC05C ASC020RP ASC05C ASC020RP ASC05C ASC020RP ASC05C ASC020RP ASC020	79 98 98 98 99 94 94 94 89 68 70 69 92 92 92 73 95 777	NI150 N1155 N1170 N1175 N1176 N1175 N1TREX VE801 N1TREX VE802 N1TREX VE803 N1TREX VE803 N1TREX VE840 NYS0S W904 PETRO VE760 PETRO VE766 PETRO VE766 PETRO VE780 PVC7327 PVC7335 TC716 TER\$400 TOUTRAVO VE509 D D D D D D D D D D D D D	77 77 77 77 77 89 88 87 88 72 82 80 82 83 83 96 96 86 ISPOSAE 107 104 111 111 WORK	TOUTRAVO VE511 TP169 VE630 VE702 VE702GR VE702P VE702PG VE712GR VE713 VE715 VE715 VE722 VE722 VE726 VE727 VE7300R VE799 VENICUT41 VENICUT41 VENICUT41 VENICUT41 VENICUT45G3 BLE WEAR P0106 P0110 SURCHPE TABP002 WEAR M6VES MCCHE MCCOM MCPAN	99 76 64 64 65 65 67 66 66 75 76 62 62 63 110 111 111 110 111 111 110	VENICUT50 VENICUT55 VENICUT55 VENICUT58G3 VENICUT5M VENITACTYL V1310 VENITACTYL V1371 VENITACTYL V1400B100 VENIZETTE VE920 ZEPHIR VE210 PALAOS PALAOS PALAOS HV PHPAN PHVES	
BASE PVCC400 CA515R CA615R CA616R CA6	79 98 98 98 99 94 94 94 94 99 68 70 69 92 92 73 95 77 110 108 106 108	NI150 N1155 N1170 N1175 N1175 N1TREX VE801 N1TREX VE802 NITREX VE803 N1TREX VE803 N1TREX VE804 NYSOS W904 PETRO VE760 PETRO VE766 PETRO VE780 PVC7327 PVC7335 TC716 TER250 TERK400 TOUTRAVO VE509 D DT221 DT300 MANCHBE MASQU M2GIL M2PAN M2SAL M2VES M6COM	77 77 77 77 77 77 89 88 87 88 72 82 80 82 83 83 98 96 96 107 104 111 111 WORK	TOUTRAVO VE511 TP169 VE630 VE702 VE702GR VE702PG VE702PG VE712GR VE713 VE715 VE722 VE726 VE727 VE7300R VE799 VENICUT41 VENICUT42 VENICUT4363 BLE WEAR P0106 P0110 SURCHPE TABP002 TABP002 TABPO02 TABPO02 TOUTANN MCYPAN MCSAL	99 76 64 64 65 65 67 66 66 75 76 62 62 63 110 111 111 110 111 111 110	VENICUT50 VENICUT52 VENICUT55 VENICUT58G3 VENICUT5M VENITACTYL V1310 VENITACTYL V1371 VENITACTYL V1400B100 VENIZETTE VE920 ZEPHIR VE210 PALAOS PALAOS PALAOS HV PHPAN	
SASE PVCC400 CA515R CA615K CP149 CC103 CR605 CS202RP CUCCOLOR VE330 CS0 NOCUT VV910 CS0 SDM VV911 CS0 VV900 CF0CV990 CFCV29 CFCV29 CFCV29 CFCV50 CFCCUE VV750 CFCG10	79 98 98 98 99 94 94 94 89 68 70 69 92 92 92 73 95 777	NI150 N1155 N1170 N1175 N1176 N1175 N1TREX VE801 N1TREX VE802 N1TREX VE803 N1TREX VE803 N1TREX VE840 NYS0S W904 PETRO VE760 PETRO VE766 PETRO VE766 PETRO VE780 PVC7327 PVC7335 TC716 TER\$400 TOUTRAVO VE509 D D D D D D D D D D D D D	77 77 77 77 77 89 88 87 88 72 82 80 82 83 83 96 96 86 ISPOSAE 107 104 111 111 WORK	TOUTRAVO VE511 TP169 VE630 VE702 VE702GR VE702P VE702PG VE712GR VE713 VE715 VE715 VE722 VE722 VE726 VE727 VE7300R VE799 VENICUT41 VENICUT41 VENICUT41 VENICUT41 VENICUT45G3 BLE WEAR P0106 P0110 SURCHPE TABP002 WEAR M6VES MCCHE MCCOM MCPAN	99 76 64 64 65 65 67 66 66 75 76 62 62 63 110 111 111 110 111 111 110	VENICUT50 VENICUT55 VENICUT55 VENICUT58G3 VENICUT5M VENITACTYL V1310 VENITACTYL V1371 VENITACTYL V1400B100 VENIZETTE VE920 ZEPHIR VE210 PALAOS PALAOS PALAOS HV PHPAN PHVES	

INDEX

				R WEAR			
304	156	DARWIN II	149	M2PAW	154	RENO	1
305	157	DUNCAN	148	MA400	157	SACHA	1
100	156	FIDJI	153	MILTON	148	SIERRA	1
BARI	152	HELSINKI	149	RANDERS	150	STOCKTON	1
		T	ECHNIC	AL WEAR			
30RCO	169	EASYVIEW	162	MAIVE	170	SSVFR	1
BORPA	169	FIDJI HV	163	MANTEAU19A	175	TABALPV	1
BORVE	169	GILP2	163	MANTEAU19N	175	TONC3	1
CAFR1	171	GILP4	163	NORDLAND	166	TONP3	1
CAGOULE19A	175	GUETRE19A	175	OPTIMUM	162	TONV3	1
CAGOULE19N	175	GUETRE19N	175	PANTA19A	174	VESFR	1
CHEFR	172	ICEBERG	166	PANTA19N	174	VESTE19A	1
00600	173	MAICO	170	PHPAN	164	VESTE19N	1
COMBI19A	175	MAICO	171	PHVES	164		
COMBI19N	175	MAIPA	170	POLFR	172		
		F	OOT PRO	OTECTION			
22180	209	FRONTERA S3 SRC	197	MAUBEC 3 SBEA SRC	209	SAKHA S3 SRC	2
15400	209	GARGAS II ISO 18KV	204	MAZAN S1P SRC	201	SAMARA S3 SRC	2
MAZONE S5 SRA	208	GARGAS II S1P SRC	204	MIAMI S1P SRC	194	SAULT S3 SRC	2
ASTI S1P SRC	193	GOULT II S1P SRC	204	MIRAGE S1P SRC	205	SAULT S3 SRC ESD	2
AURIBEAU3 S1P SRC	185	JET2 S1 SRC	207	MONTBRUN S3 SRC	201	TW400 S3 SRC	
BRISBANE S1 SRC	205	JET2 S1P SRC	207	NAVARA S1P SRC	197	VIAGI S1P SRC ESD	2
CADEROUSSE S3 SRC	201	JET2 S3 SRC	206	OHIO3 S3 SRC	185	VIRAGE S1P SRC	
AMARO S3 SRC	197	JUMPER2 S1 SRC	207	ONTARIO S1P SRC	208	VOYAGER S1P SRC	
AROMB S1P SRC	201	JUMPER2 S1P SRC	207	PERTUIS3 S1P SRC	185	XR502 S3 SRC	
OBRA 3 S3 SRC	205	JUMPER2 S3 BUMPER SRC	206	PHOCEA S3 SRC	189		
ELTA FUSION S3 SRC	198	JUMPER2 S3 FUR HC SRC	206	PHOENIX S3 SRC	189		
SPIRIT S1P SRC	191	JUMPER2 S3 FUR SRC	206	PRISM S1P SRC	189		
SPIRIT S3 SRC	191	JUMPER2 S3 SRC	206	PROTON S1P SRC	189		
)-STAR S3 SRC	191	KORANDA S3 SRC	197	RIMINI II S1P SRC	194		
ENNEC II S1 SRC	205	LACET XL	209	ROBION3 S2 SRC	209		
ENNEC II S1P SRC	205	LANTANA S1P SRC	197	SAGA S3 SRC	186		
		F	ALL PRO	DTECTION			
	051	51.10.1.10	201	HARRA		70004	
AM022X2	251	ELARA140	231	HAR23	225	TC001	2
AM002X5	251	ELARA150	232	HAR23GILNO	225	TC002	2
AM025X2	251	ELARA160	233	HAR24	224	TC003	2
N006	247	ELARA170	232	JAGUAR HAR36TCP	220	TC004	:
N12006T	239	ELARA190	232	L0005200	245	TC005	
N12010T	239	ELARA270	231	L0007100	245	TC009 TC012	:
N12015T N201200CC	239 236	ELARA280 ELARA320	230 230	L0007150 L0007150CD	245 245	TC015	
N201200CD	236	EOLIEN HAR35	222	L0030	245	TC022	
N203200CC	237	EX021	228	L0031	245	TC029	:
N203200CD	237	EX118200A	228	L0032	245	TC044 TC105	
N208150CC	235	EX118400A	228	L0045200	244		
N208RCD	235	EX120	226	L0047100	244	TETRANCHOR LV115	
N211200CCC	236	EX220	224	L0047150	244	TR00420	
N211200CDD	236	FENNEC ANOGS10	241	L0047150AD	244	TR00430	
V213200CCC V213200CDD	237 237	FENNEC AN06320 FENNEC AN06330	241 241	L0147150 L0147150CDD	244 244	TRA101 TRA102	
			239				
N218150CCC	235	FIXBLOC AN105		LV100	242	TRA103	
N218RCDD	235	GALAGO HAR35TC	221	LV102100	243	TRA20	
N235200CD	234	GALAGO HAR35TCA	221	LV102150	243	TRA22	
N245200CDD	234	HA203	229	LV105	242	TRA30	
N315	240	HAR11	226	LV400	243	TRA32	
N017	240	HAR12	226	LV401	243	TRBAG	
	240	HAR12GIL	227	LV504A	242	TRBAG3	
N317 N319		1140 400 11410		A SERBI OR AND COLOR			
N319 NATOM HAR32	223	HAR12GILNO	227	MEDBLOC AN13006C	238		
N319		HAR12GILNO HAR12MFB HAR14	227 226 226	MEDBLOC AN13006C MINIBLOC AN102 RAH33	238 239 250		